Proceedings of

# The Fifth Annual Control Engineering Conference

# Proceedings of The Fifth Annual CONTROL ENGINEERING CONFERENCE

Held as part of the Control Engineering Conference & Exposition O'Hare Exposition Center Resement, IL May 6-8, 1986

Conference and Exhibition organized by:

Tower Conference Management Co. 331 W. Wesley St. Wheaton, IL 60187 (312) 668-8100



<sup>®</sup>Copyright 1986 by Technical Publishing Company, a company of the Dun & Bradstreet Corporation. No part of this publication may be reproduced or transmitted in any form without written permission of the copyright owner.

CONTROL ENGINEERING 1301 S. Grove Ave. Barrington, IL 60010

ISBN 0-914331-55-8

### **Foreword**

This is the proceedings of the Fifth Control Engineering Conference, sponsored by Control Engineering magazine and held in Chicago, May 6-8, 1986. The conference was accompanied by CONTROL EXPO/'86, an exhibit of instrumentation and control equipment and systems available from many of the leading suppliers to the field. This volume was distributed at the conference and includes all of the papers which were available at the preprint deadline.

This was a true control engineering meeting in that the sessions dealt with all types of instrumentation and control equipment as it is applied in all types of industries. Equal practical attention was given to process control and to machinery and manufacturing control, and to subjects ranging from local area networks to advanced strategies in process control. There was no overall theme to the conference except that emphasis was placed on areas where rapidly advancing technology is forcing the most radical changes in control engineering practice.

With this conference, the five volumes of proceedings have contributed about 2,100 pages to the control engineering literature. Every effort will be made so that future conferences continue to develop an extensive reservoir of information on the practice of modern industrial control engineering.

Byron K. Ledgerwood General Program Chairman

### TABLE OF CONTENTS

	SE	SSION I: Digital Plant Optimization Using Statistical and Model-Based Techniques	
		DOES RETROFITTING A PLANT WITH DISTRIBUTED CONTROLS SOLVE YOUR PROCESS CONTROL PROBLEMS?, George J. Bacak, Allied Corporation	
		IMPLEMENTATION OF ADVANCED CONTROL METHODS AND STATISTICAL BASED OPTIMIZATION PROCEDURES USING DISTRIBUTED CONTROL SYSTEMS, Randy C. Perry, Allied Corporation	. 1°
		A DESCRIPTION OF AN ON-LINE STATISTICAL QUALITY CONTROL PACKAGE, James R. Rushing, Jr., Setpoint, Inc.	
		INTEGRATION OF STATISTICS AND HISTORICAL DATA INTO PLANT OPTIMIZATION PROCEDURES, Dr. J. P. Kennedy, Oil Systems, Inc.	
	SE	SSION II: Vision—Off the Shelf and Into Production for Under \$50,000	
	SE	SSION III: Advances in Generating Station Control	
	SE	SSION IV: Materials Handling in the Automated Factory—Using AGV\$ and AS/RS	
		THE INTEGRATION OF AUTOMATED MATERIAL HANDLING AND FLEXIBLE MANUFACTURING SYSTEMS, Bill Penoza, Electronic Data Systems Corp., and Bharat Thacker, Universal Computer Applications	34
		THE AMRF MATERIAL HANDLING SYSTEM ARCHITECTURE, Charles R. McLean and Carl E. Wenger, Center for Manufacturing Engineering, National Bureau of Standards	40
		AUTOMATED GUIDED VEHICLE CONTROL SYSTEMS DESIGN, APPLICATION, AND SELECTION, Michael Dempsey, Portec, Inc., Automated Systems Div.	
	j	AUTOMATED LOGISTICS AND PRODUCTION SYSTEM (ALPS), David V. Lewis, IBM Corporation	58
3		MATERIAL HANDLING USING MICRO-DISTRIBUTED CONTROL IN A FLEXIBLE MANUFACTURING CELL, Sue Ellen Clifford and Janie West, Texas Instruments Industrial Systems Div.	70
		SSION V: Personal Computers as Interface Tools for Distributed Systems	
	1	THE PERSONAL COMPUTER: WHAT DO THEY DO BEST AND HOW CAN THEY BE APPLIED TO THE PROCESS INDUSTRIES?, Robert V. Faso, Taylor instruments	75
	F	THE PC WORKSTATION AS AN ON-LINE MAINTENANCE TOOL, Dana G. Russell, E. I. DuPont	81
	F	PC BASED OPERATOR INTERFACE AND OPTIMIZATION TOOLS, Domaid Holley, Fisher Controls, International	87
	١	JSING THE PC FOR PROCESS MONITORING LOOP CONFIGURATION AND SUPERVISORY CONTROL, Thomas J. Franks and James A. McMahon, Westinghouse Electric Corp., Industry Electronics Div.	
•	F	PERSONAL COMPUTERS IN DISTRIBUTED CONTROL, WHAT'S NEXT?, William K. Pollock, Optimation Technology Inc.	
0		AIVIT VI. LUCZI AIPH INPIWORS— ING STOTIS OF MAD and TOD	

\* Abstract

SE	SSION VII: Project Management for Large Control Systems	a 8
	ESTIMATING RAW MATERIAL AND CAPACITY INCENTIVES FOR PROCESS CONTROL PROJECTS, Martin Dybeck and Herman Bozenhardt, Fischer & Porter Company	100
a n	*PROJECT MANAGEMENT—COMPUTER CONTROL, Myron C. Glidewell, Texaco, Inc	e 100
	PLANNING, DEVELOPMENT AND MANAGEMENT OF PORTABLE SYSTEMS IN PROCESS CONTROL, James A. McDonald, Midwest Steel Div., National Steel Corp.	113
	*PROCESS COMPUTER SYSTEM PROJECT MANAGEMENT FOR MOBIL'S ETHYLENE PLANT, Dinesh C. Mehta, Mobil Research and Development Corp	119
SE	SSION VIII: Interfacing Control System Components with Programmable Automation	
	CIM CONTROL TECHNOLOGY IN HEAVY TRUCK OPERATIONS, Davy L. Stallings, Kentucky Truck Plant, Ford Motor Company	120
	VISION SYSTEMS AS CONTROL ELEMENTS IN PRODUCTION, Valerie C. Bolhouse, Robotic and Automation Applications Consulting Center, Ford Motor Company	122
	REAL-TIME INTEGRATION OF DEVICE CONTROL WITHIN A CELL, Jesse T. Quatse, Maxitron Corp	128
S	ESSION IX: Control Software for Personal Computers	
E . W	REAL-TIME MULTI-TASKING FOR THE PERSONAL COMPUTER IN THE INDUSTRIAL ENVIRONMENT, James J. Pinto, Action Instruments, Inc.	. 135
	SOFTWARE TOOLS FOR PROCESS CONTROL WITH PERSONAL COMPUTERS, Michael Manoff, Heuristics Inc.	. 142
S	ESSION X: How to Engineer Data Bases	
	TUTORIAL ON DATABASE ARCHITECTURES IN THE PROCESS ENVIRONMENT, Toni Lee Rudnicki, Digital Equipment Corp	145
	AVOIDING TYPICAL DATA BASE DEVELOPMENT MISTAKES, Thomas D. Good, E. I. du Pont de Nemours and Co., Inc.	. 153
ke .	AN OPERATIONS DATA BASE: THE CORNERSTONE OF A COMPUTER INTEGRATED MANUFACTURING SYSTEM, D. E. Cormack and J. E. Apple, Setpoint, Inc.	. 159
	INSTRUMENTATION SYSTEMS DESIGN USING COMPUTER DATABASES, William A. Fox, Eli Lilly & Company	. 165
S	ESSION XI: Advances in High Performance Brushless Servodrives	
	FIBER OPTICS FOR SERVOMOTOR CONTROL, Raymond F. Coulombe, EOTec Corp., and Kenneth T. Williams, Pyramid Integrated Control Systems	171
	INTEGRATED MOTION CONTROL TECHNOLOGY, William E. Seitz, Seiberco Inc	. 178
	COMPACT HIGH PERFORMANCE BRUSHLESS DC SERVO DRIVE, George B.	184

	SESSION XII: Integrated Manufacturing Systems of the Future	
8	THE POTENTIAL FOR INTEGRATED MANUFACTURING SYSTEMS, Raymond H. Ash, The Proctor & Gamble Company	193
	THE HORIZON PLANT, Renzo Dallimonti, Process Management Systems Div., Honeywell, Inc	197
	*CIM TECHNOLOGY TO MATCH USER NEEDS, Glen R. Wienkoop, Measurex Automation Systems, Inc., and Duane E. Lawton, Ford Motor Company	
	FUNCTIONAL INTEGRATION IN HIGH SPEED PRODUCTION SYSTEMS, Ronald J. DeNamur, The Procter & Gamble Company	205
9	SESSION XIII: Closing the Loop Via On-Line Statistical Quality Analysis	
9	SESSION XIV: Computer Applications in Batch Process Control	*
	FUNCTIONAL REQUIREMENTS FOR A BATCH CONTROL SYSTEM BASED ON PROGRAMMABLE CONTROLLER ARCHITECTURE, Dr. Kurt W. Kominek and Dr. John A. Arnold, Texas Instruments, Industrial Systems Div	210
	SIMULATION APPLICATIONS OF BATCH AND SEMI-CONTINUOUS PROCESSES FOR DISTRIBUTED CONTROL SYSTEMS, Martin Dybeck, Fischer & Porter, Co	217
	NEW SOFTWARE TECHNOLOGY PROVIDES INCREASED FLEXIBILITY AND DECREASED IMPLEMENTATION TIME FOR BATCH APPLICATIONS, Bjorn J.	4
	Gruenwald and H. E. Johnson, Advanced Computer Applications, Inc.	227
	MANAGEMENT INFORMATION REQUIREMENTS FOR A BATCH CONTROL SYSTEM, Alan K. Carr, Campbell Soup Co., Management Information Systems	232
	SESSION XV: Automation in Test and Inspection Applications	
	A NETWORK FOR AUTOMATED DATA COLLECTION, James N. Kellog, Intel Corp.,	235
	LABORATORY INFORMATION SYSTEMS WITH LOCAL AREA NETWORKS, Robert Megargle, Cleveland State University	243
	SESSION XVI: Better Ways of Handling Process Upsets and Alarms	/
	ALARM MANAGEMENT, Henry Marks, Honeywell, Process Management Systems Div.	249
	WHEN LESS IS MORE—ALARM ANNUNCIATION, Gilbert E. Gelineau, New Hampshire Yankee Div., Public Service Company of New Hampshire	256
0	SESSION XVII: Object Identification on the Plant Floor	
	BAR CODE SYSTEM IMPLEMENTATION ON THE PLANT FLOOR IMPLEMENTATION SCENARIO—THE PLOT THICKENS, C. Deal Moore, Arthur Young & Company	264
	AUTOMATIC IDENTIFICATION AND FIXED STATION LASER BAR CODE SCANNERS, Ralph R. Meier, Accu-Sort Systems, Inc.	269
	BAR CODES IN THE ELECTRONIC MANUFACTURING ENVIRONMENT, Joseph A. Meylor, Delco Electronics Corp., Subsidiary of General Motors	ev.
	BAR CODE VERIFICATION: KEY TO SUCCESSFUL AUTOMATIC OBJECT IDENTIFICATION SYSTEMS, Kathleen J. Parsons, RJS Enterprises, Inc.	v

SE	SSION XVIII: All and Expert Systems in Control Applications	
	INDUSTRIAL ARTIFICIAL INTELLIGENCE APPLICATIONS: EXPERT SYSTEMS FOR DIAGNOSTICS AND PROCESS PLANNING, Richard A. Herrod, Texas Instruments Inc.	284
	*AN ARCHITECTURE FOR TROUBLE-SHOOTING SYSTEMS, Gary S. Kahn, AI Kepner, and Jeff Pepper, Carnegie Group Inc	
	THE PICON EXPERT SYSTEM: PROCESS CONTROL APPLICATIONS, Robert L.  Moore, LISP Machine, Inc.	294
298	*PERFORMANCE REQUIREMENTS FOR KNOWLEDGE-BASED PROCESS-MANAGEMENT SYSTEMS, Michael Fehling and B. M. Wilber, Teknowledge, Inc	300
SE	SSION XIX: Security Problems in Computer-Based Systems	
	DESIGNING SYSTEMS WITH REGARD FOR SAFETY, SECURITY AND RELIABILITY, Robert A. Harold, SSOE, Inc.	
	SECURITY ON PROCESS CONTROL COMPUTER SYSTEMS, John A. Rose, National Steel Corp., Midwest Div.	305
SE	SSION XX: Personal Computers and Programmable Controllers Link Forces	(6)
	PERSONAL COMPUTERS, PROGRAMMABLE CONTROLLERS AND THE PHARMACEUTICAL INDUSTRY, J. L. Kissling, Soft Systems Engineering, Inc.	308
	PLC COMMUNICATIONS WITH PERSONAL COMPUTERS, James J. Pinto, Action Instruments, Inc.	316
	PC AND PLC MEET PROCESS CONTROL, Thomas M. Bode, SSOE Inc	321
	FACTORYLINK AND ITS ROLE IN FACTORY AUTOMATION, Clay Waldrop, United States Data Corp.	323
	IMPLEMENTING DIAGNOSTIC SYSTEMS WITH PERSONAL COMPUTERS AND PROGRAMMABLE CONTROLLERS, Daniel R. Calcaterra, Gould Inc., Industrial Automation Div.	3
SE	SSION XXI: Communications Requirements in the Automatic Factory	
1	COMMUNICATIONS LINK THE ELEMENTS OF THE AUTOMATIC FACTORY: A CASE STUDY, Laurence R. Simmons, Avantcom Corp.	338
SE	SSION XXII: Advanced Strategies in Process Control	
	A SURVEY OF ADVANCED DIGITAL CONTROL ALGORITHIMS AND THEIR APPLICATIONS, Thomas F. Edgar, Dept. of Chemical Engineering, University of Texas.	345
	HYPERPLANE: A CASE HISTORY, Herman Bozenhardt, Fischer & Porter Co	359
	MULTIVARIABLE CONTROL MADE EASY, Charles R. Cutler and Charles R. Johnston, DMC Corp.	364
,	GRADIENT CONTROL OF A HYDROCRACKER USING A PREDICTED TEMPERATURE PROFILE, Mark Hughes, Oil Systems, Inc.	
	EXPERIENCE IN PILOT PLANT OPERATION BY USING DIGITAL CONTROLLERS LINKED TO A PERSONAL COMPUTER, C. S. Lin and Thomas H. Tsai, Tenneco Inc., A. Wagner, Tenneco Polymers	

SESSION XXIII: Control Applications of High Performance AC Adjustable Frequency Drives	
CONTROL OF HIGH POWER VARIABLE RELUCTANCE MOTORS, David A. Torrey and Jeffrey H. Lang, Lab. for Electromagnetic and Electronic Systems, Dept. of Electrical Engineering and Computer Sciences, Massachusetts Institute of Technology	202
POOR MAN'S VECTOR CONTROL OR A USER'S GUIDE TO INDUCTION MOTOR SERVOS, Donald E. Fulton, IMEC Corp.	
SELECTION OF MOTORS FOR AC DRIVES, Alexander Kusko, Alexander Kusko, Inc	
SESSION XXIV: Automating the Design of Control Software	
THE INTELLIGENT INTEGRATION OF EXISTING ENGINEERING TOOLS, Jayashree Ramanathan, Dept. of Computer and Information Science, The Ohio State University	407
STRUCTURED ANALYSIS, NETWORKING, AND THE FUTURE, Mark Williams and Dave Emerson, Rexnord Automation	
IS THERE LIFE AFTER STRUCTURED ANALYSIS?, Peter Hruschka, GEI	421
ADA IN A MANUFACTURING ENVIRONMENT, Richard Volz, Trevor Mudge, and Arch Naylor, The Robotics Research Lab, University of Michigan, and Benjamin Brosgol, ALSYS Inc.	433
SOFTANALYST: A VEHICLE FOR SOFTWARE OPTIMIZATION AND VERIFICATION FOR EMBEDDED SYSTEMS, Ted Gary, Northwest Instrument Systems, Inc	441
SESSION XXV: Process Industry Uses of Programmable Controllers	
RECIPE DRIVEN BATCH PROCESS CONTROL USING A P.C., Robert J. Tomasetta, Automated Control Concepts, Inc., and Walter Keith, E. R. Squibb & Sons	446
PROGRAMMABLE CONTROLLER APPLICATIONS AND SELECTION CRITERIA AT A PHARMACEUTICAL MANUFACTURING FACILITY, William R. Lichtenau, Hoffman-La Roche, Inc.	449
USING PLC CONCEPTS IN THE CONTROL OF OIL FIELD FACILITIES, Dr. Roger M. Clay and Richard A. Kowalski, ARCO Oil and Gas Company	
INTERFACING A PROGRAMMABLE CONTROLLER WITH A DISTRIBUTED CONTROL SYSTEM IN AN EXISTING PLANT, Joseph LaFauci and Lydia Procyk, Merk Chemical Manufacturing Div., Merck & Co	462
A PROCESS CONTROL SYSTEM APPLICATION IN A LARGE COTTON GIN, Jon	472

# DOES RETROFITTING A PLANT WITH DISTRIBUTED CONTROLS SOLVE YOUR PROCESS CONTROL PROBLEMS?

George J. Bacak Allied Corporation Philadelphia, Pennsylvania

### **ABSTRACT**

With the emergence of distributed controls in the chemical industry, many companies have retrofitted their existing pneumatic and electronic controls in order to improve quality, increase production rates, and improve overall plant efficiency. This paper discusses the various stages that Allied phenol plant in Philadelphia underwent in order to have complete conversion from pneumatic controls to the present day distributed digital control system. In addition, the advantages and disadvantages of a distributed control system are discussed.

### INTRODUCTION

Allied's Philadelphia phenol plant has deep roots in early industrial United States history. Established in 1884 as the H. W. Jayne Company, the plant is known as one of the earliest coal chemical producers. was started on four and a half acres of land in the northeast section of Philadelphia. In 1896, it was taken over by Barrett Manufacturing Company, a midwestern coal tar roofing company. At that time, three months were required to produce ten gallons of refined phenol. Over the next several decades, the plant expanded operations to produce chemical intermediates for pharmaceuticals, explosives, dyestuffs, and the first synthetic sulfonation phenol. In 1920, the Barrett Company was incorporated into Allied Chemical & Dye Corporation. The plant's manufacturing was mainly separation and purification of coal chemicals. Over the next three decades, Allied Chemical & Dye Corporation introduced many products derived from coal tar chemicals, including phthalic anhydride and phthalate

In 1954, when Allied Chemical and Dye entered the Nylon fiber business, the first synthetic phenol unit was placed into operation.

It was based on the cumene oxidation process and had a capacity of 30 MM lbs/year. The phenol demand grew overwhelmingly in the next two decades as demand for synthetic fibers expanded in this country. Two additional phenol units were built; one in 1960 and a third in 1964. "CP" is the acronym for Cumene-Phenol process. Thus the three phenol units were known as CP #1, 2, and 3. By the early 70's, demand for the coal chemical products, which originally were the backbone of Allied Chemical were now slowing down. Obsolete units which produced xylenes, benzene, phthalic anhydride, naphthalene, nicotinic acid (Niacin), and quinoline (to mention a few) were shutdown and demolished. Thus, the only process remaining by 1979 was the cumene-phenol process. Phenol capacity was now 600 MM lbs/year, with 360 MM lbs/year of acetone, a co-product in the cumene process. Allied had come to establish itself as a world leader in phenol production. The bulk of the phenol was shipped to its Hopewell, Virginia plant which produces Nylon 6 from the phenol via caprolactam polymerization.

In the early 70's there was a major effort within the plant to develop energy conservation, pollution abatement and efficiency improvements. During the period 1979 to 1981, the plant underwent many changes, including retrofitting of old pneumatic control systems with electronic and digital controls, a far cry from the operator hand control of the 1900's.

The early industrial period in America set the pace for innovation, inventiveness, and mass production. Products were being made not in backyard laboratories or machine shops, but were being mass produced in large factories. Basics for the mass production of materials were lubricating oils and greases, dyes and pigments, leather products, and later on, rubber and plastics. Most of these basic chemicals were derived from coal, plants, oil

or animals. These basics were produced crudely; in small, privately owned businesses that tried to keep up with the large mass producing business' demand for the products. All processes were carried out batch-wise, with formulas for many batches being developed by trial and error. Early plants and factories relied on operators to manually run batches. They had to handle liquid, solid and powder reagents and solvents; some of which were quite corrosive and flammable.

Later, semi-continuous processes were developed. Control of liquid, powder and gas flow rates was accomplished by operating valves. To obtain certain conditions for reactions, heat transfer, and separation, operators had to continuously monitor the process (levels, pressures, temperatures, melting/boiling points) and manipulate key hand valves. Product specifications, no matter how crude, still had to be met. Shortly before World War II, pneumatic instrumentation was developed which provided accurate process measurements with remote indication of levels, flows, and pressures. Pneumatic controllers were developed using the already applied "servo mechanism" theory of electronics and their widespread use took off in post-World War II years. Oddly enough, pneumatic controls were being used long before a quantitative technology, existed specifically for pneumatics.

The 40's and 50's gave way to electronic instrumentation. Allied's phenol plant had the early electronic controls on compressors and fans. Most of the early electronics were used in relays for switching and alarming. Up until the mid-70's, pneumatic controls dominated, mainly due to their simplicity, reliability and ease of repair. In 1976, a new carbon adsorber vent system was installed at the Philadelphia plant with an electronic sequencer. The sequencer cycled 15 motor-driven valves on the adsorbers. The sequencer panel had a rat's nest of ribbon cable connectors which caused many headaches in tracing down electrical problems. The panel had a lighted display with ability to step through the various sequencing. Programming was done by the manufacturer. Some field problems were encountered with the motor-driven valves not going to their limits and thus throwing off the sequencing.

In 1980, a new caustic soda make-up system was installed with electronic controls. This was the first electronic system in the plant to do multi-loop PID-type control. The low cost and ease of maintenance, accuracy of measurement (electronic transmitters), and no freeze-ups of pneumatic instrument lines were the big pluses of this new system. Later in the same year a larger system was installed on a rebuilt wastewater treatment

facility within the plant. The checkout, start-up and operation of this system went very well. Most of the problems encountered were field transmitter freeze-ups and wiring to/from intrinsic safety barrier panels.

In 1981 the plant installed additional sequencers on the CP #2 and CP #3 carbon adsorber vent system. Up until this point, field operators would manually swing valves at prescribed intervals. The new sequencers turned out to be an even more reliable system than the first. The new controller was programmed with a portable programming panel. Sequence programming was easily done by Allied engineers using ladder logic. Problems encountered were with limit switches on the valves due to their "freeze-ups". This problem was resolved by replacing all of the limit switches on the valves with proximity or magnetic types.

Also in 1981, the plant had made the decision to go to a distributed digital control system (DCS) as a trial on a CP #3 distillation column. It had installed a DCS unit which handled up to 16 control loops (8 primary and 8 auxiliary). The existing pneumatic system was retained as a back-up control in the event of failure of the DCS unit. Field switchover of air supply was required to go from pneumatic to digital. unit could be programmed by a menu-type configuration of control loops. A typical digital computer control loop is shown in Figure 1.2 Data base was stored on a cassette & and loop alarms were logged on a printer. Most of the maintenance was performed by vendor service people. Internal filters and the Mylar keyboard needed replacement. On a semi-regular frequency, the screen would go blank and required controlling on the back-up analog controllers. The reason for the screen blanking out was not determined. However, the system did have to be rebooted in order to restore the digital control.

### PLANT ACCIDENT

During the months of January and February of 1982, the phenol business, as well as business in general, was slow. Partial plant shutdowns were contemplated. Then on March 9, 1982 a fire occurred in the CP #1 operating unit. The fire totally engulfed CP #1 and wind carried it into CP #3, causing partial (mostly instrumentation) damage to the unit. CP #2 and the central plant Boilerhouse sustained only minor damage. However, the main process lines and the utilities (250 lb, 50 lb, 10 lb steam, cooling water, fire water, electrical power-lines, and instrument air lines) going into and out of these areas were .severed, rendering CP #2 and the Boilerhouse inoperable. There was extensive damage to safety systems which included spring-

loaded manheads, relief valves, rupture discs, sprinkler systems, fire alarms, communication systems (phones and public address). Product loss by burning, vaporization and contamination was great.

### RECONSTRUCTION

The plant operations came to a dead stop. What was to become of the plant? Could it ever be restarted? Would it ever be restarted? These and many more questions were on the minds of plant employees as well as Allied management. A short term question was asked: what needed to be done in a short time to segregate CP #2 from the damaged areas in order that it may be restarted? The plant was unique in that it had three phenol units all fed by two large reactors, both of which were not damaged. Also, the wastewater treatment facility, the residue handling area, the raw material unloading and finished product loading facilities had sustained little or no damage. Therefore, it was possible to isolate CP #2 from the damaged areas.

The decision was made to restart CP #2. A massive effort was made to isolate the unit to form a "new" plant. Construction of and training on the rebuilt unit was accomplished in record time. By mid-April, 250 lb steam was produced by use of a leased package boiler and CP #2 was restarted.

During the first several months after the fire, the decision to rebuild the partially damaged unit, CP #3, was made. C. E. Lummus was chosen as the design firm which was to provide engineering services to meet Allied's needs. The muscle was provided by the plant maintenance force. The massive decontamination and demolition effort of CP #1 that was required went on side by side with the reconstruction of CP #3. Several criteria were to be met as decided by Allied management. They were 1) the rebuilt units were to have the long range capacity of the pre-fire plant, 2) the rebuilt CP #3 was to have the safest operation possible with adequate automatic shutdown of key equipment, and 3) the rebuilt CP #3 would have state-of-art controls, i.e., a distributed digital control system.

Evaluation of various DDC vendors was made. Foxboro was chosen as the system due to its cost, availability of equipment to start the unit up by November, 1983, and specific features needed by Allied. Some of the features Allied was looking for in the new DDC system were 1) redundant indication and controls required since there was no pneumatic back-up left, 2) redundant power supply to main and back-up controls, 3) redundant processors for viewing the plant through CRT's, 4) intrinsic safety required due to flammable and hazardous chemicals in the plant, 5) programmable control logic needed to handle the complex automatic shutdown of key equipment, 6) a centralized

control room from which supervisors can direct almost every operating task, and most importantly 7) a reliable system which would have a high percentage of on-line time so vital to a newly restarted plant.

### CP #3 START-UP AND STAGING

During the period of April, 1982 to June, 1983 CP#3 reconstruction was done side by side with demolition of the destroyed CP#I. All the destroyed and damaged equipment had to be accounted for by plant management. This was a tremendous task for those concerned but the most difficult part fell on the unit supervisor's shoulders. Since he knew the unit the best, he had to verify not only all the equipment that was in it but also sample, categorize, and mark each process line for decontamination. At the same time. plant, division, and Lummus people developed a strategy to design, reconstruct, and restart CP #3. At this stage, planning was very important. All control valves and sensors were taken from the unit, cleaned, checked out, rebuilt, reinstalled, or replaced. Process flow diagrams, P&I diagrams. structural, piping and electrical drawings were developed. Piece by piece the unit was reshaped.

The massive wiring and installation of the DDC system was accomplished by electrical contractors, Foxboro service people and plant maintenance people. Installation of the Foxboro SPECTRUM system was begun. The plant was to operate via VIDEOSPECs display-based microprocessors) interfaced with UCM's (Unit Control Modules - the digital controllers), UFM's (Universal Multiplexers - discrete or analog only), and UlO's (Universal Input/Output devices). A redundant system for control and monitoring was installed as shown in Figure 2. Also, a FOX 1/A supervisory computer was installed for the purposes of process graphic display, management reporting, back-up control and monitoring, and potential for "advanced" control. The new DDC system was configured for approximately 150 control loops and 500 indicating loops in the CP #3 operating unit. The UCM's are the heart of the system. Each UCM has the capability of handling up to a maximum of 60 analog inputs and/or outputs, or a maximum of 30 control loops (15 inputs, 15 outputs), or a maximum of 240 discrete inputs and/or outputs. Field signals to the UCM may be 0-20 mA or 4-20 mA (linear or square root), RTD, or thermocouple. In addition, the UCM is capable of having 60 "blocks" configured for control logic. There are 23 different types of blocks and they may be arranged to perform various types of control (see Figure 3). UFM's were installed due to the enormous input capacity; a maximum of 96 inputs per nest with a maximum of 8 nests,

or 768 inputs per device. The UIO's can each handle a maximum of 60 analog inputs or outputs, or 60 pulse counters, of 240 digital inputs or outputs, or any combination of the above. The Fox 1/A computer can address almost any parameter on the UCM's and all 1/O on the UIO's and inputs on the UFM's. Parameters for which it cannot address directly are pulled in or written to via special FORTRAN programs run on the FOX 1/A.

As it can be seen, it was a huge task to design, configure, document and implement this system. This task fell on the shoulders of only a few people. Foxboro hardware and software experts did aid in setting up the new system. However, there was still much trial and error in configuring the system, and even more in starting it up. From detailed P&I diagrams and flow diagrams came new and rebuilt piping and equipment. Also, from these diagrams came new control logic in the form of capture loop drawings. From experienced managers, engineers, and foremen came new, detailed procedures on equipment start-ups, shutdowns and normal operation.

There was a new outlook on documentation. A new equipment numbering system was instituted. Display and configuration documentation for the SPECTRUM system was well kept. Historical collection and trending of data were to be kept on floppy disk storage for 31 days. Alarm printouts were elaborate highlighting such things as when high and low control limits were reached, when loops were disabled from alarming and when "critical" loops were a problem. Supervisory computer capabilities included monitoring when loops were put in manual from the automatic control mode and monitoring the "health" of SPECTRUM.

With process and computer equipment installation nearing completion, training of foremen and operators was begun. conducted both out of and in-plant training courses. The Operations department training group put together a comprehensive program to take operating people wary of a "computer system" to the point of feeling comfortable that the buttons they pushed on the VIDEOSPECs actually caused changes to valves (like the pneumatic systems they had been used to). Training which had started as early as the summer of 1982, was winding down. As equipment was furned over to Operations by construction, various pressure and loop checks had to be performed. As far as instrumentation was concerned, construction had performed the basic loop checks which verified the integrity of sensor to the transmitter, to the I/P, and to the digital I/O device. The final check verified that the VIDEOSPEC was reading the signal and was able to send an output to the field to move the valve to complete the test of the loop. The checkouts of the loops and software continued on into April

and May, 1983. Check-outs were made of the redundant controls and indicators, as well as the redundant VIDEOSPECs. Also, preliminary checkouts of the automatic shutdown and interlock systems were performed.

In June, 1983 the control system was nearly complete. The final stage was to introduce water into the processing equipment in order to determine pumping problems, perform some loop tuning, detect leaks, and most of all to get operators familiar with the new distributed digital control system.

Chemicals were first introduced into the rebuilt unit in July, the true test of the new control system. The unit was started up in stages, and DDC system problems were corrected. Hardware problems were minor during this period, but included items such as faulty I/P transducers, out-of-calibration transmitters, incorrect signal conditioning on I/O on the UCMs and VIDEOSPECs, and faulty operator keyboards to name a few. The start-up of CP #3 was successfully accomplished by September, 1983, two months ahead of schedule. The impact of the DDC system on the plant was just starting to be felt. The new control system had greater accuracy of measurement and an ease of tuning of loops which in the past were considered "problems" on the pneumatic system. Figure 4 shows an old pneumatic controller strip chart versus the digital trend of the same control loop. The elaborate safety shutdown system had greatly increased the ease with which the system was shutdown. The unit would shutdown and immediately alert the operators to the occurrence and cause via CRT display and alarm printout. The overall "health" of the DDC system was easily monitored by the systems' engineers and system problems were dealt with in an efficient manner. The time required to analyze and solve a process or control problem was reduced. This was due in large part to the ability to segregate and recombine indicating and/or control loops into a logical display in order to get a better picture as to what was happening with the process. However, the time required to actually manipulate a control loop(s), i.e., change setpoint or output, or put the controller in manual or automatic mode, is greater for several reasons. One reason is that Foxboro VIDEOSPECs offer only a ramping change in setpoints or outputs. Another reason is that with any DDC system, the operator can access only one loop at a time per CRT, even though he may be able to manipulate more than one loop at a time, as he did with the pneumatic controllers. Figure 5 shows the VIDEOSPEC Area-Group Loop display hierarchy for operator control.3

### RETROFITTING THE REST OF THE PLANT

In Fall of 1983, the decision was made to retrofit CP #2 and the Boilerhouse with Foxboro SPECTRUM equipment for digital control of the unit. Installing DDC on an operating unit required a different type of strategic planning than did the rebuilt CP #3. The unit had to be staged; initially retrofit two distillation columns (the first two in the train) in the existing CP #2 control room, then retrofit two off-line reactors in the same control room, then retrofit the rest of the reactor section and distillation train, including the wastewater treatment facility with DDC. By April and May, 1984, the two stills and the two reactors were done, respectively, "on the fly". Operations took a short shutdown, retrofitted the equipment, loop checked and restarted with two VIDEOSPEC CRTs located in the existing CP #2 control room. The rest of the unit, including the wastewater facility, was retrofitted during the unit's annual maintenance turnaround in June, 1984. Before the turnaround, the wiring for CP #2 DDC was made to the main control room in order that unit control operations be centralized. By mid-June, the entire CP #2 unit was restarted with the Foxboro SPECTRUM system. One major problem experienced with the retrofit of CP #2 was the relocation of many transmitters and transducers due to space limitations in the unit. A second problem was in integrating the new DDC wiring into the existing (originally installed) electronic controls system wiring of the wastewater facility. Third was the critical coordination of various staging activities between operations, maintenance, project and process engineering, and outside construction groups. A final and difficult task to be accomplished was the training of operators and foremen on the operation of CP #2 on DDC.

In July, 1984, a new VIDEOSPEC system had arrived which was to eventually contain CP #3 controls. These new bays of VIDEOSPECs (type IVs) would have the display and configuration transferred over from the older type VIDEOSPECs (type IIIs) to make room for the Boilerhouse retrofit. By Fall, 1984, through various shutdowns and turnarounds of the three individual boilers, the conversion of the Boilerhouse from pneumatic to an advanced three-level boiler control system was completed. However, not all of the Boilerhouse control and monitoring functions had been transferred to the SPECTRUM system. The boiler safety shutdown system, i.e., flame safeguard, was kept as a series of relays. To monitor the high-speed relays, a sequential events recorder was installed which can monitor and record inputs at a 1 millisecond scan rate. In general, the staging problems of the Boilerhouse operation were similar to those of CP #2. However, one difference was that due to time constraints a large part of the design and implementation of the Boilerhouse DDC configuration was left up to the Foxboro Company. CP #3 and CP #2 configuration was done by Lummus and Allied Fibers Engineering with extensive input from operations and systems engineers. Also, some of the Boilerhouse retrofitting problems were associated with the method to expedite, coordinate and plan which resulted in improper wiring/grounding and incorrect configuration. These caused several "unexplained" boiler shutdowns which were investigated and resolved.

### CONTROL SYSTEM MAINTENANCE

From the first day a DDC system is installed, it requires a special kind of maintenance different than that of a pneumatic system. Most of what goes wrong with a DDC system is electronic by virtue of the fact that it is comprised mostly of printed circuit boards, I/O nests and busses, and power supplies. The maintenance group must learn the basic hardware if it is installing the DDC system. However, the more complicated troubleshooting and repair should be left to the hardware vendor or reputable repair service through a service contract. Foxboro service personnel undergo regular training sessions in order to keep up with the latest hardware on the market and software revisions.

At the Allied plant in Philadelphia, the preventive maintenance by Foxboro has been worthwhile. The size of a DDC system dictates the cost of the yearly service contract. Foxboro services run in excess of \$100,000 for maintenance on 6 VIDEOSPEC processors with 13 CRTs, 17 UCMs, 8 UIOs, 2 UFMs, the FOX I/A, LINKPORTS, LINK CONTROL STATIONS (LCS), the data highways, and several alarm printers and typers. Other peripherals such as the TEKTRONIX video copiers, the UPS (uninterruptible Power Supply) system, and the KIDDE Halon fire detection and extinguishing system, are maintained by the respective outside service groups. To date, there has not been any unscheduled downtime of the DDC system.

### NEW OUTLOOK ON THE CONTROL SYSTEM

Until the beginning of last year only a small portion of time and effort was devoted to making the utmost of the DDC system. At that time, a controls group was organized to begin identifying individual control problems and started developing control schemes to better control the plant. Even prior to the formation of the controls group, a series reactor train level control scheme was developed in order to steady out variations in levels. The steady levels which resulted when the scheme was implemented led to operation of the reactors at higher levels, thus producing higher reaction yields. To date, this one scheme has saved over several million dollars.

Since then, the controls group has designed and implemented advanced control schemes for both distillation trains and has developed a statistical testing of distillation columns to

statistical testing of distillation columns to determine their optimum operating conditions. This statistical testing procedure is the topic of another paper to follow.

One other advantage of a DDC system is easy implementation of statistical process/quality control (SPC/SQC). Also, heat (or steam) and material balances may be easily performed. However, these balances are only as good as the accuracy of the metered flows, temperatures, pressures, and analyses. Both balances and statistical calculations may be performed on the supervisory computer with FORTRAN programs.

### CONCLUSIONS

In retrospect, a DDC system can definitely monitor and control a plant better than a pneumatic system. In summary, a comparison of a pneumatic and a digital control system is shown in Figure 6. A well designed and installed DDC system can immensely benefit a plant by saving energy, improving yields, and increasing production rates. The better process control, the steadier operation will be the end result with a minimum of downtime.

### REFERENCES

- Buckley, Page S., "Techniques of Process Control", John Wiley & Sons, Inc., N.Y., 1964.
- Deshpande, Pradeep B. and Ash, Raymond H., "Elements of Computer Process Control with Advanced Control Applications:, ISA, 1981.
- "Display Hierarchy", Fig. 2-1, Foxboro VIDEOSPEC Manual, p. 2-2.

FIGURE 1
TYPICAL COMPUTER CONTROL SYSTEM




FIGURE 2
FOXBORO SPECTRUM SYSTEM FOR CP#3




FIGURE 3

### UCM BLOCK TYPES

	UCM BLOCK TYPES		, Fg	
CONTROLLERS		DYNAMIC COMP	ENSATION	
PID PID-NONL DGAP INT	PROPORTIONAL-INTEGRAL-DERIVATIVE NON-LINEAR (PID WITH EXTENDER BLOCK) DIFFERENTIAL GAP INTEGRAL	LLAG DTIM	LEAD/LAG DEAD TIME	
INPUT AND CO	<u>DNVERSION</u>	COMPUTATIONAL		
AIN PCIN AMB ACUM CHAR ALRM	ANALOG INPUT PULSE COUNTER INPUT AUTO MANUAL AND BIAS ACCUMULATOR LINEAR CHARACTERIZER ALRM	CALC SUM RTIO	CALCULATION SUMMER RATIO	
Logic		LIMING AND S	ELECTION	
DIN DOUT SEQ GATE	DIGITAL INPUT DIGITAL OUTPUT SEQUENCER GATE	TIMR SSEL SWCH RAMP	TIMER SIGNAL SELECTOR SWITCH RAMP	

FIGURE 4

CUMENE RECOVERY COLUMN OVERHEADS FLOW - PNEUMATIC STRIP CHART VS.

