

DEPOSIT CHARACTERIZATION,
MEASUREMENTS, AND MODELING

Edited by

Francesco Coletti, PhD Geoffrey F. Hewitt, PhD



CRUDE OIL FOULING

Deposit Characterization, Measurements, and Modeling

Edited by

FRANCESCO COLETTI, PhD

Hexxcell Ltd, London, UK

GE

hD

Imp



Amsterdam • Boston • Heidelberg • London New York • Oxford • Paris • San Diego San Francisco • Singapore • Sydney • Tokyo

Gulf Professional Publishing is an imprint of Elsevier



Gulf Professional Publishing is an imprint of Elsevier 225 Wyman Street, Waltham, MA 02451, USA The Boulevard, Langford Lane, Kidlington, Oxford, OX5 1GB, UK

Copyright © 2015 Elsevier Inc. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or any information storage and retrieval system, without permission in writing from the publisher. Details on how to seek permission, further information about the Publisher's permissions policies and our arrangement with organizations such as the Copyright Clearance Center and the Copyright Licensing Agency, can be found at our website: www.elsevier.com/permissions

This book and the individual contributions contained in it are protected under copyright by the Publisher (other than as may be noted herein).

Notices

Knowledge and best practice in this field are constantly changing. As new research and experience broaden our understanding, changes in research methods, professional practices, or medical treatment may become necessary.

Practitioners and researchers must always rely on their own experience and knowledge in evaluating and using any information, methods, compounds, or experiments described herein. In using such information or methods they should be mindful of their own safety and the safety of others, including parties for whom they have a professional responsibility.

To the fullest extent of the law, neither the Publisher nor the authors, contributors, or editors, assume any liability for any injury and/or damage to persons or property as a matter of products liability, negligence or otherwise, or from any use or operation of any methods, products, instructions, or ideas contained in the material herein.

ISBN: 978-0-12-801256-7

Library of Congress Cataloging-in-Publication Data

A catalog record for this book is available from the Library of Congress

British Library Cataloguing in Publication Data

A catalogue record for this book is available from the British Library

For information on all Gulf Professional Publishing visit our website at http://store.elsevier.com

Typeset by TNQ Books and Journals www.tnq.co.in

This book has been manufactured using Print On Demand technology.





Working together to grow libraries in developing countries

www.elsevier.com • www.bookaid.org

CRUDE OIL FOULING

LIST OF CONTRIBUTORS

Dr. John Chew

Lecturer in Chemical Engineering, University of Bath, UK

Dr. Francesco Coletti

Chief Technology Officer, Hexxcell Ltd, UK

Prof. Barry D. Crittenden

Professor of Chemical Engineering, University of Bath, UK

Dr. Andrew J. Haslam

Research Fellow, Imperial College London, UK

Prof. Geoffrey F. Hewitt

Professor of Chemical Engineering, Imperial College London, UK

Prof. George Jackson

Professor of Chemical Physics, Imperial College London, UK

Dr. Guadalupe Jimenez-Serratos

Research Associate, Imperial College London, UK

Dr. Himanshu M. Joshi

Principal Heat Transfer Engineer, Shell Global Solutions (US), Inc., USA

Prof. Sergei G. Kazarian

Professor of Physical Chemistry, Imperial College London, UK

Prof. Sandro Macchietto

Professor of Process Systems Engineering, Imperial College London, UK

Prof. Omar K. Matar

Professor of Fluid Mechanics, Imperial College London, UK

Dr. Marcos Millan-Agorio

Reader in Chemical Engineering, Imperial College London, UK

Prof. Erich A. Müller

Professor of Thermodynamics, Imperial College London, UK

Dr. Khairul Rostani

CO2 Management R&D, PETRONAS Research Sdn Bhd, Malaysia

Dr. Daniele Sileri

Senior Business Consultant, Misys, Hong Kong

Dr. Feng H. Tay

Head of R&D, EliteTNS, Singapore

Dr. Silvia Venditti

R&D Engineer, Resource Centre for Environmental Technologies, Luxembourg

viii List of Contributors

Dr. Junfeng Yang

Research Associate, Imperial College London, UK

Dr. Mengyan Yang

Research Associate, University of Bath, UK

PREFACE

Nearly every gallon (or liter!) of fuel, which is used in transport vehicles (cars, trucks, trains, airplanes, etc.), is derived from oil that is extracted in the crude state from oil wells and is then processed in an oil refinery to yield the required transport fuel (gasoline, diesel, kerosene, etc.). The first task in the refinery is to separate these useful fuels from the crude oil by the process of distillation in which the components of the oil are separated on the basis of their volatility. Of course, the components of crude oil, which are of volatility too low to allow them to be used as fuels, are also separated in the distillation process and can be either directly used (for example, as lubricating or fuel oils) or can be chemically converted to more volatile materials.

In the distillation of crude oils, the separated components are hot and it is important to use this heat in a series of heat exchangers (the "crude preheat train") in which heat is transferred from the separated streams into the incoming crude oil. Unfortunately, these heat exchangers are subject to fouling, which reduces the amount of heat they exchange and increases the amount of extra heat that needs to be added (usually through an oil-fired furnace immediately preceding the distillation column). Fouling the exchangers also leads to higher pressure losses (and hence an increased pumping power requirement) and, of course, the exchangers need to be periodically cleaned. Altogether, fouling in the crude preheat train leads to an enormous cost penalty (of the order of 1 billion dollars per annum in the United States alone).

The economic penalties associated with crude oil fouling led the UK Engineering and Physical Sciences Research Council (EPSRC) to finance a research program on crude oil fouling (CROF), which was started in 2006. This three-year program was carried out as a collaboration among Imperial College (London), Bath University, and Cambridge University. Industrial companies representing about 70% of the world's refining capacity also participated through a special Working Party. The work comprised experimental measurements of fouling, analytical modeling, and the development of techniques for the analysis and characterization of crude oils and deposits.

As a result of this research project, a step change has been possible in the characterization and modeling of crude oil fouling and it is clearly important to capture the impact of the work in a published form. Although a number

Preface

of articles have been published on various aspects of the work, it was considered important to create a unified and structured presentation of the subject, and this is the objective of the present book.

Although the work described here is focused on crude oil fouling in refinery heat exchangers, most of the experimental and modeling techniques can be either directly applied or readily adapted to address to other types of crude oil fouling. We believe that engineers and researchers involved with waxing in pipelines, fouling of offshore equipment or other downstream units will also find the science and applications contained in the book useful.

Though considerable progress has been made in the work summarized here, it seems safe to predict that crude oil fouling will-remain an important focus for research for many years to come!

G.F. Hewitt & F. Coletti

NOMENCLATURE

G

Free energy (kJ mol⁻¹)

ROMANS

```
Curvature of annulus (m)
a
           Material-specific constant (-)
           Various fouling model constants
a_1,..a_n
A
           Pre-exponential factor for chemical reaction fouling (m<sup>2</sup> K J<sup>-1</sup>)
A
A
           Pre-exponential factor for aging model (s<sup>-1</sup>)
           Cross-sectional area for flow (m2)
A_{flow}
B_c
           Baffle cut (%)
           Biot number for fouling (-)
Bi_f
C
           Phase volume fraction or species concentration (-)
Ca
           Capillary number (-)
C_d
           Discharge coefficient (-)
C_f
           Friction factor (-)
           Constant of integration (-)
C
           Concentration in the bulk (kg m<sup>-3</sup>)
Cb
           Foulant concentration (kg m<sup>-3</sup>)
Cf
           Concentration of precursors (kg m<sup>-3</sup>)
c_p
           Specific heat capacity at constant pressure (J kg<sup>-1</sup> K<sup>-1</sup>)
Cp
           Concentration at the surface (kg m<sup>-3</sup>)
Cs
           Concentration of reactants (kg m<sup>-3</sup>)
c_r
D
           Diameter (m)
D_d
           Deposit diffusion coefficient (m<sup>2</sup> s<sup>-1</sup>)
           Hydraulic diameter of annulus (m)
D_H
           Inner diameter (m)
D_i
Do
           Outer diameter (m)
Dott
           Tube bundle diameter (m)
D_S
           Shell inner diameter (m)
D,
           Inverse of diffusion coefficient (s m<sup>-2</sup>)
           Asphaltene phase mole fraction (-)
d
d_t
           Inner diameter of nozzle throat (m)
druhe
           Inner diameter of tube connected to nozzle (m)
dir
           Direction of flow (-)
E_a
           Activation energy ageing reaction (J mol<sup>-1</sup>)
           Activation energy fouling reaction (J mol-1)
E_f
e
           Roughness (m)
           Mathematical constant 2.71828 (-)
           Initial roughness value (m)
e °
           Final roughness value (m)
```

```
Enthalpy (kJ mol<sup>-1</sup>)
H
H
            Channel height (m)
H_{D}
            Heptane dilution value (-)
            Precipitation enthalpy (kJ mol<sup>-1</sup>)
\Delta H_{n}
h
            Distance between nozzle and deposit (m)
            Distance between nozzle and substrate (m)
h_0
            Heat transfer coefficient for ideal cross-flow (W m<sup>-2</sup> K<sup>-1</sup>)
hid
I_N
            Insolubility number (-)
            Heat transfer coefficient correction factor (-)
J
J
            Mass flux from the oil phase to fouling phase (kg m<sup>-2</sup>)
K
            Equilibrium coefficient (-)
K_0
            Equilibrium constant at precipitation temperature (-)
k
            Order of reaction
k1
            Growth rate constant (s<sup>-1</sup>)
            Removal rate constant (s<sup>-1</sup>)
k2
            Roughness dynamics model constant (-)
k_a
            Thermal conductivity of deposit (W m<sup>-1</sup> K<sup>-1</sup>)
kf
            Mass transfer coefficient (m s<sup>-1</sup>)
k_m
            Rate constant of energy barrier (m s<sup>-1</sup>)
k.
            Ageing rate (s<sup>-1</sup>)
k_t
l_e
            Length of element (m)
leff
            Effective length of tube connect to nozzle (m)
L
            Tube length (m)
L_{hc}
            Central baffle spacing (m)
Lhi
            Inlet baffle spacing (m)
Lho
            Outlet baffle spacing (m)
L_{tv}
            Tube pitch (m)
            Number of moles present for each phase (mol)
L_X
M
            Mass (kg)
\dot{M}
            Mass flow rate (kg s<sup>-1</sup>)
Ma
            Mass rate of deposition (kg s<sup>-1</sup>)
            Mass rate of fouling removal (kg s<sup>-1</sup>)
M.
MW
            Molecular weight (kg mol<sup>-1</sup>)
            Characteristic value of mobility (s kg<sup>-1</sup>)
M.
            Mass flux (kg m^{-2} s^{-1})
m
            Measured gauging mass flow rate (kg s<sup>-1</sup>)
m_{q}
            Normal vector (-)
n
N
            Total number of measurements (-)
Nh
            Number of baffles (-)
            Number of tube-side pass per shell (-)
N_p
Ns
            Number of shells per unit (-)
NSS
            Number of sealing strip pairs (-)
            Total number of tubes (-)
N_{t}
Nu
            Nusselt number (-)
NV
            Number of measurements (-)
P, p
            Pressure (Pa)
P
            Wetted perimeter (m)
```

```
P
           Probability (-)
Pe
           Peclet number (-)
           Pressure drop between station i and j (Pa)
\Delta P_{ii}
Pr
           Prandtl number (-)
           Tube-side inner perimeter (m)
P_t
P_x
           Pitch ratio (-)
9"
           Heat flux (W m<sup>-2</sup>)
Q
           Heat duty (W)
           Radial coordinate (m)
r
           Reaction rate (mol m<sup>-3</sup> s<sup>-1</sup>)
*
           Dimensionless radial coordinate (-)
r
           Density ratio (-)
rd
           Conductivity ratio (-)
rk
           Reaction i (-)
r_i
           Viscosity ratio (-)
r_{\nu}
           Radius (m)
R
           Fouling resistance (m<sup>2</sup> K W<sup>-1</sup>)
R_f
            Average fouling resistance (m2 K W-1)
\overline{R}_f
            Universal gas constant (J kg<sup>-1</sup> mol<sup>-1</sup>)
R_{\varrho}
Re
           Reynolds number (-)
            Reynolds number in the annulus (-)
Rea
            Heat transfer surface (m2)
S
            Entropy (kJ mol<sup>-1</sup> K<sup>-1</sup>)
S
            Solubility blending number (-)
SBN
T
            Temperature (K)
T_b
            Bulk temperature (K)
T_f
            Film temperature (K)
\hat{T}_f
            Modified film temperature (K)
T_{in}
            Inlet flow temperature (K)
T_p
            Precipitation temperature (K)
T_r
            Reduced temperature (-)
T_s
            Surface temperature (K)
T_{s0}
            Initial surface temperature (K)
Tst
            Surface temperature at time t (K)
T_w
            Wall surface temperature (K)
T_{wh}
            Thermocouple temperature (K)
T_{wm}
            Thermocouple temperature (K)
T_{ws}
            Thermocouple temperature (K)
\Delta T_e
            Temperature increase of element (K)
            Time (s)
            Time when \theta is half its maximum value (s)
to.5
            Ageing time (s)
tage
            Overall heat transfer coefficient (W m<sup>-2</sup> K<sup>-1</sup>)
U
            Velocity vector (-)
u
            Mean fluid velocity in the tube (m s<sup>-1</sup>)
и
V bulk
            Average mean velocity in the bulk (m s<sup>-1</sup>)
            Volume (m<sup>3</sup>)
V
```

Nomenclature

z

```
\dot{V}
            Volumetric flow rate (m<sup>3</sup> h<sup>-1</sup>)
            Molar volumes of asphaltenes in the asphaltene phase (m<sup>3</sup> mol<sup>-1</sup>)
V_A
            Volume of deposit (m<sup>3</sup>)
V_d
            Molar volumes of asphaltenes in the liquid phase (m<sup>3</sup> mol<sup>-1</sup>)
V_L
            Volume of channel (m3)
V_t
            Velocity (m s<sup>-1</sup>)
            Width of nozzle rim (m)
w
W
            Power (W)
X_{A_i}
            Fraction of non-associated molecules (-)
            Horizontal coordinate (-)
x
            Simulated value
x
            Measured value
x
            Distance expanded by element (m)
x,
            Youth variable (-)
y
            Initial value of youth variable (-)
70
            Axial coordinate (m)
2
            Vertical coordinate (-)
```

GREEK

```
Local heat transfer coefficient (W m<sup>-2</sup> K<sup>-1</sup>)
α
             Angle of nozzle entry (°)
             Heat transfer coefficient for ideal cross–flow (W \ensuremath{\text{m}}^{-2}\ensuremath{\,\text{K}}^{-1})
\alpha_{id}
             Tube-side heat transfer coefficient in clean conditions (\dot{W} m<sup>-2</sup> K<sup>-1</sup>)
\alpha_t^0
B
             Linear expansion coefficient (K<sup>-1</sup>)
B
             Constant in Ebert and Panchal model (-)
             Thermocapillarity term (K<sup>-1</sup>)
B
             Suppression parameter (m<sup>4</sup> K N<sup>-1</sup> J<sup>-1</sup>)
γ
Ϋ́
             Local shear rate (s<sup>-1</sup>)
δ
             Thickness of deposit (m)
\delta_A
             Average solubility parameters in the asphaltene phase (Pa<sup>1/2</sup>)
             Average solubility parameters in the liquid phase (Pa<sup>1/2</sup>)
\delta_L
             Temperature percentage residuals (-)
ε
5
             Data filtering procedure parameter (%)
              Dimensionless function (-)
η
              Mechanical efficiency (-)
\eta_{mech}
0
              Non-dimensional parameter that depends on L_X (-)
\theta
              Characteristic formation time of polyaromatic structure in fouling layer (s)
\theta
              Fractional surface coverage (-)
\theta_{tp}
              Tube pitch angle (°)
             Thermal conductivity (W m<sup>-1</sup> K<sup>-1</sup>)
λ
λ
              Length of nozzle entry (m)
             Thermal conductivity for freshly deposit material (W m<sup>-1</sup> K<sup>-1</sup>)
             The maximum value of thermal conductivity (W m<sup>-1</sup> K<sup>-1</sup>)
λ°
             Thermal conductivity of foulant layer (W m<sup>-1</sup> K<sup>-1</sup>)
Af
```

```
Dynamic viscosity (Pa s)
μ
             Viscosity of fresh foulant material (Pa s)
\mu_0
v
             Kinematic viscosity (St)
ξ
             Structure parameter (-)
             Density (kg m<sup>-3</sup>)
ρ
p
             Molar density in Section 5.2 (mol m<sup>-3</sup>)
             Interfacial tension between oil phase and asphaltene phase (N m<sup>-1</sup>)
\sigma
             Measurement variance (K)
\sigma
             Surface shear stress (Pa)
τ
             Surface shear stress along the arc of inner annulus (Pa)
\tau_{ya}
             Characteristic value of chemical potential (kg m<sup>2</sup> s<sup>-2</sup>)
\phi_c
             Fouling rate decrease by conversion of tarry layer to coke (m<sup>2</sup> K W<sup>-1</sup> s<sup>-1</sup>)
\phi_{cr}
             Fouling deposition term (m<sup>2</sup> K W<sup>-1</sup> s<sup>-1</sup>)
\phi_d
             Fouling removal term (m2 K W1 s-1)
\phi_r
             Fouling rate decrease by mass transfer of tars to the bulk fluid (m2 K W1 s-1)
\phi_{tr}
Ø
             Heat balance closure parameter (%)
             Weight fraction for component i (-)
\chi_i
Ω
             Model domain (-)
```

>

SUBSCRIPTS

- 0 Initial
 b Bulk
 c Cold
 cr Conversion to coke
 d Deposit
- f Fouling, film
 h Hot
- i Inner, i-th component, interface
- in Inlet
- L Fouling layer
- n Pass number
- o Outer
- out Outlet
- p Precursor
- s Shell-side
- T Tube-sideT Total
- tr Tar layer
- W Wall

xvi Nomenclature



SUPERSCRIPTS

0 Initial state of deposit

∞ Final state of deposit

* Asymptotic value

m Reaction order for reactant one

n Reaction order for reactant two

n Fluid parameter for aging model

Reaction order for precursor



l

ABBREVIATIONS

2D Two-dimensional3D Three-dimensional

AFM Atomic force microscopy .
ATR Attenuated total reflection
CDU Crude distillation unit

CFD Computational fluid dynamics

CG Coarse grained C-H Cahn-Hilliard

CII Colloidal instability index CIT Coil Inlet Temperature

CLSM Confocal laser scanning microscopy

COT Coil Outlet Temperature

CV Control valve

DFT Density functional theory
DIM Diffuse interface method
DNS Direct numerical simulation
DPD Dissipative particle dynamics

EOS Equation of State

ETS Emissions Trading Scheme FDG Fluid dynamic gauging

FTIR Fourier transform infrared spectroscopy

HEN Heat exchanger network

HEX Heat exchanger
HiPOR High Pressure Oil Rig

HTRI Heat Transfer Research Incorporated

LES Large eddy simulation
LLE Liquid—liquid equilibria

LWDT Logarithmic mean temperature difference
LVDT Linear variable displacement transducer

N-S Navier-Stokes NRV Nonreturn valve PHT Pre heat train Nomenclature xvii

RANS Reynolds-averaged Navier-Stokes

SAFT Statistical associating fluid theory

SARA Saturate, Aromatic, Resin and Asphaltene

SEC Size-exclusion chromatography

SEM Scanning electron microscopy

TGA Thermogravimetric analysis

Ultraviolet fluorescence

VdW Van der Waals VGO Virgin gas oil

UV-F

VLE Vapor–liquid equilibria
VLLE Vapor–liquid–liquid equilibria

VOF Volume of fluid XRD X-ray diffraction

CONTENTS

List	of Co	ontributors	vii	
Prei	Preface			
Noi	menci	ature	χi	
1.	Intr	oduction	1	
	F. C	oletti, H.M. Joshi, S. Macchietto, G.F. Hewitt		
	1.1	Crude Distillation Units in Oil Refineries	5	
	1.2	Impact of Fouling on Crude Distillation Units	10	
	1.3	Concluding Remarks	21	
2.	Bas	ic Science of the Fouling Process	23	
	F. Coletti, B.D. Crittenden, S. Macchietto			
	2.1	Fouling Mechanisms	24	
	2.2	Routes to Crude Oil Fouling Formation	27	
	2.3	Events in Crude Oil Fouling	35	
	2.4	Variables Affecting Fouling	43	
	2.5	Conclusions	50	
3.	Exp	perimental Generation of Fouling Deposits	51	
	B.D.	Crittenden, G.F. Hewitt, M. Millan-Agorio, K. Rostani, S. Venditti, M. Yang		
	3.1	Small Scale, Accelerated Conditions: Microbomb Fouling Tests	53	
	3.2	Batch System: Stirred Cell at the University of Bath	66	
	3.3	Large-Scale Experiments in Flow Systems	86	
4.	De	posit Characterization and Measurements	95	
	J. C	hew, H.M. Joshi, S.G. Kazarian, M. Millan-Agorio, F.H. Tay, S. Venditti		
	4.1	Analysis of Field Fouling Deposits from Crude Heat Exchangers	96	
	4.2	Chemical Structure and Molecular Weight Characterization	113	
	4.3	Chemical Imaging of Deposited Foulants and Asphaltenes	123	
	4.4	Fluid Dynamic Gauging: Thickness and Strength Measurements	155	

5.	Modeling of Fouling from Molecular to Plant Scale F. Coletti, B.D. Crittenden, A.J. Haslam, G.F. Hewitt, G. Jackson, G. Jimenez-Serratos, S. Macchietto, O.K. Matar, E.A. Müller, D. Sileri, J. Yang		
	5.1	Review of Heat Exchanger Design Methodologies and Mathematical	
		Models of Fouling	181
	5.2	Thermodynamic and Molecular Modeling	223
	5.3	Fundamental Transport Modeling	242
	5.4	Industrial Scale High-Fidelity Modeling	284
6.	Concluding Remarks		321
	F. Coletti, G.F. Hewitt		
App	Appendix 1		
References .			329
Index			361