

bre

Design of durable concrete structures

Stuart Matthews



fib
CEB • FIP

iHS

Design of durable concrete structures

Stuart Matthews

The research and writing for this publication has been funded by BRE Trust, the largest UK charity dedicated specifically to research and education in the built environment. BRE Trust uses the profits made by its trading companies to fund new research and education programmes that advance knowledge, innovation and communication for public benefit.

BRE Trust is a company limited by guarantee, registered in England and Wales (no. 3282856) and registered as a charity in England (no. 1092193) and in Scotland (no. SC039320).

Registered office: Bucknalls Lane, Garston, Watford, Herts WD25 9XX

Tel: +44 (0) 1923 664743

Email: secretary@bretrust.co.uk

www.bretrust.org.uk

IHS (NYSE: IHS) is the leading source of information, insight and analytics in critical areas that shape today's business landscape. Businesses and governments in more than 165 countries around the globe rely on the comprehensive content, expert independent analysis and flexible delivery methods of IHS to make high-impact decisions and develop strategies with speed and confidence. IHS is the exclusive publisher of BRE Trust publications.

IHS Global Ltd is a private limited company registered in England and Wales (no. 00788737).

Registered office: Willoughby Road, Bracknell, Berkshire RG12 8FB.

www.ihs.com

BRE Trust publications are available from www.brebookshop.com

or

IHS BRE Press

Willoughby Road

Bracknell

Berkshire RG12 8FB

Tel: +44 (0) 1344 328038

Fax: +44 (0) 1344 328005

Email: brepress@ihs.com

© IHS 2014. No part of this publication may be reproduced or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, or be stored in any retrieval system of any nature, without prior written permission of IHS. Requests to copy any part of this publication should be made to:

The Publisher

IHS BRE Press

Garston

Watford

Herts WD25 9XX

Tel: +44 (0) 1923 664761

Email: brepress@ihs.com

Printed using FSC or PEFC material from sustainable forests.

Printed in Great Britain by Bell & Bain Ltd, Glasgow

FB 70

First published 2014

ISBN 978-1-84806-175-0

Front cover photograph: Rio-Antirrio Bridge (also called Charilaos Trikoupis Bridge) near Patras, Greece

Back cover photograph: The Aquatics Centre, London 2012 Olympic Park

Index compiled by Cathryn Pritchard

All URLs accessed August 2013. Any third-party URLs are given for information and reference purposes only and BRE Trust and IHS do not control or warrant the accuracy, relevance, availability, timeliness or completeness of the information contained on any third-party website. Inclusion of any third-party details or website is not intended to reflect their importance, nor is it intended to endorse any views expressed, products or services offered, nor the companies or organisations in question.

Any views expressed in this publication are not necessarily those of BRE Trust or IHS. BRE Trust and IHS have made every effort to ensure that the information and guidance in this publication were accurate when published, but can take no responsibility for the subsequent use of this information, nor for any errors or omissions it may contain. To the extent permitted by law, BRE Trust and IHS shall not be liable for any loss, damage or expense incurred by reliance on the information or any statement contained herein.

Preface

This document seeks to give an appreciation of the wide range of issues associated with the design of durable concrete structures, and matters concerned with service life design. The material reported here is drawn from many sources, which have, it is hoped, been adequately acknowledged. The document attempts to reflect recent and evolving developments, and thereby give an up-to-date overview on matters concerned with service life design. This is a process whose overall objective is to ensure that the concrete structure concerned achieves appropriate durability – which is one of the primary functional requirements that the design and construction process should be expected to deliver.

The document contains 19 main chapters:

- 1 Introduction
- 2 Overview of the service life design, construction and through-life care process
- 3 Through-life performance, life-cycle cost and sustainability
- 4 Mechanisms that may cause deterioration or damage to concrete structures
- 5 Some factors influencing the durability of concrete structures
- 6 Environmental aggressivity
- 7 Recommendations in standards and codes of practice
- 8 Overview of modelling of deterioration processes
- 9 Factorial approach to estimating service life
- 10 Service life design process and considerations
- 11 Measures to enhance resistance or avoid reinforcement corrosion
- 12 Measures to enhance resistance and avoid deterioration
- 13 Influence of some design, execution and workmanship issues on durability
- 14 Construction quality issues: the role of the project execution specification
- 15 Improving durability: benefits of pre-construction planning and trials
- 16 Condition control: planned through-life structure management and care
- 17 Monitoring of durability and performance
- 18 Examples from practice
- 19 Future look: potential developments influencing service life design

This publication is an updated and significantly extended version of Volume 3 (Chapter 5) of the second edition of the *fib Structural concrete textbook*, which deals generally with the behaviour, design and performance of structural concrete. Volume 3 of the second edition of the *fib Structural concrete textbook*, which was published as *fib Bulletin 53* in December 2009, is concerned with the design of durable concrete structures. Stuart Matthews prepared *fib Bulletin 53*, which was an updating and extensive further development of the chapter on durability prepared by Dr Steen Rostam that formed part of the original *fib Structural concrete textbook*, and was published as part of *fib Bulletin 3* in 1999.

This updated and extended version takes account of subsequent developments in *fib Model Code 2010* for the design of concrete structures between the early committee draft versions available when *fib Bulletin 53* was produced and the final version due for publication in 2012, as well as those in related areas of service life design for concrete structures, such as those associated with ISO/DIS 16204. Account has also been taken of recent technical activities within groups such as *fib Commission 5: Structural service life aspects*. Other revisions and additions include further developments associated with topics such as the through-life management and care of concrete structures (Chapters 2 and 3), the diversity in views on the effect of cracks in concrete upon durability (Chapter 5), and the potential future influence of sustainability on service life design considerations (Chapter 19). In addition, various amendments have been made to the earlier text to reflect specific aspects of UK technical practice and guidance in this area (particularly BS 8500 and associated standards).

Chapter 1 provides an introduction and sets out the scope of the issues, providing an overview of the document. It notes that modern concrete forms a family of materials, and seeks to indicate why durability of concrete structures is important. It reviews previous experience in terms of the in-service performance of concrete structures, and the need to take a holistic view when creating durable concrete structures. The chapter also notes the importance of variations in concrete properties and the durability-critical role of the cover concrete, and outlines some simple conceptual models for the deterioration

caused by the corrosion of reinforcement. It introduces the benefits of considering through-life performance, life-cycle cost and sustainability perspectives when undertaking outline service life design and developing durability and service life design concepts. The chapter provides definitions and terminology, before giving an overview of the various approaches to service life design and drawing parallels between contemporary structural and probabilistic-based service life design concepts.

Chapter 2 builds on Chapter 1 to provide an overview of the service life design, construction and through-life care process. It examines the role and importance of the client brief and the definition of performance expectations, before headlining environment aggressivity classification, conceptual and detailed design for durability, and the deemed-to-satisfy durability solutions design given in codes and standards. The chapter introduces the concept of probabilistic, performance-based service life design, before examining the way in which project specifications can be used by clients and owners as a tool to achieve the desired durability, and the importance of the execution of the construction works for through-life care and maintenance aspects.

Chapter 3 examines through-life performance, life-cycle cost and sustainability issues, and seeks to draw out wider societal sustainability perspectives, as well as consideration of life-cycle cost issues.

Chapter 4 reviews mechanisms that may cause deterioration or damage to concrete structures. It provides an overview of deterioration and damage mechanisms (but excludes damage arising from accidental actions), and outlines the role of water and moisture transport mechanisms in this. The chapter looks in detail at mechanisms that may cause deterioration or damage, classifying these into four groups: those causing physical deterioration and damage processes in concrete; those associated with chemical deterioration processes; those associated with biological deterioration processes in concrete; and the corrosion of reinforcement. Consideration is briefly given to deterioration mechanisms acting in combination.

Chapter 5 reviews some factors that influence the durability of concrete structures. These include the geometrical form and architectural detailing of the structure; the cement type, mix design and concrete quality; the reinforcement type, and the depth and quality of the concrete cover; together with the potential influence of cracking, crack width and crack orientation.

Chapter 6 examines issues associated with environmental aggressivity, looking at moisture-driven deterioration processes, atmospheric-induced deterioration, the role of temperature-induced effects, and a contemporary system for the classification of environmental exposure.

Chapter 7 reviews the recommendations made in some standards and codes of practice, looking at those given in the CEB-FIP Model Code 1990 (CEB-FIP, 1992) and the *fib* Model Code for Service Life Design (*fib*, 2006b) (published in *fib* Bulletin 34), together with the guidance given in BS EN 1992 *Concrete structures* (Eurocode 2, BSI, 2004 – 2006) and associated product standards. The approach and content of *fib* Model Code 2010 (*fib*, 2012b) and ISO 16204 (ISO, 2012) are also examined.

Chapter 8 provides a brief overview of the modelling of deterioration processes, with the main focus being on carbonation and chloride-induced corrosion of reinforcement in uncracked concrete. Consideration is also given to the modelling of other mechanisms of deterioration, such as frost attack, sulfate attack, alkali–aggregate reaction, leaching and surface weathering, and abrasion by ice. The application of deterministic and probabilistic models is discussed, together with the partial factor method. The results for reinforcement corrosion obtained from a deterministic service life design model are compared with those from a probabilistic model.

Chapter 9 explains the use of the factorial approach to estimating service life, making reference to a process used for combining additional protective measures to extend service life.

Chapter 10 examines the service life design process and related considerations, outlining the main steps in a service life design procedure, and the approaches that may be adopted for detailed service life design, together with the definition of the target service life and environmental aggressivity. The various steps in the overall service life design procedure are introduced, but with more detailed discussion being provided about the adoption of a multi-layer protection approach, with an example of this concept being given for multi-layer protection of prestressing tendons, as given in *fib* Bulletin 33 (*fib*, 2006a). Additional observations are made for durability and service life design issues for environments where de-icing salt is applied, and for structures in a marine environment. The concepts associated with Birth Certificate documentation and reliability updating are also explained.

Chapter 11 presents detailed recommendations for measures to enhance resistance or avoid reinforcement corrosion on the basis of the selection of cementitious materials, the use of admixtures and fibres, ways of enhancing the resistance of the surface of the concrete, ways of enhancing tolerance to carbonation and chlorides, and the avoidance approach (ie the design-out approach). The chapter concludes with an overview of measures to enhance resistance or avoid reinforcement corrosion.

Chapter 12 summarises some measures to enhance resistance or avoid forms of deterioration other than reinforcement corrosion.

Chapter 13 examines the influence of some design, execution and workmanship issues on the durability of concrete structures. The matters considered include: the influence of locally available concrete materials and labour; dimensioning of structural elements; reinforcement detailing and congestion; compaction and curing of concrete; the use of controlled-permeability formwork, self-compacting concrete and high-performance concrete; durability problems associated with spacers and chairs to support reinforcement; and the use of inserts and fixtures. The benefits of using of stainless steel reinforcement, the role of quality assurance and quality control, and the potential importance of aesthetics and appearance issues are discussed.

Chapter 14 examines construction quality issues and, in particular, the role of the project execution specification in creating greater certainty of achieving durable concrete structures. The approach adopted is centred on the European construction standards and the Execution Standard (BS EN 13670; BSI, 2009d), with observations being made about how these link with the quality management standards contained in the ISO 9000 series.

Chapter 15 discusses the potential benefits of pre-construction planning and trials as a means of improving the durability of concrete structures, particularly for major infrastructure projects. Six steps to delivering improved certainty of achieving durable concrete construction are set down.

Chapter 16 describes the condition control processes that may be adopted for planned through-life structure management and care, linking these into an overall process of condition survey and monitoring activities, condition assessment and condition evaluation. These are based on the concepts developed in the work undertaken

for Chapter 9: 'Conservation' of *fib* Model Code 2010 (*fib*, 2012b). This chapter outlines the role of classes of condition control within the process of through-life management of a structure, describing the associated condition control levels and inspection regimes. While a strategy using proactive condition control measures is recommended for new concrete structures, the approach outlined allows for reactive condition control measures, and for situations where condition control measures are not feasible (ie foundations).

Chapter 17 describes methodologies for monitoring the durability and performance of a concrete structure. It provides advice on the locations for surveys, testing and monitoring activities, condition survey and monitoring activities, tools and techniques for surveys, and monitoring and data gathering for condition control purposes. As with Chapter 16, the approach is based on the concepts developed in the work undertaken for Chapter 9: 'Conservation' of *fib* Model Code 2010. The chapter also briefly considers issues associated with the automated monitoring of concrete structures, and how these techniques can link to the updating of service life predictions.

Chapter 18 presents details of two service life design examples from practice: the Great Belt Fixed Link, Denmark, and the Western Scheldt Tunnel, the Netherlands.

Chapter 19 provides a future look, examining some potential developments that may influence durability and service life design in the future. The topics considered include the *fib* Model Code 2010, the need for improved scientific understanding of deterioration processes, anticipated developments in cementitious and concrete materials, and the further development and application of service life design principles.

The document concludes with extensive lists of references and further reading.

Acknowledgements

The author gratefully acknowledges the financial support provided by BRE Trust for elements of the background work employed in this publication. The publication also draws on work undertaken in BRE research and related projects over recent years.

The author wishes to thank *fib* and other colleagues for their input to discussions supporting the development of the ideas and material presented here, in *fib* Bulletin 44 (2008) and in other work; plus access that has been obtained to various other sources of technical information for use in this publication. Particular thanks go to C Andrade (especially in relation to aspects of Chapter 4), A Bigaj-van Vliet (in relation to Chapter 16), J Buffenbarger (in relation to the results of the comparative study of ternary and other powder blend concretes reported in section 11.2.7), C Clear, M Clift, S Curtis (particularly in relation to Chapters 14 and 15 and the Appendix), C Gehlen, J Gulikers, S Helland, S Rostam and T Ueda (in relation to Chapter 16) for the material that they have made available. The author also wishes to thank *fib* for permission to reproduce Figures from various *fib* Bulletins.

The author is particularly indebted to BRE colleagues for access to material prepared in respect of BRE publications, and also to that produced during the BRE service life research project. The author has drawn freely on this compendium of work, and acknowledges the valuable assistance that this material has given in the preparation of this publication. Particular thanks go to Phil Bamforth, Éanna Nolan and Keith Quillin for the material that they have made available. Special thanks also go to the BRE librarians Marian Bodian and Susanne Woodman for their assistance in researching literature sources and obtaining copies of the required information, along with Nick Clarke of IHS BRE Press for his efforts in the process of editing and updating the original *fib* Bulletin 53 version of the document.

The author is very grateful to the following individuals and organisations for making available photographs and images used in this document: C Andrade, U Angst, S Curtis, C Edvardsen, A Knudsen, M Raupach, I Stipanovic Oslakovic, G Thielen, Arminox, BRE, CIRIA, *fib*, IHS BRE Press, the Concrete Society and UK CARES. Also of note is the assistance of Adam Hughes of IHS BRE Press in the resourcing and processing of digital images.

The Concrete Society has permitted the reproduction of the figures listed below from its publications, with thanks to R Day and J Clarke for their assistance in sourcing various items. These figures are reproduced with permission of the Concrete Society from the publications cited in the references and bibliography, which are available to purchase from www.concretebookshop.com. Copyright for these figures is retained by the Concrete Society. The figures reproduced are Figures 1.10, 4.3, 4.10, 4.16, 5.2, 5.5 to 5.7, 11.1 to 11.9, 11.17 to 11.20, 14.2 and 14.3.

The author is also indebted to the colleagues who undertook the task of reviewing the original *fib* publication (published as *fib* Bulletin 53) and the current publication and for their helpful comments, especially Carmen Andrade, György Balázs, Nick Clarke and Keith Quillin.

The author wishes to acknowledge Steen Rostam, the author of the chapter on durability in the original *fib* Textbook on Structural Concrete published as part of *fib* Bulletin 3, who passionately promoted consideration of matters relating to durability and the service life design of concrete structures.

And finally, apologies to any of the numerous people who have assisted me in the task of creating this publication that I may have inadvertently overlooked in this list of citations.

About the author

Stuart Matthews is currently Chief Engineer Construction, BRE, and was formerly Director of the Centre for Concrete Construction at BRE. He is a Chartered Engineer, a Chartered Scientist and a Chartered Water and Environmental Manager and has extensive experience in the fields of civil engineering and building, having been in practice for over 35 years. He worked for a range of organisations, including a water authority, a contractor, a consultant and a specialist test house, before joining BRE to undertake research and consultancy in a range of areas.

Stuart has been involved in the design and construction of concrete infrastructure, service life and durability issues for concrete structures, including various types of nuclear industry structures, plus methods for their investigation, assessment, repair and refurbishment. Other topics have included non-destructive testing techniques, the use of marine aggregates, and work on the sustainability/environmental impact evaluation of concrete materials.

He is actively engaged in the work of several professional, national and international organisations and technical committees. Among others, he is currently co-chair of *fib* Special Activity Group 7 on the assessment of existing structures. He previously convened *fib* Commission 5 concerned with the service life design, assessment and rehabilitation of concrete structures. He was also closely involved in the work of *fib* Special Activity Group 5, which was responsible for the preparation of *fib* Model Code 2010, published in early 2012.

He is the author or principal author of *fib* Bulletins 53 and 62, BRE Report 511, and BRE Digests 366 (2012), 510 and 526; as well as being a main contributor to the CONREPNET project report EP77 and *fib* Bulletin 44. He also contributed extensively to the second (1996) and third (2010) editions of the Institution of Structural Engineers' report *Appraisal of existing structures*, to *fib* Bulletin 17 and *fib* Model Code 2010, and to the *ICE Manual of Structural Design* (2012), contributing the chapter on 'Taking a through-life perspective in design'. In addition, Stuart is the author or joint author of numerous technical papers and other publications.

List of figures and colour plates

List of figures

- 1.1 The Pantheon, Rome. *The interior of the Pantheon*, Giovanni Paolo Panini (images Wikimedia Commons)
- 1.2 Failure of parking deck due to deterioration of the concrete structure, which was not sufficiently durable for the aggressive environment (courtesy of Arminox)
- 1.3 Severe delamination and spalling of a concrete slab soffit caused by reinforcement corrosion
- 1.4 Perceived occupational origin of the problems of achieving adequate cover depth in concrete structures (courtesy of Clark *et al*, 1997)
- 1.5 A design service life performance plan for elements of a bridge (after Nolan *et al*, 2006a)
- 1.6 Decision matrix for durability risk (after Nolan *et al*, 2006a)
- 1.7 Normal variations in concrete quality across the section of a concrete beam (after Dewar, 1985)
- 1.8 Simplified models for the corrosion of reinforcement
- 1.9 Relationship between durability and performance (courtesy of CEB, 1992, and Thomas Telford)
- 1.10 Replacement of reinforced quay wall cope beam by an unreinforced precast concrete capping block (courtesy of Concrete Society, 2008a)
- 1.11 Comparison of the ease of use and the sophistication of various service life design methodologies
- 2.1 Simplified service life design procedure (after Nolan *et al*, 2006a)
- 2.2 Some micro-climate conditions on a bridge subject to de-icing salts (courtesy of Pritchard, 1992)
- 3.1 Relative level of knowledge about the performance of a concrete structure, and the cost and environmental implications of the timing of making a change (courtesy of *fib*, 2008)
- 3.2 Relative impact on the performance of a concrete structure and on life-cycle costs and environmental impacts of the timing of making a change (courtesy of *fib*, 2008)
- 3.3 Illustrative cumulative direct cost and environmental impact profiles of a concrete structure for two design and operation strategies (courtesy of *fib*, 2008)
- 3.4 Aerial view of Progreso piers (courtesy of *fib*, 2008, and Arminox)
- 3.5 Life-cycle costs for four different service life design strategies: influence of financial discount rates on the choice of service life design strategy for a concrete quay exposed to a marine environment (courtesy of Steen Rostam)
- 3.6 A potential breakdown of the components of sustainable construction
- 3.7 Schematic combination of the components of design quality to achieve best-value solutions using the three-factor representation style
- 3.8 Schematic combination of the components of sustainable construction using a four-factor representation style
- 3.9 Achieving a balance between the different components of design quality: schematic illustrating various compromises in the performance levels attained (based on the three-factor representation style portrayed in Figure 3.7)
- 3.10 Achieving a balance between the different components of design quality: a three-spoke radar-style plot portrayal of various compromises in the performance levels attained (based on the three-factor representation style illustrated in Figure 3.7)
- 3.11 Achieving a balance between the different components of design quality: a four-spoke radar-style plot portrayal of various compromises in the performance levels attained (based on the four-factor representation style illustrated in Figure 3.8)
- 3.12 The plateau of sustainable construction (after Somerville, 1999)
- 3.13 Schematic diagram illustrating the BRE service life design process with associated links to sustainability-related initiatives (courtesy of Nixon, 2002)
- 4.1 Deterioration processes affecting concrete (data from BCA, 1997)

- 4.2 Process factors contributing to durability (data from BCA, 1997)
- 4.3 Schematic representation of various types of crack that can occur in concrete structures (courtesy of Concrete Society, 2010b)
- 4.4 Stages of corrosion-induced deterioration of a concrete structure (adapted from *fib*, 2008)
- 4.5 The changing condition with time of a concrete structure experiencing deterioration due to reinforcement corrosion (after EUROLIFEFORM project)
- 4.6 Early thermal cracking due to continuous edge restraint (courtesy of Bamforth, 2008a)
- 4.7 Early thermal cracking: location of the first crack on wall elevation (courtesy of Bamforth, 2008a)
- 4.8 Early thermal cracking: comparison of estimated cracks widths using BS 8007, EN 1992-3 and the Bamforth revised method (courtesy of Bamforth *et al*, 2009)
- 4.9 Autogenous shrinkage for different strength classes, estimated using the method given in EN 1992-2-1 (courtesy of Concrete Society, 2008b)
- 4.10 Original concept for the development of frost damage in concrete (courtesy of Scherer *et al*, 2008)
- 4.11 Change in dimensions of concrete during cooling and freezing (courtesy of Powers and Helmuth, 1953)
- 4.12 Original concept of frost damage: air voids prevent excessive pore pressure by providing sinks for displaced water (courtesy of Scherer *et al*, 2008)
- 4.13 Revised concept of frost damage: air voids provide sites for nucleation and growth of ice crystals, drawing in liquid from pores (courtesy of Scherer *et al*, 2008)
- 4.14 Frost- and de-icing-salt-induced damage at the base of a concrete plinth supporting a pipeline
- 4.15 Tanking of foundations to reduce the chance of reinforcement corrosion just above ground level (courtesy of Concrete Society, 2008a)
- 4.16 Integral crosshead as shown in BA 57/01 (courtesy of Highways Agency, 2001)
- 4.17 Illustrative time relationships for leaching and loss of concrete strength: (a) permeability of concrete is constant with time; (b) permeability of concrete increases with increased leaching (after CONTECVET, 2000c)
- 4.18 Cracking due to alkali-silica reaction in a column. Cracks form in the direction in which there is least resistance to expansion effects
- 4.19 Diagrammatic view of steel protected from carbonation-induced corrosion in partially carbonated concrete
- 4.20 Diagrammatic view of steel corroding in carbonated concrete
- 4.21 Diagrammatic view of steel corroding in cracked concrete
- 4.22 Conceptual model showing the typical shape of a carbonation front with depth into the concrete
- 4.23 Simplified model of the corrosion of reinforcement in concrete
- 4.24 Relative volumes of iron and of its oxides created during corrosion (after Mansfield, 1981)
- 4.25 Cracking of column due to chloride-induced corrosion caused by contaminated aggregates and mixing water. Age of structure at first cracking: 3 years. Gulf climate (courtesy of *fib*, 1999)
- 4.26 Delamination of precast balcony partition wall due to chloride-induced corrosion caused by calcium chloride added as mix accelerator. Age of structure: 15 years. North European climate (courtesy of *fib*, 1999)
- 4.27 Variation of RH at depth and of the convective zone for a concrete with a 0.6 water/cement ratio over a 14-day full cycle between T1 (60% RH) and T2 (95% RH)
- 4.28 Increase in corrosion rate with increase in RH of carbonated concrete (after Sergi and Dunster, 2004)
- 4.29 Relationship between relative humidity and corrosion rate of steel reinforcement obtained on carbonated mortars dosed with chloride ($1 \text{ mA/m}^2 = 0.1 \text{ } \mu\text{A/cm}^2 \approx 1.2 \text{ } \mu\text{m/year}$) (adapted from Glass *et al*, 1991)
- 4.30 Postulated variation of critical chloride concentration for corrosion initiation with moisture level in the concrete (courtesy of CEB, 1992)
- 4.31 The likelihood of corrosion at different levels of chloride (after Vassie, 1984, and Browne, 1982)
- 4.32 Chloride threshold values reported in the literature (Angst *et al*, 2009). (a) Expressed as total chloride per weight of binder, (b) Expressed as Cl^-/OH^- ratios
- 4.33 Indicative likelihood of corrosion at different levels of chloride content in uncarbonated concrete in the vicinity of the reinforcing steel (after Concrete Society, 2011a and Part 2 of BRE, 2000b)
- 4.34 Indicative likelihood of corrosion at different levels of chloride content in uncarbonated concrete in the vicinity of the reinforcing steel, incorporating data from experiences reported by various researchers (after Concrete Society, 2011a and Part 2 of BRE, 2000b)
- 4.35 Examples of situations potentially leading to crevice corrosion (courtesy of Andrade *et al*)
- 4.36 Microcracks generated at the metallic surface (courtesy of Sanchez, Andrade and Fullea)
- 4.37 A ductile fracture of a prestressing wire (courtesy of Sanchez, Andrade and Fullea)
- 4.38 A brittle fracture of a prestressing wire (courtesy of Sanchez, Andrade and Fullea)

- 5.1 Some mechanisms of deterioration that affect concrete structures, and associated environmental influences (after Price, 2000)
- 5.2 Partial washing of concrete surface associated with rainwater run-off from a horizontal surface, with an upper washed zone and a lower soiled concrete surface, and a wavy interface line between the two zones (courtesy of Hawes, 1986)
- 5.3 A building façade with a high durability risk (courtesy of Rostam and *fib*, 1999)
- 5.4 A building façade with a low durability risk (courtesy of Rostam and *fib*, 1999)
- 5.5 The time to corrosion initiation due to carbonation or chloride penetration depends on the concrete cover achieved in the structure. The example corresponds to high-quality uncracked concrete (courtesy of Concrete Society, 1996)
- 5.6 Distribution of cover – analysis of 1600 covermeter readings for a 13 m high retaining wall (courtesy of Concrete Society, 1996)
- 5.7 Aesthetically acceptable crack widths (courtesy of Concrete Society, 2008b; adapted from Campbell-Allen, 1979)
- 5.8 Effect of crack frequency f on cumulative weight loss due to corrosion, estimated using galvanic current (zero-resistance ammetry; ZRA) measurements (courtesy of Arya and Ofori-Darko, 1996)
- 5.9 Effect of crack frequency on cumulative weight loss due to corrosion, estimated by linear polarisation resistance (LPR) measurement (courtesy of Arya and Ofori-Darko, 1999)
- 5.10 Alignment of cracks relative to the longitudinal axis of reinforcing bars
- 5.11 Self-healing of a dormant crack and an active crack (courtesy of Edvardsen, 1999)
- 5.12 Limiting crack width for self-healing of crack in a concrete wall section related to pressure gradient across the section (courtesy of Bamforth, 2007)
- 6.1 Rate of carbonation of concrete as a function of relative humidity
- 6.2 Reinforced concrete jetty in the Gulf exhibiting extensive chloride-induced corrosion damage after only 2–3 years (courtesy of *fib*, 1999)
- 7.1 Relationship between BS EN 206 and other European standards for the design and execution of concrete structures, including standards for constituent materials and associated test standards, adapted from Figure 1, BS EN 206 (after BSI, 2013a)
- 7.2 The BS EN 206 durability concept for concrete structures (after Thielen, 2009)
- 7.3 BS EN 206 exposure conditions and environmental actions associated with the corrosion of reinforcement in concrete: illustration of influencing variables (after Thielen, 2009)
- 7.4 BS EN 206 exposure conditions and environmental actions associated with deterioration of the concrete (after Thielen, 2009)
- 7.5 Estimated reliability values for BS EN 206-1 exposure class XS1 for a service life period of 50 years for selected CEN member states and Australia (courtesy of Gehlen, 2011)
- 7.6 Estimated reliability values for BS EN 206-1 exposure class XS3 for a service life period of 50 years for selected CEN member states and Australia (courtesy of Gehlen, 2011)
- 7.7 Estimated reliability values for BS EN 206-1 exposure class XD3 for a service life period of 50 years for selected CEN member states (courtesy of Gehlen, 2011)
- 7.8 Illustration of variations in time to depassivation of steel reinforcement associated with different relative probabilities of depassivation reported for different national durability design recommendations for selected CEN member states, together with hypothetical estimates of associated cracking of concrete, for an example concrete composition (after Helland, 2011, 2013)
- 7.9 Illustration of different probabilities of depassivation of steel reinforcement for a working life of 50 years for different national durability design recommendations selected by some CEN member states, for the same environmental exposure (after Helland, 2011, 2013)
- 7.10 Flow chart for the *fib* Model Code for Service Life Design (courtesy of *fib*, 2006b)
- 7.11 Schematic illustrating the concepts of probabilistic service life
- 7.12 ISO 16204 flow chart for service life design of concrete structures (courtesy of ISO, 2012)
- 8.1 Increase of carbonation depth with time, illustrating the influence of concrete quality
- 8.2 Predicted chloride profiles for a C30 Portland cement concrete assuming a diffusion coefficient D after 1 year of $10^{-11} \text{ m}^2/\text{s}$ and $n = -0.26$
- 8.3 Predicted chloride profiles for a C30 15% fly ash concrete assuming a diffusion coefficient D after 1 year of $4 \times 10^{-12} \text{ m}^2/\text{s}$ and $n = -0.7$
- 8.4 Overlap between the depth of carbonation, represented by a single (maximum) value, at a particular time and the depth of cover to the reinforcement
- 8.5 Increase in the overlap between the depth of carbonated concrete and the depth of cover to reinforcement with time, leading to depassivation of an increasing percentage of the embedded reinforcement as time passes
- 8.6 Proportion of reinforcement estimated to be depassivated for selected PDFs of the depth of carbonation of concrete and the cover to reinforcement in a concrete member: situation 1

- 8.7 Proportion of reinforcement estimated to be depassivated for selected PDFs of the depth of carbonation of concrete and the cover to reinforcement in a concrete member: situation 2
- 8.8 Service period design and lifetime design (adapted from Siemes and Rostam, 1996)
- 8.9 Relationship between probability P_i and β values (for a normal probability distribution)
- 8.10 Deterministic approach (courtesy of *fib*, 1999)
- 8.11 Probabilistic approach (courtesy of *fib*, 1999)
- 10.1 The main steps in a service life design procedure for concrete structures
- 10.2 Levels of service life design: hierarchy of simplifications versus degree of correctness of representation of physical processes (after Siemes, undated)
- 10.3 Illustrative hazard scenarios for prestressing steel in a notional box girder bridge (courtesy of *fib*, 2006a; after Matt, 2000)
- 10.4 Protection levels (PL) required for post-tensioning tendons based on aggressivity/exposure versus structural protection layers present (courtesy of *fib*, 2006a)
- 10.5 Tendon system for protection level 1 (PL1) (courtesy of *fib*, 2006a)
- 10.6 Tendon system for protection level 2 (PL2) (courtesy of *fib*, 2006a)
- 10.7 Tendon system for protection level 3 (PL3) (courtesy of *fib*, 2006a)
- 10.8 Transport processes active in a sea wall, with the influence of different climatic conditions (derived from Slater and Sharp, 1998, with reference to Concrete Society, 1996)
- 10.9 Stages in developing a Birth Certificate (after Mayer and Schiessel, 2008)
- 10.10 Probability of corrosion versus time (courtesy of Rostam, 1999)
- 11.1 Penetration over a 10-year period of chloride ions into a 30% fly ash concrete with a water/cement ratio of 0.48 (courtesy of Thomas, 1996)
- 11.2 Relationship between fly ash content and relative apparent diffusion coefficient (courtesy of Bamforth, 2004)
- 11.3 Relationship between apparent diffusion coefficient and period of exposure for fly ash concretes exposed to regular wetting (courtesy of Bamforth, 2004)
- 11.4 Relationship between ggbs content and relative apparent diffusion coefficient (courtesy of Bamforth, 2004)
- 11.5 Chloride profiles recorded over a 10-year period of splash zone exposure for 70% ggbs concrete with a water/cement ratio of 0.48 (courtesy of Bamforth, 2004)
- 11.6 Relationship between apparent diffusion coefficient and period of exposure for ggbs concretes exposed to regular wetting (courtesy of Bamforth, 2004)
- 11.7 Relationship between apparent diffusion coefficient and period of exposure for sf concretes exposed to regular wetting, as affected by water/cement ratio (courtesy of Bamforth, 2004)
- 11.8 Detected chloride levels at 20 mm depth in various types of concrete after 12 months' wetting and drying (courtesy of Bamforth, 2004)
- 11.9 Relative mean carbonation depth for concretes with and without metakaolin. The concretes were cured for different periods, and then stored indoors under natural carbonation exposure conditions (courtesy of Bamforth, 2004)
- 11.10 Comparison of compressive strength (determined in accordance with ASTM C 39) of various ternary and other powder blend concretes (courtesy of Buffenbarger *et al*, 2012)
- 11.11 Comparison of the boiled absorption properties (determined in accordance with ASTM C 642) of various ternary and other powder blend concretes (courtesy of Buffenbarger *et al*, 2012)
- 11.12 Comparison of the porosity (determined in accordance with ASTM C 642) of various ternary and other powder blend concretes (courtesy of Buffenbarger *et al*, 2012)
- 11.13 Comparison of the rapid chloride permeability properties (determined in accordance with ASTM C 1012) of various ternary and other powder blend concretes (courtesy of Buffenbarger *et al*, 2012)
- 11.14 Comparison of the bulk diffusion coefficient values (determined in accordance with ASTM C 1556) of various ternary and other powder blend concretes (courtesy of Buffenbarger *et al*, 2012)
- 11.15 Comparison of hydroxide ion diffusion coefficient values (determined in accordance with ASTM C 1556) of various ternary and other powder blend concretes (courtesy of Buffenbarger *et al*, 2012)
- 11.16 Comparison of chloride ion diffusion coefficient values (determined in accordance with ASTM C 1556) of various ternary and other powder blend concretes (courtesy of Buffenbarger *et al*, 2012)
- 11.17 Schematic illustration of how surface coatings and impregnants work on concrete (courtesy of Bamforth, 2004)
- 11.18 Classification of coatings and surface treatments (courtesy of Concrete Society, 1997)
- 11.19 Principal elements of a controlled-permeability formwork system (courtesy of Price, 2000)
- 11.20 Variations in water/cement ratio with distance from the formed surface (courtesy of Price, 2000)
- 11.21 Carbonation depth versus time, and implications of different concrete cover depths for the notional service life of a concrete structure

- 11.22 Total corrosion versus time in 3% NaCl solution as a function of water/cement ratio and calcium nitrite level (courtesy of Berke, 1987)
- 11.23 Corrosion cell between epoxy-coated reinforcement (e-bar) in the top surface and uncoated reinforcing bars in the soffit, such as might occur in a car park deck slab (courtesy of Nürnberger, 1995)
- 11.24 Structure of the coating produced by hot-dip galvanising of steel (courtesy of *fib*, 2009)
- 11.25 The influence of crack width on the corrosion of galvanised reinforcing bars under seawater splash zone exposure conditions (courtesy of *fib*, 2009)
- 11.26 A conceptual model for the corrosion behaviour of normal 'black/carbon' steel reinforcement and galvanised reinforcement in concrete (after Bamforth, 2004)
- 11.27 Corrosion performance of ungalvanised and galvanised reinforcing steel in concrete (courtesy of *fib*, 2009)
- 11.28 Passivity of carbon and stainless steel reinforcement grades in chloride-contaminated concrete at 20°C (courtesy of UK CARES, undated)
- 11.29 The principle of cathodic prevention (courtesy of Bamforth, 2004)
- 13.1 In the foreground is the original 1940s stainless steel-reinforced pier at Progreso in Mexico, which is still intact after 60 years in service without any maintenance. In the background are the remains of a 1970s pier reinforced with ordinary carbon (black) steel after being in service for only about 30 years (courtesy of Arminox)
- 13.2 Krk Bridge, Croatia, general views, and illustration of deterioration (courtesy of *fib*, 2008): (a) view of the Krk Bridge from the island of Krk to the mainland; (b) main span of the Krk Bridge; (c) deterioration of part of the main arch
- 13.3 Life-cycle costs for the Krk Bridge (courtesy of *fib*, 2008)
- 14.1 Main modules of the system of European standards that provide a basis for the design, execution and selection of materials for concrete structures
- 14.2 Preparing to concrete, by John G Richardson (courtesy of Richardson, 2002 and *fib*)
- 14.3 Placing, compacting and caring for cast concrete, by John G Richardson (courtesy of Richardson, 2002 and *fib*)
- 15.1 Congested reinforcement in a bridge plinth (courtesy of Storebaelt Authority)
- 15.2 Example of a potential durability problem in the base of a bridge pylon wall (courtesy of Storebaelt Authority)
- 15.3 The challenge of concrete mix design (courtesy of *fib*, 2008)
- 16.1 Conservation management: overview of the through-life condition control process and recording of information (courtesy of *fib*, 2012b)
- 16.2 General flow of condition survey for structures taken into condition control following construction (courtesy of *fib*, 2012b)
- 17.1 River Tees Barrage, UK, during construction. Instrumentation was installed for monitoring the in-service performance of the concrete structure
- 17.2 River Tees Barrage, UK, illustrating the in-service conditions
- 17.3 The role of monitoring in the management of concrete structures (courtesy of Buenfeld *et al*, 2008)
- 18.1 Great Belt East Bridge, main span of 1624 m: 100-year service life design (courtesy Henrik Sendelbach, Wikimedia Commons, 2009)
- 18.2 Proportions of a high-performance concrete mix (courtesy of Idorn Consult)
- 18.3 Great Belt Link project: epoxy coating of reinforcement cage (courtesy of *fib*, 1999)
- 18.4 Great Belt Link project: corrosion sensor installed in a tunnel segment (courtesy of M Raupach)
- 18.5 Great Belt Link project: sacrificial anode installation (courtesy of *fib*, 1999)
- 18.6 Geometry of the Western Scheldt Tunnel, and the construction of a tunnel segment (courtesy of Gehlen and Schiessl, 1999)
- 18.7 Anticipated change in the reliability index with time for the Western Scheldt Tunnel: criterion depassivation of the steel in the tunnel segments (courtesy of Gehlen and Schiessl, 1999)

List of colour plates

- Plates 1–6 Examples of some forms of deterioration affecting concrete structures (courtesy of *fib*, 2008)
- Plates 7–12 Examples of the effects of some forms of deterioration and accidental actions (fire and impact) on concrete bridges (courtesy of *fib*, 2008)
- Plate 13 Stress corrosion cracking in a prestressing wire (courtesy of Sanchez, Andrade and Fulla)
- Plate 14 Loss of zinc from galvanised reinforcing bars embedded in normal-weight concrete as a function of chloride content after seawater exposure of 2.5 years, for concrete cover depths of 15 mm and 25 mm (courtesy of *fib*, 2009)

List of tables

- | | | | |
|------|---|-----|---|
| 3.1 | Embodied carbon content of standard concrete mixes containing varying degrees of Portland cement replacement by fly ash: ICE database (kg CO ₂ /tonne concrete) (University of Bath) | 6.3 | Limiting values for exposure classes for chemical attack from natural soil and groundwater, as classified in Table 6.2 (after BS EN 206: BSI, 2013a) |
| 3.2 | Embodied carbon content of standard concrete mixes containing varying degrees of Portland cement replacement by ggbs: ICE database (kg CO ₂ /tonne concrete) (University of Bath) | 6.4 | Exposure classes for concrete structures according to BS 8500-1 (courtesy of BSI, 2012b) |
| 3.3 | Embodied carbon content of standard UK-supplied ready-mixed concretes containing varying degrees of Portland cement replacement by fly ash and ggbs and recycled aggregate: from BRE data (kg CO ₂ eq (100 year)/tonne concrete) | 6.5 | Classification of ground conditions according to BS 8500-1 (courtesy of BSI, 2012b) |
| 3.4 | Embodied carbon content for an average C 28/35 UK concrete, from UK trade association data (SCF, 2008c) | 7.1 | Recommended minimum values for composition and properties of concrete as defined by BS EN 206 (BSI, 2013a) |
| 3.5 | Embodied carbon content of selected grades of concrete, from UK trade association data (SCF, 2009a) | 7.2 | Durability recommendations for reinforced or prestressed concrete elements with an intended working life of at least 50 years (after BS 8500-1: BSI, 2012b) |
| 4.1 | Overview of some deterioration mechanisms for some types of concrete structure (<i>fib</i> , 2008) | 7.3 | Durability recommendations for reinforced or prestressed concrete elements with an intended working life of at least 100 years (after BS 8500-1: BSI, 2012b) |
| 4.2 | Nominal unrestrained drying shrinkage values (microstrain, $\mu\epsilon$) for different relative humidities, from BS EN 1992-1-1 (BSI, 2004a) | 7.4 | Cement and combination types |
| 4.3 | The aggressiveness of water to concrete (after BS EN 206: BSI, 2013a) | 7.5 | Limiting values for composition and properties of concrete to resist freezing and thawing (XF exposures) including BS 8500-1:2012 amendments |
| 4.4 | Corrosion likelihood classification (after Browne, 1982) | 7.6 | The BS 8500-2:2012 amendment for minimising the likelihood of damaging alkali-silica reaction in concrete: recommended limits for alkali contents of concretes |
| 4.5 | Assumed critical chloride concentrations for the initiation of reinforcement corrosion for different binders for service life modelling (Bamforth, 2004) | 7.7 | Comparison of national requirements for minimum concrete cover, maximum water/cementitious ratio, minimum cement content and minimum compressive strength class (after Harrison <i>et al</i> , 2009) |
| 4.6 | Some examples of synergetic deterioration, where several deterioration mechanisms act simultaneously (after CONTECVET, 2001) | 7.8 | Illustration of some of the national durability recommendation selected by CEN member countries for concrete made with CEM I for an intended working life of at least 50 years (after Annex B, Harrison <i>et al</i> , 2009; and with reference to Table 6.2 for the exposure classes to BS EN 206-1) |
| 6.1a | General indication of the influence of moisture condition on deterioration processes (after CEB, 1992) | 7.9 | Estimated reliability values for Norwegian structures made with CEM I concrete and subject to exposure classes XC3 and XC4 for an intended service life of 50 years (after Maage, 2001) |
| 6.1b | Revised general indication of the influence of moisture condition on deterioration processes (adapted from CEB, 1992, using Sergi and Dunster, 2004) | | |
| 6.2 | Exposure classes for concrete structures according to BS EN 206 (BSI, 2013a) | | |

- 7.10 Estimated reliability values for Norwegian structures made with CEM I concrete and subject to exposure classes XC3 and XC4 for an intended service life of 100 years (after Maage and Smeplass, 2001)
- 7.11 Definition of consequence classes (CC) (from Table A2-1, *fib*, 2006b)
- 7.12 Recommended minimum values for reliability index β for use in service life design for the intended design lifetime (from Table A2-2, *fib*, 2006b)
- 7.13 Robustness classes (ROC) (from Table A3-1, *fib*, 2006b)
- 7.14 Design supervision levels (DSL) (from Table A4-1, *fib*, 2006b)
- 7.15 Execution classes (EXC) (from Table A5-1, *fib*, 2006b)
- 7.16 Condition control levels (CCL) (from Table A6-1, *fib*, 2006b)
- 7.17 Recommended target reliability indices β for structures under design, for specified reference periods (from Table 3.3-5, *fib*, 2013a)
- 8.1 Overview of availability of service life models for various forms of deterioration and their relationship to structural limit states (Buenfeld *et al*, 2008)
- 8.2 Illustration of the notional change in the probability of reinforcement depassivation as the carbonation front progressively overlaps the depth of cover of the embedded steel reinforcing bars as time passes
- 9.1 Factors that can affect service life (Nolan *et al*, 2006b)
- 9.2 Effectiveness of combinations of measures to enhance service life (Nolan *et al*, 2006b)
- 9.3 Estimated additional service life (in years) from use of additional protection measures for conventional Portland cement concrete structure
- 11.1 Comparison of material factors that influence time to onset of corrosion (after Bamforth, 2004)
- 11.2 Performance data for proprietary silica fume concretes
- 11.3 Binder proportions for the ternary and other Portland cement blend concretes used in the comparative laboratory study reported by Buffenbarger *et al* (2012)
- 11.4 Summary of test results for the ternary and other Portland cement blend concretes used in the comparative laboratory study reported by Buffenbarger *et al* (2012)
- 11.5 Recommended calcium nitrite dosage rate (using a 30% solution) as a function of the anticipated acid-soluble chloride level in concrete
- 11.6 Some stainless steel types and their characteristic compositions
- 11.7 Some stainless steels used as reinforcement (*fib*, 2009)
- 11.8 Indicative characteristics and mechanical properties for austenitic and duplex stainless steels (BSI, 2005d; *fib*, 2009)
- 11.9 Some measures to enhance resistance or avoid reinforcement corrosion
- 14.1 Characteristics of the types of inspection defined in BS EN 13670 with suggested application of inspection classes
- 17.1 Inspection, testing and monitoring regimes for different classes of condition control
- 17.2 Gathering data for condition control purposes for various conservation strategies
- 17.3 Indicative feasibility of automated monitoring of various properties and behaviours in a concrete structure (after Buenfeld *et al*, 2008)
- 17.4 Suitability of service life models for use with automated monitoring (courtesy of Buenfeld *et al*, 2008)
- 17.5 Feasibility of the use of some carbonation and chloride ingress models with automated monitoring (courtesy of Buenfeld *et al*, 2008)

Abbreviations

AAR	alkali–aggregate reaction	DEF	delayed ettringite formation
AC	alternating current	DSL	design supervision level
ACEC class	aggressive chemical environment for concrete class	EA	environmental aggressivity
ACI	American Concrete Institute	EC	European Commission
AFRP	aramid fibre-reinforced polymer	EDC	equivalent durability concept
ASR	alkali–silica reaction	EDP	equivalent durability procedure
BCA	British Cement Association	ECPC	equivalent concrete performance concept
BRE	Building Research Establishment Ltd	EN	European Norm (a European Standard)
BS	British Standard	ENV	European Pre-standard (voluntary use)
BSI	British Standards Institution	EPCC	equivalent performance of combinations concept
CABE	Commission for Architecture and the Built Environment	ERMCO	European Ready-Mixed Concrete Organisation
CAC	calcium aluminate cement	ESLC	estimated service life
CAL	condition assessment level	EXC	execution class
CARES	Certification Authority for Reinforcing Steels	fa	Fly ash: see pulverised fuel ash
CC	consequence class	FBECR	fusion-bonded, epoxy-coated reinforcement
C&CA	Cement and Concrete Association	<i>fib</i>	Fédération Internationale du Béton [International Federation for Structural Concrete]
CCL	condition control level	FIP	Fédération Internationale de la Précontrainte [International Federation for Prestressing]
CE	CE Mark	FRP	fibre-reinforced polymer
CEB	Comité Euro-International du Béton [European Committee for Concrete]	ggbs	ground granulated blastfurnace slag
CEN	Comité Européen de Normalisation [European Committee for Standardisation]	GHG	greenhouse gas
CFRP	carbon fibre-reinforced polymer	GRC	glass-fibre-reinforced concrete
CIB	Conseil International du Bâtiment [International Council for Research and Innovation in Building and Construction]	GRCA	Glassfibre Reinforced Concrete Association
CIRIA	Construction Industry Research and Information Association	HAC	high-alumina cement
CONREPNET	Thematic network on performance-based remediation of reinforced concrete structures: CONcrete REPair NETwork	hEN	harmonised European Norm (European technical standard)
CONTECVET	A validated user's manual for assessing the residual service life of concrete structures	HETEK	high-quality concrete, the contractor's technology (Danish research project)
CoV	coefficient of variation	HPC	high-performance concrete
CPD	Construction Products Directive	HRWRA	high-range water-reducing admixture
CPF	controlled-permeability formwork	HSC	high-strength concrete
CPR	Construction Products Regulation	IABSE	International Association for Bridge and Structural Engineering
CSMA	Cementitious Slag Makers Association	IBA	incinerator bottom ash
DARTS	durable and reliable tunnel structures	IBAA	incinerator bottom ash aggregate
DC class	design chemical class	ICE	inventory of carbon and energy; Institution of Civil Engineers

ISE	Institution of Structural Engineers	PREN	pitting resistance equivalent number
ISO	International Organization for Standardization	QA	quality assurance
LCA	life-cycle analysis/assessment	QC	quality control
LCC/LCCA	life-cycle cost/life-cycle cost analysis	QFD	quality function deployment
LIFECON	life-cycle management of concrete infrastructures for improved sustainability, competitive and sustainable	QSRMC	quality scheme for ready mixed concrete
LIFECON LMS	life-cycle management of concrete infrastructures for improved sustainability, competitive and sustainable	RA	recycled aggregate
LMS	life-cycle maintenance and management planning system	RAMS	reliability, availability, maintainability and safety
LPR	linear polarisation resistance	RC	reliability class
MADA	multi-attribute decision aid	RCA	recycled concrete aggregate
MC	(CEB-FIP) Model code	RH	relative humidity
MCDM	multiple criteria decision making	ROC	robustness class
MC-SLD	(<i>fib</i>) Model Code for Service Life Design	RLC	reference service life
MFU value	most frequently used value	SBR	styrene-butadiene rubber
mk	metakaolin	SCC	self-compacting concrete
MMFX	microcomposite multistructural formable	SCC	stress corrosion cracking
MPA	Mineral Products Association	SCE	saturated calomel electrode: mercurous chloride
NANDO	New Approach Notified and Designated Organisation	SCF	Sustainable Concrete Forum
NDP	nationally determined parameter	SCM	secondary cementitious material
NDT	non-destructive testing	sf	silica fume or microsilica
PBA	performance-based approach	SLD	service life design
PC	Portland cement	SLS	serviceability limit state
PDF	probability distribution function	SM	safety margin
pfa	pulverised fuel ash: see fly ash	TR	technical report
PL	protection level	TSA	thaumasite form of sulfate attack
prEN	pre-normative European Standard (a provisional standard issued for comment)	UKQAA	UK Quality Ash Association
		ULS	ultimate limit state
		w/b	water/binder (ratio)
		w/c	water/cement (ratio)
		WLC	whole-life cost
		ZRA	zero-resistance ammetry