ITERATIVE LEARNING CONTROL FOR

MULTI-AGENT SYSTEMS COORDINATION

SHIPING YANG JIAN-XIN XU XUEFANG LI DONG SHEN



WILEY

Iterative Learning Control for Multi-agent Systems Coordination

Shiping Yang
Jian-Xin Xu
Xuefang Li
National University of Singapore
Dong Shen
Beijing University of Chemical Technology, P.R. China





This edition first published 2017 © 2017 John Wiley & Sons Singapore Pte. Ltd

Registered Office

John Wiley & Sons Singapore Pte. Ltd, 1 Fusionopolis Walk, #07-01 Solaris South Tower, Singapore 138628.

For details of our global editorial offices, for customer services and for information about how to apply for permission to reuse the copyright material in this book please see our website at www.wiley.com.

All Rights Reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, scanning, or otherwise, except as expressly permitted by law, without either the prior written permission of the Publisher, or authorization through payment of the appropriate photocopy fee to the Copyright Clearance Center. Requests for permission should be addressed to the Publisher, John Wiley & Sons Singapore Pte. Ltd., 1 Fusionopolis Walk, #07-01 Solaris South Tower, Singapore 138628, tel: 65-66438000, fax: 65-66438008, email: enquiry@wiley.com.

Wiley also publishes its books in a variety of electronic formats. Some content that appears in print may not be available in electronic books.

Designations used by companies to distinguish their products are often claimed as trademarks. All brand names and product names used in this book are trade names, service marks, trademarks or registered trademarks of their respective owners. The Publisher is not associated with any product or vendor mentioned in this book. This publication is designed to provide accurate and authoritative information in regard to the subject matter covered. It is sold on the understanding that the Publisher is not engaged in rendering professional services. If professional advice or other expert assistance is required, the services of a competent professional should be sought.

Limit of Liability/Disclaimer of Warranty: While the publisher and author have used their best efforts in preparing this book, they make no representations or warranties with respect to the accuracy or completeness of the contents of this book and specifically disclaim any implied warranties of merchantability or fitness for a particular purpose. It is sold on the understanding that the publisher is not engaged in rendering professional services and neither the publisher nor the author shall be liable for damages arising herefrom. If professional advice or other expert assistance is required, the services of a competent professional should be sought.

Library of Congress Cataloging-in-Publication Data

Names: Yang, Shiping, 1987 - author. | Xu, Jian-Xin, author. | Li, Xuefang, 1985- author. | Shen, Dong, 1982- author.

Title: Iterative learning control for multi-agent systems coordination / by

Shiping Yang, Jian-Xin Xu, Xuefang Li, Dong Shen.

Description: Singapore: John Wiley & Sons, Inc., 2017. | Includes bibliographical references and index. Identifiers: LCCN 2016052027 (print) | LCCN 2016056133 (ebook) | ISBN 9781119189046 (hardback) | ISBN 9781119189060 (pdf) | ISBN 9781119189077 (epub)

Subjects: LCSH: Intelligent control systems. | Multiagent systems. | Machine learning. | Iterative methods (Mathematics) | BISAC: TECHNOLOGY & ENGINEERING / Robotics.

Classification: LCC TJ217.5 .Y36 2017 (print) | LCC TJ217.5 (ebook) | DDC 629.8/9-dc23

LC record available at https://lccn.loc.gov/2016052027

A catalog record for this book is available from the British Library.

Set in 10/12pt Warnock by SPi Global, Pondicherry, India

Cover design: Wiley

Cover image: @ Michael Mann/Gettyimages

Printed in Singapore by C.O.S. Printers Pte Ltd

Preface

The coordination and control problems of multi-agent systems (MAS) have been extensively studied by the control community due to the broad practical applications, for example, the formation control problem, search and rescue by multiple aerial vehicles, synchronization, sensor fusion, distributed optimization, the economic dispatch problem in power systems, and so on. Meanwhile, many industry processes require both repetitive executions and coordination among several independent entities. This observation motivates the research of multi-agent coordination from an iterative learning control (ILC) perspective. This book is dedicated to the application of iterative learning control to multi-agent coordination problems.

In order to study multi-agent coordination by ILC, an extra dimension, the iteration domain, is introduced into the problem. A challenging issue in controlling multi-agent systems by ILC is the non-perfect repeating characteristics of MAS. The inherent nature of MAS such as heterogeneity, information sharing, sparse and intermittent communication, imperfect initial conditions, and inconsistent target tracking trajectories increases the complexity of the problem. Due to these factors, controller design becomes a challenging problem. This book provides detailed guidelines for the design of learning controllers under various coordination conditions, in a systematic manner. The main content can be classified into two parts following the two main frameworks of ILC, namely, contraction-mapping (CM) and composite energy function (CEF) approaches. Chapters 2-7 apply the CM approach, while Chapters 8-10 apply the CEF approach. Each chapter studies the coordination problem under certain conditions. For example, Chapter 2 assumes a fixed communication topology, Chapter 3 assumes a switching topology, and Chapter 4 addresses the initial state error problem in multi-agent coordination. In a sense, each chapter addresses a unique coordination control problem for MAS. Chapters 2-10 discuss continuous-time systems. In Chapter 11 we present a generalized iterative learning algorithm to solve an optimal power dispatch problem in a smart grid by utilizing discrete-time consensus algorithms.

This book is self contained and intensive. Prior knowledge of ILC and MAS is not required. Chapter 1 provides a rudimentary introduction to the two areas. Two minimal examples of ILC are presented in Chapter 1, and a short review of some terminologies in graph theory is provided in Appendix A. Readers can skip the preliminary parts if they are familiar with the domain. We present detailed convergence proofs for each controller as we believe that understanding the theoretical derivations can benefit readers in two ways. On the one hand, it helps readers appreciate the controller design. On the other hand, the control design and analysis techniques can be transferred to

x Preface

other domains to facilitate further exploration in various control applications. Specifically for industrial experts and practitioners, we provide detailed illustrative examples in each chapter to show how those control algorithms are implemented. The examples demonstrate the effectiveness of the learning controllers and can be modified to handle practical problems.

Contents

Preface ix

1	Introduction 1
1.1	Introduction to Iterative Learning Control 1
1.1.1	Contraction-Mapping Approach 3
1.1.2	Composite Energy Function Approach 4
1.2	Introduction to MAS Coordination 5
1.3	Motivation and Overview 7
1.4	Common Notations in This Book 9
2	Optimal Iterative Learning Control for Multi-agent Consensus
	Tracking 11
2.1	Introduction 11
2.2	Preliminaries and Problem Description 12
2.2.1	Preliminaries 12
2.2.2	Problem Description 13
2.3	Main Results 15
2.3.1	Controller Design for Homogeneous Agents 15
2.3.2	Controller Design for Heterogeneous Agents 20
2.4	Optimal Learning Gain Design 21
2.5	Illustrative Example 23
2.6	Conclusion 26
3	Iterative Learning Control for Multi-agent Coordination Under
	Iteration-Varying Graph 27
3.1	Introduction 27
3.2	Problem Description 28
3.3	Main Results 29
3.3.1	Fixed Strongly Connected Graph 29
3.3.2	Iteration-Varying Strongly Connected Graph 32
3.3.3	Uniformly Strongly Connected Graph 37
3.4	Illustrative Example 38
3.5	Conclusion 40

4	Iterative Learning Control for Multi-agent Coordination with Initial
	State Error 41
4.1	Introduction 41
4.2	Problem Description 42
4.3	Main Results 43
4.3.1	Distributed D-type Updating Rule 43
4.3.2	Distributed PD-type Updating Rule 48
4.4	Illustrative Examples 49
4.5	Conclusion 50
5	Multi-agent Consensus Tracking with Input Sharing by Iterative
	Learning Control 53
5.1	Introduction 53
5.2	Problem Formulation 54
5.3	Controller Design and Convergence Analysis 54
5.3.1	Controller Design Without Leader's Input Sharing 55
5.3.2	Optimal Design Without Leader's Input Sharing 58
5.3.3	Controller Design with Leader's Input Sharing 59
5.4	Extension to Iteration-Varying Graph 60
5.4.1	Iteration-Varying Graph with Spanning Trees 60
5.4.2	Iteration-Varying Strongly Connected Graph 60
5.4.3	Uniformly Strongly Connected Graph 62
5.5	Illustrative Examples 63
5.5.1	Example 1: Iteration-Invariant Communication Graph 63
5.5.2	Example 2: Iteration-Varying Communication Graph 64
5.5.3	Example 3: Uniformly Strongly Connected Graph 66
5.6	Conclusion 68
6	A HOIM-Based Iterative Learning Control Scheme for Multi-agent
	Formation 69
6.1	Introduction 69
6.2	Kinematic Model Formulation 70
6.3	HOIM-Based ILC for Multi-agent Formation 71
6.3.1	Control Law for Agent 1 72
6.3.2	Control Law for Agent 2 74
6.3.3	Control Law for Agent 3 75
6.3.4	Switching Between Two Structures 78
6.4	Illustrative Example 78
6.5	Conclusion 80
7	P-type Iterative Learning for Non-parameterized Systems with
	Uncertain Local Lipschitz Terms 81
7.1	Introduction 81
7.2	Motivation and Problem Description 82
7.2.1	Motivation 82
7.2.2	Problem Description 83
7.3	Convergence Properties with Lyapunov Stability Conditions 84

7.3.1 7.3.2 7.3.3 7.4	Preliminary Results 84 Lyapunov Stable Systems 86 Systems with Stable Local Lipschitz Terms but Unstable Global Lipschitz Factors 90 Convergence Properties in the Presence of Bounding Conditions 92
7.4.1	Systems with Bounded Drift Term 92
7.4.2	Systems with Bounded Control Input 94
7.5	Application of P-type Rule in MAS with Local Lipschitz Uncertainties 9.
7.6	Conclusion 99
8	Synchronization for Nonlinear Multi-agent Systems by Adaptive Iterative Learning Control 101
8.1	Introduction 101
8.2	Preliminaries and Problem Description 102
8.2.1	Preliminaries 102
8.2.2	Problem Description for First-Order Systems 102
8.3	Controller Design for First-Order Multi-agent Systems 105
8.3.1	Main Results 105
8.3.2	Extension to Alignment Condition 107
8.4	Extension to High-Order Systems 108
8.5	Illustrative Example 113
8.5.1	First-Order Agents 114
8.5.2	High-Order Agents 115
8.6	Conclusion 118
9	Distributed Adaptive Iterative Learning Control for Nonlinear Multi-agent Systems with State Constraints 123
9.1	Introduction 123
9.2	Problem Formulation 124
9.3	Main Results 127
9.3.1	Original Algorithms 127
9.3.2	Projection Based Algorithms 135
9.3.3	Smooth Function Based Algorithms 138
9.3.4	Alternative Smooth Function Based Algorithms 141
9.3.5	Practical Dead-Zone Based Algorithms 145
9.4	Illustrative Example 147
9.5	Conclusion 174
10	Synchronization for Networked Lagrangian Systems under Directed Graphs 175
10.1	Introduction 175
10.2	Problem Description 176
10.3	Controller Design and Performance Analysis 177
10.4	Extension to Alignment Condition 183
10.5	Illustrative Example 184
10.6	Conclusion 188

viii	Contents

11	Generalized Iterative Learning for Economic Dispatch Problem in a Smart Grid 189	
11.1	Introduction 189	
11.2	Preliminaries 190	
11.2.1	In-Neighbor and Out-Neighbor 190	
11.2.2	Discrete-Time Consensus Algorithm 191	
11.2.3	Analytic Solution to EDP with Loss Calculation 192	
11.3	Main Results 193	
11.3.1	Upper Level: Estimating the Power Loss 194	
11.3.2	Lower Level: Solving Economic Dispatch Distributively 194	
11.3.3	Generalization to the Constrained Case 197	
11.4	Learning Gain Design 198	
11.5	Application Examples 200	
11.5.1	Case Study 1: Convergence Test 201	
11.5.2	Case Study 2: Robustness of Command Node Connections 202	
11.5.3	Case Study 3: Plug and Play Test 203	
11.5.4	Case Study 4: Time-Varying Demand 205	
11.5.5	Case Study 5: Application in Large Networks 207	
11.5.6	Case Study 6: Relation Between Convergence Speed and Learning Gain 20	17
11.6	Conclusion 208	
12	Summary and Future Research Directions 209	
12.1	Summary 209	
12.2	Future Research Directions 210	
12.2.1	Open Issues in MAS Control 210	
12.2.2	Applications 214	
Appendi	ix A Graph Theory Revisit 223	
Appendi	ix B Detailed Proofs 225	
B.1	HOIM Constraints Derivation 225	
B.2	Proof of Proposition 2.1 226	
B.3	Proof of Lemma 2.1 227	
B.4	Proof of Theorem 8.1 229	
B.5	Proof of Corollary 8.1 230	

Bibliography 233

Index 245

1

Introduction

1.1 Introduction to Iterative Learning Control

Iterative learning control (ILC), as an effective control strategy, is designed to improve current control performance for unpredictable systems by fully utilizing past control experience. Specifically, ILC is designed for systems that complete tasks over a fixed time interval and perform them repeatedly. The underlying philosophy mimics the human learning process that "practice makes perfect." By synthesizing control inputs from previous control inputs and tracking errors, the controller is able to learn from past experience and improve current tracking performance. ILC was initially developed by Arimoto *et al.* (1984), and has been widely explored by the control community since then (Moore, 1993; Bien and Xu, 1998; Chen and Wen, 1999; Longman, 2000; Norrlof and Gunnarsson, 2002; Xu and Tan, 2003; Bristow *et al.*, 2006; Moore *et al.*, 2006; Ahn *et al.*, 2007a; Rogers *et al.*, 2007; Ahn *et al.*, 2007b; Xu *et al.*, 2008; Wang *et al.*, 2009, 2014).

Figure 1.1 shows the schematic diagram of an ILC system, where the subscript idenotes the iteration index and y_d denotes the reference trajectory. Based on the input signal, u_i , at the *i*th iteration, as well as the tracking error $e_i = y_d - y_i$, the input u_{i+1} for the next iteration, namely the (i + 1)th iteration, is constructed. Meanwhile, the input signal u_{i+1} will also be stored into memory for use in the (i+2)th iteration. It is important to note that in Figure 1.1, a closed feedback loop is formed in the iteration domain rather than the time domain. Compared to other control methods such as proportional-integral-derivative (PID) control and sliding mode control, there are a number of distinctive features about ILC. First, ILC is designed to handle repetitive control tasks, while other control techniques don't typically take advantage of task repetition—under a repeatable control environment, repeating the same feedback would yield the same control performance. In contrast, by incorporating learning, ILC is able to improve the control performance iteratively. Second, the control objective is different. ILC aims at achieving perfect tracking over the whole operational interval. Most control methods aim to achieve asymptotic convergence in tracking accuracy over time. Third, ILC is a feedforward control method if viewed in the time domain. The plant shown in Figure 1.1 is a generalized plant, that is, it can actually include a feedback loop. ILC can be used to further improve the performance of the generalized plant. As such, the generalized plant could be made stable in the time domain, which is helpful in guaranteeing transient response while learning takes place. Last but not

Memory u_{i} u_{i+1} Plant y_{i+1}

Memory

Figure 1.1 The framework of ILC.

least, ILC is a partially model-free control method. As long as an appropriate learning gain is chosen, perfect tracking can be achieved without using a perfect plant model.

Generally speaking, there are two main frameworks for ILC, namely contraction-mapping (CM)-based and composite energy function (CEF)-based approaches. A CM-based iterative learning controller has a very simple structure and is easy to implement. A correction term in the controller is constructed from the output tracking error; to ensure convergence, an appropriate learning gain is selected based on system gradient information in place of an accurate dynamic model. As a partially model-free control method, CM-based ILC is applicable to non-affine-in-input systems. These features are highly desirable in practice as there are plenty of data available in industry processes but there is a shortage of accurate system models. CM-based ILC has been adopted in many applications, for example X-Y tables, chemical batch reactors, laser cutting systems, motor control, water heating systems, freeway traffic control, wafer manufacturing, and so on (Ahn et al., 2007a). A limitation of CM-based ILC is that it is only applicable to global Lipschitz continuous (GLC) systems. The GLC condition is required by ILC in order to form a contractive mapping, and rule out the finite escape time phenomenon. In comparison, CEF-based ILC, a complementary approach to CM-based ILC, applies a Lyapunov-like method to design learning rules. CEF is an effective method to handle locally Lipschitz continuous (LLC) systems, because system dynamics is used in the design of learning and feedback mechanisms. It is, however, worthwhile pointing out that in CM-based ILC, the learning mechanism only requires output signals, while in CEF-based ILC, full state information is usually required. CEF-based ILC has been applied in satellite trajectory keeping (Ahn et al., 2010) and robotic manipulator control (Tayebi, 2004; Tayebi and Islam, 2006; Sun et al., 2006).

This book follows the two main frameworks and investigates the multi-agent coordination problem using ILC. To illustrate the underlying idea and properties of ILC, we start with a simple ILC system.

Consider the following linear time-invariant dynamics:

$$\dot{x}_i(t) = ax_i(t) + u_i(t), \ t \in [0, T], \tag{1.1}$$

where i is the iteration index, a is an unknown constant parameter, and T is the trial length. Let the target trajectory be $x_d(t)$, which is generated by

$$\dot{x}_d(t) = a x_d(t) + u_d(t), \ t \in [0, T], \tag{1.2}$$

with $u_d(t)$ is the desired control signal. The control objective is to tune $u_i(t)$ such that without any prior knowledge about the parameter a, the tracking error

 $e_i(t) \triangleq x_{il}(t) - x_i(t)$ can converge to zero as the iteration number increases, that is, $\lim_{t\to\infty} e_i(t) = 0$ for $t \in [0, T]$.

We perform the ILC controller design and convergence analysis for this simple control problem under the frameworks of both CM-based and CEF-based approaches, in order to illustrate the basic concepts in ILC and analysis techniques. To restrict our discussion, the following assumptions are imposed on the dynamical system (1.1).

Assumption 1.1 The identical initialization condition holds for all iterations, that is, $x_i(0) = x_d(0), \forall i \in \mathbb{N}.$

Assumption 1.2 For $\forall x_d(t), t \in [0, T]$, there exists a $u_d(t), t \in [0, T]$ such that $u_i(t) \rightarrow$ $u_d(t)$ implies $x_i(t) \to x_d(t), t \in [0, T]$.

1.1.1 Contraction-Mapping Approach

Under the framework of CM-based methodology, we apply the following D-type updating law to solve the trajectory tracking problem:

$$u_{i+1} = u_i + \gamma \dot{e}_i, \tag{1.3}$$

where $\gamma > 0$ is the learning gain to be determined. Our objective is to show that the ILC law (1.3) can converge to the desired u_d , which implies the convergence of the tracking error $e_i(t)$, $t \in [0, T]$ as i increases.

Define $\Delta u_i = u_d - u_i$. First we can derive the relation

$$\Delta u_{i+1} = u_d - u_{i+1}$$

$$= u_d - u_i - \gamma \dot{e}_i$$

$$= \Delta u_i - \gamma \dot{e}_i.$$
(1.4)

Furthermore, the state error dynamics is given by

$$\dot{e}_i = \dot{x}_d - \dot{x}_i
= (ax_d + u_d) - (ax_i + u_i)
= ae_i + \Delta u_i.$$
(1.5)

Combining (1.4) and (1.5) gives:

$$\Delta u_{i+1} = \Delta u_i - \gamma \dot{e}_i$$

= $(1 - \gamma)\Delta u_i - a\gamma e_i$. (1.6)

Integrating both sides of the state error dynamics and using Assumption 1.1 yields

$$e_i(t) = e_i(0) + \int_0^t e^{a(t-\tau)} \Delta u_i(\tau) d\tau$$

$$= \int_0^t e^{a(t-\tau)} \Delta u_i(\tau) d\tau. \tag{1.7}$$

Then, substituting (1.7) into (1.6), we obtain

$$\Delta u_{i+1} = (1 - \gamma)\Delta u_i - a\gamma \int_0^t e^{a(t-\tau)} \Delta u_i(\tau) d\tau. \tag{1.8}$$

Taking λ -norm on both sides of (1.8) gives

$$|\Delta u_{i+1}|_{\lambda} \le |1 - \gamma| |\Delta u_i|_{\lambda} + a\gamma \frac{1 - e^{-(\lambda - a)T}}{\lambda - a} |\Delta u_i|_{\lambda}$$

$$\triangleq \rho_1 |\Delta u_i|_{\lambda}, \tag{1.9}$$

where $\rho_1 \triangleq |1 - \gamma| + a\gamma \frac{1 - e^{-(\lambda - a)T}}{1 - a}$, and the λ -norm is defined as

$$|\Delta u_{i+1}|_{\lambda} = \sup_{t \in [0,T]} e^{-\lambda t} |\Delta u_{i+1}(t)|.$$

The λ -norm is just a time weighted norm and is used to simplify the derivation. It will be formally defined in Section 1.4.

If $|1 - \gamma| < 1$ in (1.9), it is possible to choose a sufficiently large $\lambda > a$ such that $\rho_1 < 1$. Therefore, (1.9) implies that $\lim_{t\to\infty} |\Delta u_i|_{\lambda} = 0$, namely $\lim_{t\to\infty} u_i(t) = u_d(t)$, $t \in [0, T]$.

1.1.2 Composite Energy Function Approach

In this subsection, the ILC controller will be developed and analyzed under the framework of CEF-based approach. First of all, the error dynamics of the system (1.1) can be expressed as follows:

$$\dot{e}_i(t) = -ax_i + \dot{x}_d - u_i, \tag{1.10}$$

where x_d is the target trajectory.

Let k be a positive constant. By applying the control law

$$u_i = -ke_i + \dot{x}_d - \hat{a}_i(t)x_i \tag{1.11}$$

and the parametric updating law $\forall t \in [0, T]$,

$$\hat{a}_i(t) = \hat{a}_{i-1}(t) + x_i e_i, \quad \hat{a}_{-1}(t) = 0,$$
 (1.12)

we can obtain the convergence of the tracking error e_i as i tends to infinity.

In order to facilitate the convergence analysis of the proposed ILC scheme, we introduce the following CEF:

$$E_i(t) = \frac{1}{2}e_i^2(t) + \frac{1}{2}\int_0^t \phi_i^2(\tau)d\tau,$$
(1.13)

where $\phi_i(t) \triangleq \hat{a}_i - a$ is the estimation error of the unknown parameter a.

The difference of E_i is

$$\Delta E_i(t) = E_i - E_{i-1}$$

$$= \frac{1}{2}e_i^2 + \frac{1}{2}\int_0^t (\phi_i^2 - \phi_{i-1}^2)d\tau - \frac{1}{2}e_{i-1}^2.$$
(1.14)

By using the identical initialization condition as in Assumption 1.1, the error dynamics (1.10), and the control law (1.11), the first term on the right hand side of (1.14) can be calculated as

$$\frac{1}{2}e_{i}^{2} = \int_{0}^{t} e_{i}\dot{e}_{i}d\tau
= \int_{0}^{t} e_{i}(-\dot{x}_{d} + ax_{i} + u_{i})d\tau
= \int_{0}^{t} (-\phi_{i}x_{i}e_{i} - ke_{i}^{2})d\tau.$$
(1.15)

In addition, the second term on the right hand side of (1.14) can be expressed as

$$\frac{1}{2} \int_{0}^{t} (\phi_{i}^{2} - \phi_{i-1}^{2}) d\tau = \frac{1}{2} \int_{0}^{t} (\hat{a}_{i-1} - \hat{a}_{i})(2a - 2\hat{a}_{i} + \hat{a}_{i} - \hat{a}_{i-1}) d\tau
= \int_{0}^{t} (\phi_{i} x_{i} e_{i} - \frac{1}{2} x_{i}^{2} e_{i}^{2}) d\tau,$$
(1.16)

where the updating law (1.12) is applied. Clearly, $\phi_i x_i e_i$ appears in (1.15) and (1.16) with opposite signs. Combining (1.14), (1.15), and (1.16) yields

$$\Delta E_i(t) = -k \int_0^t e_i^2 d\tau - \frac{1}{2} \int_0^t x_i^2 e_i^2 d\tau - \frac{1}{2} e_{i-1}^2$$

$$\leq -\frac{1}{2} e_{i-1}^2 < 0. \tag{1.17}$$

The function E_i is a monotonically decreasing sequence, hence is bounded if E_0 is bounded.

Now, let us show the boundedness of E_0 . For the linear plant (1.1) or in general GLC plants, there will be no finite escape time, thus E_0 is bounded. For local Lipschitz continuous plants, ILC designed under CEF guarantees there is no finite escape time (see Xu and Tan, 2003, chap. 7), thus E_0 is bounded. Hence, the boundedness of $E_0(t)$ over [0, T] is obtained.

Consider a finite sum of ΔE_i ,

$$\sum_{i=1}^{l} \Delta E_j = \sum_{i=1}^{l} (E_j - E_{j-1}) = E_i - E_0, \tag{1.18}$$

and apply the inequality (1.17); we have:

$$E_{i}(t) = E_{0}(t) + \sum_{j=1}^{i} \Delta E_{j}$$

$$\leq E_{0}(t) - \frac{1}{2} \sum_{i=1}^{i} e_{j-1}^{2}.$$
(1.19)

Because of the positiveness of E_i and boundedness of E_0 , $e_i(t)$ converges to zero in a pointwise fashion as i tends to infinity.

1.2 Introduction to MAS Coordination

In the past several decades, MAS coordination and control problems have attracted considerable attention from many researchers of various backgrounds due to their potential applications and cross-disciplinary nature. Consensus in particular is an important class of MAS coordination and control problems (Cao et al., 2013). According to Olfati-Saber et al. (2007), in networks of agents (or dynamic systems), consensus means to reach an agreement regarding certain quantities of interest that are associated with all agents. Depending on the specific application, these quantities could be velocity, position, temperature, orientation, and so on. In a consensus realization, the control action of an agent is generated based on the information received or measured from its neighborhood. Since the control law is a kind of distributed algorithm, it is more robust and scalable compared to centralized control algorithms.

The three main components in MAS coordination are the agent model, the information sharing topology, and the control algorithm or consensus algorithm.

Agent models range from simple single integrator model to complex nonlinear models. Consensus results on single integrators are reported by Jadbabaie et al. (2003), Olfati-Saber and Murray (2004), Moreau (2005), Ren et al. (2007), and Olfati-Saber et al. (2007). Double integrators are investigated in Xie and Wang (2005), Hong et al. (2006), Ren (2008a), and Zhang and Tian (2009). Results on linear agent models can be found in Xiang et al. (2009), Ma and Zhang (2010), Li et al. (2010), Huang (2011), and Wieland et al. (2011). Since the Lagrangian system can be used to model many practical systems, consensus has been extensively studied by means of the Lagrangian system. Some representative works are reported by Hou et al. (2009), Chen and Lewis (2011), Mei et al. (2011), and Zhang et al. (2014).

Information sharing among agents is one of the indispensable components for consensus seeking. Information sharing can be realized by direct measurement from on board sensors or communication through wireless networks. The information sharing mechanism is usually modeled by a graph. For simplicity in the early stages of consensus algorithm development, the communication graph is assumed to be fixed. However, a consensus algorithm that is robust or adaptive to topology variations is more desirable, since many practical conditions can be modeled as time-varying communications, for example asynchronous updating, or communication link failures and creations. As communication among agents is an important topic in the MAS literature, various communication assumptions and consensus results have been investigated by researchers (Moreau, 2005; Hatano and Mesbahi, 2005; Tahbaz-Salehi and Jadbabaie, 2008; Zhang and Tian, 2009). An excellent survey can be found in Fang and Antsaklis (2006). Since graph theory is seldom used in control theory and applications, a brief introduction to the topic is given in Appendix A.

A consensus algorithm is a very simple local coordination rule which can result in very complex and useful behaviors at the group level. For instance, it is widely observed that by adopting such a strategy, a school of fish can improve the chance of survival under the sea (Moyle and Cech, 2003). Many interesting coordination problems have been formulated and solved under the framework of consensus, for example distributed sensor fusion (Olfati-Saber et al., 2007), satellite alignment (Ren and Beard, 2008), multi-agent formation (Ren et al., 2007), synchronization of coupled oscillators (Ren, 2008b), and optimal dispatch in power systems (Yang et al., 2013). The consensus problem is usually studied in the infinite time horizon, that is, the consensus is reached as time tends to infinity. However, some finite-time convergence algorithms are available (Cortex, 2006; Wang and Hong, 2008; Khoo et al., 2009; Wang and Xiao, 2010; Li et al., 2011). In the existing literature, most consensus algorithms are model based. By incorporating ILC into consensus algorithms, the prior information requirement from a plant model can be significantly reduced. This advantage will be shown throughout this book.

1.3 Motivation and Overview


In practice, there are many tasks requiring both repetitive executions and coordination among several independent entities. For example, it is useful for a group of satellites to orbit the earth in formation for positioning or monitoring purposes (Ahn et al., 2010). Each satellite orbiting the earth is a repeated task, and the formation task fits perfectly in the ILC framework. Another example is the cooperative transportation of a heavy load by multiple mobile robots (Bai and Wen, 2010; Yufka et al., 2010). In such kinds of task implementation, the robots have to maneuver in formation from the very beginning to the destination. The economic dispatch problem in power systems (Xu and Yang, 2013; Yang et al., 2013) and formation control for ground vehicles with nonholonomic constraints (Xu et al., 2011) also fall in this category. These observations motivate the study of multi-agent coordination control from the perspective of ILC.

As discussed in the previous subsection, the consensus tracking problem is an important multi-agent coordination problem, and many other coordination problems can be formulated and solved in this framework, such as the formation, cooperative search, area coverage, and synchronization problems. We chose consensus tracking as the main topic in this book. Here we briefly describe a prototype consensus tracking problem and illustrate the concepts of distributed tracking error which are used throughout the book. In the problem formulation, there is a single leader that follows a prescribed trajectory, and the leader's behavior is not affected by others in the network. There are many followers, and they can communicate with each other and with the leader agent. However, they may not know which one the leader is. Due to communication limitations, a follower is only able to communicate with its near neighbors. The control task is to design an appropriate local controller such that all the followers can track the leader's trajectory. A local controller means that an agent is only allowed to utilize local information. To illustrate these concepts, Figure 1.2 shows an example of a communication network. (Please see Appendix A for a revision of graph theory.) Each node in the graph represents an agent (agents will be modeled by dynamic systems in later chapters). Edges in the graph show the information flow. For instance, there is an edge starting from agent 2 and ending at agent 1, which means agent 1 is able to obtain information from agent 2. In this example there are two edges ending at agent 1. This implies that agent 1 can utilize the information received from agents 0 and 2. Let x_i denote the variable of interest for the ith agent, for instance, position, velocity, orientation, temperature, pressure, and so on. The distributed error ξ_1 for agent 1 is defined as

$$\xi_1 = (x_0 - x_1) + (x_2 - x_1).$$

The distributed error ξ_1 will be used to construct the distributed learning rule.

Figure 1.2 Example of a network.



With this problem in mind, the main content of the book is summarized below.

- 1) In Chapter 2, a general consensus tracking problem is formulated for a group of global Lipschitz continuous systems. It is assumed that the communication is fixed and connected, and the perfect identical initialization condition (iic) constraint is satisfied as well. A D-type ILC rule is proposed for the systems to achieve perfect consensus tracking. By adoption of a graph dependent matrix norm, a local convergence condition is devised at the agent level. In addition, optimal learning gain design methods are developed for both directed and undirected graphs such that the λ -norm of tracking error converges at the fastest rate.
- 2) In Chapter 3, we investigate the robustness of the D-type learning rule against communication variations. It turns out that the controller is insensitive to iteration-varying topology. In the most general case, the learning controller is still convergent when the communication topology is uniformly strongly connected over the iteration domain.
- 3) In Chapter 4, the PD-type learning rule is proposed to deal with imperfect initialization conditions as it is difficult to ensure perfect initial conditions for all agents due to sparse information communication—hence only a few of the follower agents know the desired initial state. The new learning rule offers two main features. On the one hand, it can ensure controller convergence. On the other hand, the learning gain can be used to tune the final tracking performance.
- 4) In Chapter 5, a novel input sharing learning controller is developed. In the existing literature, when designing the learning controller, only the tracking error is incorporated in the control signal generation. However, if the follower agents can share their experience gained during the process, this may accelerate the learning speed. Using this idea, the new controller is developed for each agent by sharing its learned control input with its neighbors.
- 5) In Chapter 6, we apply the learning controller to a formation problem. The formation contains two geometric configurations. The two configurations are related by a high-order internal model (HOIM). Usually the ILC control task is fixed. The most challenging part of this class of problem is how to handle changes in configuration. By incorporating the HOIM into the learning controller, it is shown that, surprisingly, the agents are still able to learn from different tasks.
- Chapter 7, by combining the Lyapunov analysis method contraction-mapping analysis, we explore the applicability of the P-type learning rule to several classes of local Lipschitz systems. Several sufficient convergence conditions in terms of Lyapunov criteria are derived. In particular, the P-type learning rule can be applied to a Lyapunov stable system with quadratic Lyapunov functions, an exponentially stable system, a system with bounded drift terms, and a uniformly bounded energy bounded state system under control saturation. The results greatly complement the existing literature. By using the results of this chapter, we can immediately extend the results in Chapters 2-5 to more general nonlinear systems.
- 7) In Chapter 8, the composite energy function method is utilized to design an adaptive learning rule to deal with local Lipschitz systems that can be modeled by system dynamics that are linear in parameters. With the help of a special parameterization method, the leader's trajectory can be treated as an iteration-invariant parameter