Robert J. Urick

Adjunct Professor, The Catholic University of America, Washington, D.C. Formerly Senior Research Physicist U.S. Naval Surface Weapons Center Headquarters White Oak, Silver Spring, Maryland

principles of underwater sound / 3d edition

First edition published in 1967 under the title "Principles of Underwater Sound for Engineers"

McGraw-Hill Book Company

Mw York St. Louis San Francisco Auckland Bigotá Hamburg Johannesburg London Madrid Mexico Montreal New Delhi Imama Paris São Paulo Singapore Bydney Tokyo Toronto Library of Congress Cataloging in Publication Data

Urick, Robert J.
Principles of underwater sound.

Includes bibliographies and index.

 1. Underwater acoustics.
 2. Sonar.
 I. Title.

 QC242.2.U74
 1983
 534'.23
 82-14059

 ISBN 0-07-066087-5

Copyright © 1983 by McGraw-Hill, Inc. All rights reserved. Printed in the United States of America. Except as permitted under the Copyright Act of 1976, no part of this publication may be reproduced or distributed in any form or by any means, or stored in a data base or retrieval system, without the prior written permission of the publisher.

1234567890 KGP/KGP 89876543

ISBN 0-07-066087-5

The editors for this book were Diane Heiberg and Janet Davis, the designer was Naomi Auerbach, and the production supervisor was Paul Malchow. It was set in Baskerville by Bi-Comp, Inc. Printed and bound by The Kingsport Press.

The purpose of the third edition, like that of the second, is to present new ideas, facts, and concepts that have emerged in recent years. At the same time some older and useful material has been added as deemed appropriate by the use of the book in course teaching.

The question of metric units has been given much consideration. Although scientists and engineers today use metric units universally, operations analysts and the users of sonar equipments do not, preferring to cling to the yard instead of the meter as the unit of distance—not because of the natural human reluctance to change, but because the range scales and manuals of existing equipments are calibrated in yards and nautical miles. A curious benefit of the yard in practical work is that the nautical mile can be taken with little error to be an even 2 kiloyards (actually, it is 2.025), but it is an unhandy, uneven number of kilometers (1.853). While the yard has been retained as the unit of distance, a section on the metric conversion of the sonar parameters has been included.

The basic plan of the book has remained the same: to introduce the sonar equations after an introductory chapter and then, at the end, to illustrate their use in practical sonar problem solving after the many diverse and perplexing phenomena hidden within them have been explained in the intervening chapters.

Robert J. Urick

preface to the third edition Underwater sound, as a specialized branch of science and technology, has seen service in two world wars. Although it has roots deep in the past, underwater sound, as a quantitative subject, may be said to be only a quarter of a century old. Its modern era began with the precise quantitative studies undertaken with great vigor during the days of World War II. In subsequent years, its literature has grown to sizable proportions, and its practical uses have expanded in keeping with man's continuing exploration and exploitation of the seas.

This book attempts to summarize the principles of underwater sound from the viewpoint of the engineer and the practical scientist. It lies squarely in the middle of the spectrum—between theory at one end and sonar technology at the other. Its intent is to provide a summary of the principles, effects, and phenomena of underwater sound and to give numerical quantitative data, wherever possible, for the solution of practical problems.

The framework of the book is the sonar equations—the handy set of relationships that tie together all the essential elements of underwater sound. The approach is, after an introductory chapter, to state the equations in a convenient form and then to discuss in subsequent chapters each one of the quantities occurring in the equations. The final chapter is largely devoted to problem solving, in which the use of the equations is illustrated by hypothetical problems taken from some of many practical applications of the subject.

preface to the first edition In the desire to keep the book within sizable bounds, some aspects of underwater sound have had to be slighted. One is the subject of transducers—the conversion of electricity into sound and vice versa. Although transducer arrays are discussed, only one sound source—the underwater explosion—is dealt with at any length. It is felt that the design of electroacoustic transducers for generating and receiving sound is truly an art in itself, with a technology and theoretical background that deserves a book of its own. In addition, much of the basic theory of underwater sound is confined to references to the literature, and engineering matters of sonar hardware are omitted entirely. Although the book will therefore appeal neither to the theoretician nor to the hardware builder, it hopes to cover the vast middle ground between them and be of interest to both the design engineer and the practical physicist. It is based on a course given for several years at the Catholic University, Washington, D.C., and at Westinghouse Electric Co., and the Martin Co. in Baltimore.

The book owes a great deal to my colleagues at the Naval Ordnance Laboratory for many discussions and helpful criticism. In particular, Mr. T. F. Johnston, chief of the acoustics division, has been a constant encouragement and stimulant in the long and arduous task of writing the book. My students have been helpful too in providing me with a receptive and critical audience for whatever is original in the presentation.

Robert J. Urick

abbreviations

used in the book

Abbreviation

Unit

Α ampere $d\mathbf{B}$ decibel dyne dyn fathom fm ft foot

foot per second ft/s

gram g Hz hertz hour h kHz kilohertz kyd kiloyard knots kn

micropascal μPa microsecond μ s

mi mile

millisecond ms nautical mile nmi second V volt \mathbf{W}

 $W \cdot s/cm^2$ watt-second per square centimeter

yd yard

principles of underwater sound

contents

Preface to the Third Edition ix Preface the First Edition xi Abbreviations Used in the Book xiii

one	The Nature of Sonar				
	1.1 Historical Survey 2				
	1.2	Postwar Developments 6			
	1.3	Nonmilitary Uses of Underwater Sound 7			
	1.4	Military Uses of Underwater Sound 7			
	1.5	Some Basic Concepts 11			
	1.6	The Micropascal Reference Unit and the Decibel 14 References 16			
two	The Sonar Equations				
	2.1	Basic Considerations 18			
	2.2	The Active and Passive Equations 19			
	2.3	Names for Various Combinations of Parameters 22			
	2.4	The Parameters in Metric Units 23			
	2.5	Echo, Noise, and Reverberation Level as Functions of Range 23			
	2.6	Transient Form of the Sonar Equations 25			
	2.7	Statement of the Equations 28			
	2.8	Limitations of the Sonar Equations 29			
		References 30			
three	Properties of Transducer Applys Directivity Index				
	3.1	Array Gain 33			
	3.2	Measuring the Collectific of Sound Fields 41			
	3.3	Receiving Directively Index 42			
	3.4	Limitations of Diractivity water 42			
	3.5	Transducer Responses 44			
	3.6	Calibration Methods 44			

V

vi	/	contents
		27

	3.7	Reciprocity Calibration 51				
	3.8	Calibration of Large Arrays 53				
	3.9	Beam Patterns 54				
	3.10	The Product Theorem and the Mills Cross 60				
	3.11	Shading and Superdirectivity 62				
	3.12	Adaptive Beam Forming 64				
	3.13	Multiplicative Arrays 65				
	0.10	References 68				
		Tagoronica do				
four	Generation of Underwater Sound: Projector Source Level 7					
	4.1	Relation between Source Level and Radiated Acoustic Power 73				
	4.2	Limitations on Sonar Power 76				
	4.3	Nonlinear Effects in Sonar 81				
	4.4	Explosions as Sources of Underwater Sound 86				
		References 97				
five	Propagation of Sound in the Sea: Transmission Loss, I					
	5.1	Introduction 99				
	5.2	Spreading Laws 100				
	5.3	Absorption of Sound in the Sea 102				
	5.4	Velocity of Sound of the Sea 111				
	5.5	Velocity Structure of the Sea 116				
	5.6	Propagation Theory and Ray Tracing 120				
	5.7	The Sea Surface 128				
	5.8	The Sea Bottom 136				
		References 143				
six	Prop	Propagation of Sound in the Sea: Transmission Loss, II				
	6.1	The Mixed-Layer Sound Channel 147				
	6.2	The Deep Sound Channel 159				
	6.3	Caustics and Convergence Zones 164				
	6.4	Internal Sound Channels 169				
	6.5	Artic Propagation 169				
	6.6	The Shallow-Water Channel 172				
	6.7	Fluctuation of Transmitted Sound 182				
	6.8	Horizontal Variability 190				
	6.9	Coherence of Transmitted Sound 193				
	6.10	Multipaths in the Sea 193				
	6.11	Deep-Sea Paths and Losses: A Summary 194				
		References 197				
seven	The Noise Background of the Sea: Ambient-Noise Level 202					
	7.1	Sources of Ambient Noise in Deep Water 203				
	7.2	Deep-Water Spectra 209				
	7.3	Shallow-Water Ambient Noise 211				

	7.4 7.5 7.6 7.7 7.8 7.9 7.10 7.11	Variability of Ambient Noise 215 Intermittent Sources of Ambient Noise 216 Effect of Depth 221 Amplitude Distribution 223 Noise in Ice-Covered Waters 224 Directional Characteristics of Deep-Water Ambient Noise 227 Spatial Coherence of Ambient Noise 231 Summary 233 References 233				
eight	Scattering in the Sea: Reverberation Level					
	8.1	Types of Reverberation 237				
	8.2	The Scattering-Strength Parameter 238				
	8.3	Equivalent Plane-Wave Reverberation Level 240				
	8.4	Volume-Reverberation Theory 240				
	8.5	Surface-Reverberation Theory 244				
	8.6	Target Strength and Scattering Strength 246				
	8.7	Surface Scattering by a Layer of Volume Scatterers 247				
	8.8	Reverberation Level for Short Transients 248				
	8.9	Air Bubbles in Water 249				
	8.10	Volume Reverberation: The Deep Scattering Layer 255				
	8.11	Sea-Surface Reverberation 262				
	8.12	Theories and Causes of Sea-Surface Scattering 267				
	8.13	Sea-Bottom Reverberation 271				
	8.14	Under-Ice Reverberation 280				
	8.15	Reverberation in Shallow Water 281				
	8.16	Characteristics of Reverberation 281				
	8.17	Reverberation Prediction 285 References 287				
nine	Reflection and Scattering by Sonar Targets: Target Strength 291					
	9.1	The Echo as the Sum of Backscattered Contributions 294				
	9.2	Geometry of Specular Reflection 295				
	9.3	Target Strength of a Small Sphere 298				
	9.4	Complications for a Large Smooth Solid Sphere 301				
	9.5	Target Strength of Simple Forms 302				
	9.6	Bistatic Target Strength 302				
	9.7	Target-Strength Measurement Methods 306				
	9.8	Target Strength of Submarines 308				
	9.9	Target Strength of Surface Ships 314				
	9.10	Target Strength of Mines 314				
	9.11	Target Strength of Torpedoes 315				
	9.12	Target Strength of Fish 315				
	9.13	Target Strength of Small Organisms 317				
	9.14	Echo Formation Processes 317				
	9.15	Reduction of Target Strength 320				
	9.16	Echo Characteristics 322				
	9.17	Summary of Numerical Values 325				
		References 325				

ten		ted Noise of Ships, Submarines, and Torpedoes: ted-Noise Levels	328		
	10.1	Source Level and Noise Spectra 328			
	10.2	Methods of Measurement 329			
	10.3	Sources of Radiated Noise 332			
	10.4	Summary of the Sources of Radiated Noise 341			
	10.5	Total Radiated Acoustic Power 343			
	10.6	Radiated-Noise Levels 345			
	10.7	Cautionary Remark 351			
		References 352			
eleven	Self-N	oise of Ships, Submarines, and Torpedoes:			
	Self-Noise Levels				
	11.1	Self-Noise Measurements and Reduction 356			
	11.2	Sources and Paths of Self-Noise 357			
	11.3	Flow Noise 360			
	11.4	Flow-Noise Reduction 365			
	11.5	Domes 367			
	11.6				
	11.7				
	11.8	Self-Noise Levels 372 References 376			
nweive	12.1 12.2 12.3 12.4 12.5 12.6 12.7	• • • • • • • • • • • • • • • • • • • •	377		
	12.8	Detection Threshold for Reverberation 395			
	12.9 12.10	Tabular Summary 396 Auditory Detection 396			
	12.10	References 403			
thirteen	Design and Prediction in Sonar Systems				
	13.1	Sonar Design 406			
	13.2	Sonar Prediction 407			
	13.3	The Optimum Sonar Frequency 408			
	13.4	Applications of the Sonar Equations 411			
	13.5	Concluding Remarks 416 References 416			
	Indev	417			

the nature of sonar

Of all the forms of radiation known, sound travels through the sea the best. In the turbid, saline water of the sea, both light and radio waves are attenuated to a far greater degree than is that form of mechanical energy known as sound.

Because of its relative ease of propagation, people have applied underwater sound to a variety of purposes in their use and exploration of the seas. These uses of underwater sound constitute the engineering science of *sonar*, and the systems employing underwater sound in one way or another are *sonar systems*.

Sonar systems, equipments, and devices are said to be active when sound is purposely generated by one of the system components called the projector. The sound waves generated by the projector travel through the sea to the target, and are returned as sonar echoes to a hydrophone, which converts sound into electricity. The electric output of the hydrophone is amplified and processed in various ways and is finally applied to a control or display device to accomplish the purpose for which the sonar set was intended. Active sonar systems are said to echo-range on their targets.

Passive or listening sonar systems use sound radiated (usually unwittingly) by the target. Here only one-way transmission through the sea is involved, and the system centers around the hydrophone used to listen to the target sounds. Communication, telemetry, and control applications employ a hybrid form of sonar system using a projector and hydrophone at both ends of the acoustic communication path.

1.1 Historical Survey

Although the "modern age" of sonar may be said to date back more than a quarter of a century to the start of World War II, sonar has its origins deep in the past. One of the earliest references to the fact that sound exists beneath the surface of the sea, as well as in the air above, occurs in one of the notebooks of that versatile, archetypal engineer, Leonardo da Vinci. In 1490, two years before Columbus discovered America, he wrote (1)*: "If you cause your ship to stop, and place the head of a long tube in the water and place the outer extremity to your ear, you will hear ships at a great distance from you." Although this earliest example of a passive sonar system has the enviable merit of extreme simplicity, it does not provide any indication of direction and is insensitive as a result of the great mismatch between the acoustic properties of air and water. Yet the idea of listening to underwater sounds by means of an air-filled tube between the sea and the listener's ear had widespread use as late as World War I, when, by the addition of a second tube between the other ear and a point in the sea separated from the first point, a direction could be obtained and the bearing of the target could be deter-

Perhaps the first quantitative measurement in underwater and sound occurred in 1827, when a Swiss physicist, Daniel Colladon, and a French mathematician, Charles Sturm, collaborated to measure the velocity of sound in Lake Geneva in Switzerland. By timing the interval between a flash of light and the striking of a bell underwater, they determined the velocity of sound to a surprising degree of accuracy.

Later on in the nineteenth century, a number of famous physicists of the time indirectly associated themselves with underwater sound through their interest in the phenomenon of "transduction"—the conversion of electricity into sound and vice versa (2). Jacques and Pierre Curie are usually credited with the discovery in 1880 of piezoelectricity—the ability of certain crystals, when stressed, to develop an electric charge across certain pairs of crystal faces. Other physicists had dabbled in the subject before this. Charles Coulomb is said to have speculated on the possibility of producing electricity by pressure, and Wilhelm Röntgen wrote a paper on the electric charge appearing on the various faces of crystals under stress. The counterpart of piezoelectricity as a transduction process is magnetostriction, wherein a magnetic field produces a change in the shape of certain substances. The earliest manifestation of magnetostriction was the musical sounds that were heard when, about 1840, the current in a coil of wire was changed or interrupted near the poles of a horseshoe magnet. James Joule, in the 1840s, carried out quantitative measurements on the change of length associated with magnetostriction, and is commonly credited with being the discoverer of the effect.

^{*} The parenthetical numbers throughout the text denote numbered references to the literature in a list of references at the end of each chapter.

These studies, and those of others in the 1840s and 1850s, were the foundation for the invention of the telephone, for which a long-disputed patent was issued in 1876 to A. G. Bell. Another nineteenth-century invention that was the mainstay of sonar systems before the advent of electronic amplifiers was the carbon-button microphone, a device which became the earliest, and still probably the most sensitive, hydrophone for underwater sound.

About the turn of the century there came into being the first practical application of underwater sound. This was the submarine bell, used by ships for offshore navigation. By timing the interval between the sound of the bell and the sound of a simultaneously sent blast of a foghorn, a ship could determine its distance from the lightship where both were installed. This system was the impetus for the founding of the Submarine Signal Company (now part of Raytheon Mfg. Co.), the first commercial manufacturer of sonar equipment in the United States. The method was never in widespread use and was soon replaced by navigation methods involving radio—especially radio direction finding.

Another pre-World War I achievement was the embryonic emergence of the first schemes for the detection of underwater objects by echo ranging. In 1912, five days after the "Titanic" collided with an iceberg, L. F. Richardson filed a patent application with the British Patent Office for echo ranging with airborne sound (2). A month later he applied for a patent for its underwater analog. These ideas involved the then-new features of a directional projector of kilohertz-frequency sound waves and a frequency-selective receiver detuned from the transmitting frequency to compensate for the doppler shift caused by the motion of the echo-ranging vessel. Unfortunately, Richardson did nothing at the time to implement these proposals. Meanwhile, in the United States, R. A. Fessenden had designed and built a new kind of movingcoil transducer for both submarine signaling and echo ranging and was able, by 1914, to detect an iceberg at a distance of 2 miles. Fessenden "oscillators" operating at frequencies near 500 and near 1,000 Hz are said (3) to have been installed on all United States submarines of the World War I period to enable them to signal one another while submerged. They remained in use until recently as powerful sinusoidal sound sources for research purposes.

The outbreak of World War I in 1914 was the impetus for the development of a number of military applications of sonar. In France a young Russian electrical engineer, Constantin Chilowsky, collaborated with a distinguished physicist, Paul Langevin, in experiments with a condenser (electrostatic) projector and a carbon-button microphone placed at the focus of a concave mirror. In spite of leakage and breakdown troubles caused by the high voltages needed for the projector, by 1916 they were able to obtain echoes from the bottom and from a sheet of armor plate at a distance of 200 meters. Later, in 1917, Langevin turned to the piezoelectric effect and use a quartz-steel sandwich to replace the condenser projector. He also employed one of the newly developed vacuum-tube amplifiers—probably the first application of electronics to underwater sound equipment. For the first time, in 1918,

echoes were received from a submarine, occasionally at distances as great as 1,500 meters. Parallel British investigations with quartz projectors were conducted by a group under R. W. Boyle. The word "asdic" was coined at the time to refer to their then highly secret experiments.* World War I came to a close, however, before underwater echo ranging could make any contribution to meet the German U-boat threat.

In the meantime, extensive use had been made of Leonardo's air tube for passive listening, improved by the use of two tubes to take advantage of the binaural directional sense of a human observer. The MV device consisted (5) of a pair of line arrays of 12 air tubes each, mounted along the bottom of a ship on the port and starboard sides and steered with a special compensator. Surprising precision was achieved in determining the bearing of a noisy target; an untrained observer could find the bearing of a distant target to an accuracy of ½°. Another development of the time (5) was a neutrally buoyant, flexible line array of 12 hydrophones called the "eel," which could easily be fitted to any ship and could be towed astern away from the noisy vessel on which it was mounted. All in all, some three thousand escort craft were fitted with listening devices of various kinds in World War I. By operating in groups of two or three and using cross bearings, they could obtain a "fix" on a suspected submarine contact.

In 1919, soon after the end of World War I, the Germans published the first scientific paper on underwater sound (6). This paper described theoretically the bending of sound rays produced by slight temperature and salinity gradients in the sea, and recognized their importance in determining sound ranges. Longer ranges were predicted in winter than in summer, and the prediction was verified by measurements of transmission ranges in all seasons of the year in six shallow-water areas, including two off the east coast of the United States made presumably before the entry of this country into the war in 1917. This paper was far ahead of its time and remained unrecognized for over 60 years. It is testimony to the excellence of German physics in the early years of the present century.

The years of peace following World War I saw a steady, though extremely slow, advance in applying underwater sound to practical needs. Depth sounding by ships under way was soon developed, and by 1925, fathometers, a word coined by the Submarine Signal Company for their own equipment, were available commercially in both the United States and Great Britain. The search for a practical means of echo ranging on submarine targets was conducted in the United States by a handful of men under H. C. Hayes at the Naval Research Laboratory. The problem of finding a suitable sound projector in echo ranging was solved by resorting to magnetostrictive projectors for generating the required amount of acoustic power. Also, synthetic crystals of

^{*}According to A. B. Wood (4), the word "asdic" was originally an acronym for "antisubmarine division—ics" from the name of the group which did the work. The suffix had the same significance as it does in the words "physics," "acoustics," etc. For many years thereafter, the word "asdic" was used by the British to refer to echo ranging and echoranging sonar systems generally.

Rochelle salt began to replace scarce natural quartz as the basic piezoelectric material for piezoelectric transducers. During the interwar period sonar received a great practical impetus from advances in electronics, which made possible vast new domains of amplifying, processing, and displaying sonar information to an observer.

Ultrasonic frequencies, that is, frequencies beyond the region of sensitivity of the unaided human ear, came to be used for both listening and echo ranging and enabled an increased directionality to be obtained with projectors and hydrophones of modest size. A number of small, but vital, components of sonar systems were added during this period, notably the development by the British of the range recorder for echo-ranging sonars to provide a "memory" of past events and the streamlined dome to protect the transducer on a moving ship from the noisy, turbulent environment of water flow past a moving vessel. By 1935, several fairly adequate sonar systems had been developed, and by 1938, with the imminence of World War II, quantity production of sonar sets started in the United States. By the time the war began, a large number of American ships were equipped for both underwater listening and echo ranging. The standard echo-ranging sonar set for surface ships was the QC equipment. The operator searched in bearing with it by turning a handwheel and listening for an echo with headphones or loudspeaker. If an echo was obtained, its range was noted by the flash of a rotating light or from the range recorder. Submarines were fitted with JP listening sets, consisting of a rotatable horizontal line hydrophone, an amplifier, a selectable bandpass filter, and a pair of headphones. The cost of this equipment with spares was \$5,000! With such primitive sonar sets, the Battle of the Atlantic against the German U-boats was engaged and, eventually, won.

But from a scientific standpoint, perhaps the most notable accomplishment of the years between World War I and World War II was the obtaining of an understanding of the vagaries of sound propagation in the sea. Early shipboard echo-ranging sets installed in the late twenties and early thirties were mysteriously unreliable in performance. Good echoes were often obtained in the morning, but poor echoes, or none at all, were obtained in the afternoon. When it became clear that the sonar operators themselves were not to blame and that the echoes were actually weaker in the afternoon, the cause began to be sought in the transmission characteristics of the seawater medium. Only with the use of a special temperature-measuring equipment did it become evident that slight thermal gradients, hitherto unsuspected, were capable of refracting sound deep into the depths of the sea and could cause the target to lie in what is now known as a "shadow zone." The effect was called by E. B. Stephenson the "afternoon effect." As a means to indicate temperature gradients in the upper few hundred feet of the sea, A. F. Spilhaus built the first bathythermograph in 1937; by the start of World War II, every naval vessel engaged in antisubmarine work was equipped with the device. During this period also, a clear understanding was gained of absorption of sound in the sea, and remarkably accurate values of absorption coefficients were determined at the ultrasonic frequencies 20 to 30 kHz then of interest. These and

other achievements of the interwar period are described in a paper by Klein (7).

On both sides of the Atlantic, as in World War I, the World War II period was marked by feverish activity in underwater sound. In the United States, a large group of scientists organized by the National Defense Research Committee (NDRC) began investigations of all phases of the subject.* Most of our present concepts as well as practical applications had their origins in this period. The acoustic homing torpedo, the modern acoustic mine, and scanning sonar sets were wartime developments. Methods for quick calibration of projectors and hydrophones began to be used, and an understanding of the many factors affecting sonar performance that are now summarized in the sonar equations was gained. Factors such as target strength, the noise output of various classes of ships at different speeds and frequencies, reverberation in the sea, and the recognition of underwater sound by the human ear were all first understood in a quantitative way during the years of World War II. Indeed, in retrospect, there is little of our fund of underwater acoustic knowledge that cannot be traced, in its rudiments, to the discoveries of the wartime period.

The Germans must be given credit for a number of unique accomplishments. One was the development of Alberich, a nonreflecting coating for submarines. It consisted of a perforated sheet of rubber cemented to the hull of a submarine and covered by a solid, thin sheet of rubber to keep water out of the air-filled perforations. This coating was effective only over a limited range of depth and frequency, and could not be kept bonded to the hull for long periods under operating conditions. Another innovation was the use of flush-mounted arrays for listening aboard surface ships. An array of this kind—given the designation GHG for grüppen-hört-gerät or "array listening equipment"—was installed on the cruiser "Prinz Eugen" and used with some success (8).

According to Batchelder (9), the word "sonar" was coined late in the war as a counterpart of the then-glamorous word "radar" and came into use later only after having been dignified as an acronym for sound navigation and ranging!

Underwater acoustics is now a mature branch of science and engineering, with a vast literature and a history of achievement that has only briefly been touched on in the foregoing. The historically minded reader may be referred to a number of papers on the history of sonar through the close of World War II (10–14).

1.2 Postwar Developments

The years since World War II have seen some remarkable advances in the exploitation of underwater sound, for both military and nonmilitary pur-

^{*} At the end of the war the findings of that part of NDRC engaged in underwater sound were summarized in an admirable series of some 22 reports called the NDRC Division 6 Summary Technical Reports.