

56.257.02

中国地震台网观测报告

BULLETIN OF SEISMOLOGICAL
OBSERVATIONS OF CHINESE STATIONS

1982



国家地震局地球物理研究所编
地 震 出 版 社 出 版

中国地震台网观测报告

BULLETIN OF SEISMOLOGICAL
OBSERVATIONS OF CHINESE STATIONS

1 9 8 2

中国 北京

国家地震局地球物理研究所

地震出版社 出版

INSTITUTE OF GEOPHYSICS
STATE SEISMOLOGICAL BUREAU
PUBLISHED BY SEISMOLOGICAL PRESS
BEIJING CHINA

1986

中国地震台网观测报告

(1982)

国家地震局地球物理研究所编

*

地震出版社出版

北京复兴路63号

北京印刷一厂印刷

新华书店北京发行所发行

全国各地新华书店经售

*

787×1092 1/16 55.5印张 1768字

1986年6月出版

统一书号：13180·320 定价：13.00元

目 录

序	(1)
台站目录	(5)
仪器常数	(6)
仪器放大倍率曲线	(10)
1982年地震目录	(11)
一、世界地震目录	(13)
二、中国及邻区地震目录	(124)
1982年震中分布图	(137)
一、世界地震震中分布图	(139)
二、中国及邻区地震震中分布图	(140)
1982年地震数据	(141)
1月	(143)
2月	(214)
3月	(269)
4月	(336)
5月	(394)
6月	(456)
7月	(515)
8月	(577)
9月	(642)
10月	(715)
11月	(763)
12月	(810)

CONTENTS

Introduction	(1)
List of the seismological stations	(5)
Constants of seismographs	(6)
Magnification curve of instruments.....	(10)
The Catalogue of earthquakes in 1982.....	(11)
1. The Catalogue of earthquakes in the World	(13)
2. The Catalogue of earthquakes near and within China	(124)
Illustrations of epicentral distribution in 1982.....	(137)
1. Epicentral distribution of earthquakes of the world	(139)
2. Epicentral distribution of earthquakes near and within China.....	(140)
The observed seismological data in 1982.....	(141)
January.....	(143)
February.....	(214)
March.....	(269)
April	(336)
May	(394)
June	(456)
July	(515)
August	(577)
September	(642)
October	(715)
November.....	(763)
December	(810)

序

1. 《中国地震台网观测报告》是我国地震台网对发生在全世界、特别是发生在中国和邻近地区的地震观测数据的汇编。自1979年起，本报告改用国际协调时UTC，并采用汉语拼音拼写中国地名和人名，外国地名和人名仍沿用英文。

2. 本报告测定震源参数，沿用J-B走时表^[1]。除使用报告中所列台站的数据外，还选用了一部分国内外其它地震台站的P波到时，用计算机进行修定。残差、标准偏差和标准误差分别列于计算结果和参加运算的原始数据之后。震源深度数据符号“S”，表示定位过程中选用了J-B表的表面走时。参数之后加注“*”表示选用了地方台网或国外机构的结果。

每个选定的震中都按Flinn和Engdahl等^[2,3]的分区办法给出相应的地理区。这些地区的界限沿经纬线整度划分，因而有时与国境线不符。应该强调指出，所用地震及地理区域的名称仅作位置的指引，而不包含任何政治意义。对发生在中国的地震，分别注明震中的具体地理位置。

3. 测定面波震级Ms，沿用北京台1965年的面波震级公式：

$$M_S = \log(A/T) + 1.66 \log \Delta + 3.50 \quad (1^\circ < \Delta < 130^\circ)$$

测定体波震级Mb，采用古登堡-里克特1956年的体波震级公式：

$$M_B = 1.59m - 3.97$$

式中m为统一震级

测定近震震级Ml，采用里克特的经典方法：

$$M_l = \log A + R(\Delta)$$

式中A是地动位移，以μ计，量规函数R(Δ)是由李善邦教授确定的。

4. 本报告还摘录了部分国内较大地震的宏观结果，分别附在各地震之后。其中给出的烈度，均按1957年谢毓寿教授所编《新的中国地震烈度表》^[4]标度评定。

5. 汇编《中国地震台网观测报告》采用了国际通用的符号^[5]。为便于使用计算机打印报告，对下列震相和P波初动方向的符号采用了NEIS的地震电报符号暂时予以替代，敬请注意。

PG	代表	PG	SG	代表	S或Se	LG	代表	Lg
PB	代表	P*	SB	代表	S*	PU	代表	中长周期仪器记录的+P
AP	代表	pP	XP	代表	P	PR	代表	中长周期仪器记录的-P
			XS	代表	S	PC	代表	短周期仪器记录的+P
AP KP	代表	pPKP	XP KP	代表	P KP	PD	代表	短周期仪器记录的-P

参 考 文 献

- [1] H. 杰弗里斯和K. E. 布伦 1940 地震表 伦敦不列颠协会 (1967年再版)。
- [2] E. A. 福林和E. R. 恩达尔 1965 地理和地震分区基础的建议 地球物理评论 第3卷，第123页。
- [3] E. A. 福林, E. R. 恩达尔和A. R. 希尔 1974 地震和地理分区 美国地震学会报告 第64卷 第771页。
- [4] 谢毓寿 1957 新的中国地震烈度表 地球物理学报第6卷第1期。
- [5] P. L. 维尔莫 1979 地震观测业务手册，固体地球物理世界资料中心A 报告之SE-20。

INTRODUCTION

1. The "Bulletin of Seismological Observations Of Chinese Stations" is a summary of the observed data of earthquakes occurring in the whole world, especially in China and its neighbouring regions, Beginning from 1979, the observational times and the times of epicentral estimates are given in UTC. The names of Chinese places and persons are spelt with Chinese phonetic alphabets while foreign names are all given in English.

2. All computation of focal parameters are based on the Seismological Tables by Jeffreys and Bullen^[1]. Besides the data observed at the stations listed in this Bulletin, the P arrivals at some other stations inside and outside China are used for computer revision of the parameters. The residuals, standard deviations and standard errors are listed with the results. The focal depth "S" indicates that travel times for a surface focus are used in positioning earthquake focus. An asterisk after the focal parameters indicates that the results are adopted from local network of stations or foreign agencies.

For each adopted epicenter a geographical region corresponding to that given by Flinn and Engdahl^[2] and Flinn, Engdahl and Hill^[3] is given, The boundaries of these regions follow integral degree lines of latitude and longitude and this system of division leads, on occasion, to discrepancies with state or national frontiers. It should be noted that the names used to classify seismic and geographic regions are meant to be only a guide to their location and in no way to imply any political matter. For earthquakes occurring in China, concrete geographic positions of the epicenters are given.

3. The surface wave magnitude M_s is determined, as usual, with the surface wave magnitude formula (1965) of Beijing Station (BJI)

$$M_s = \log(A/T) + 1.66 \log \Delta^\circ + 3.50 \quad (1^\circ < \Delta < 130^\circ)$$

The body wave magnitude M_b is determined with the Gutenberg-Richter formula (1965)

$$M_b = 1.59m - 3.97$$

where m is the unified magnitude.

The local magnitude M_L is determined with the Richter formula (1935)

$$M_L = \log A + R(\Delta)$$

where A is, amplitude of ground motion in μ and $R(\Delta)$ is as determined by Prof. S. P. Lee.

4. In this Bulletin are also included macroseismic phenomena of part of the major earthquakes occurring in China. The intensities listed are evaluated according to the "New Chinese Seismic Intensity Scale" of 1957 given by Prof. Xie

Yushou.^[4]

5. The Bulletin is compiled with internationally adopted symbols^[5]. For the convenience of typing out the Bulletin on a computer, the following phases and initial motion symbol of p are represented by the telegraphic symbols used by US National Earthquake Information Service, namely:

P G	represents	\bar{P}	or	Pg
P B	represents	P*		
S B	represents	S*		
AP	represents	pP		
AP XP	represents	pPKP		
S G	represents	\bar{S}	or	Sg
XP	represents	sP		
XS	represents	sS		
XP KP	represents	sPKP		
L G	represents	Lg		

PU represents +P of the broadband or Long-period record.

PR represents -P of the broadband or Long-period record.

PC represents +P of the short-period record.

PD represents -P of the short-period record.

References

- [1] Jeffreys, H. and Bullen, K. E., 1940, Seismological Tables, British Association, London, (Reprinted, with additions, 1967).
- [2] Flinn, E. A. and Engdahl, E. R., 1965, A Proposed Basis for Geographical and Seismic Regionalization, Rev. Geophys., Vol. 3, 123.
- [3] Flinn, E. A., Engdahl, E. R. and Hill, A. R., 1974, Seismic and Geographical Regionalization, Bull. Seism. Soc. Am., Vol. 64, 771.
- [4] Hsieh(Xie) Yushou, 1957, A New Scale of Seismic Intensity adapted to the Conditions in Chinese Territories, Acta Geophysica Sinica, Vol. 6, №. 1, pp. 35-47.
- [5] Willmore, P. L., 1979, Manual of Seismological Observatory Practice, World Data Center A for Solid Earth Geophysics, Report SE-20.

一九八二年地震观测资料 汇编工作人员

Compiling personnel of the observed seismological
data in 1982

主 编：曲克信

责任编辑：赵凤竹 房明山

震相分析校核：金桂芳、赵其玲、杜安陆、黄 瑾

计 算：王科英 贺冬梅

Chief editor: Qu Kexin

Managing editor: Zhao Fengzhu, Fang Mingshan

Analysers, Revisers of seismic phases: Jin Guifang, Zhao Qiling, Du Anlu,
Huang Jin

Calculator: Wang Keying, He Dongmei

LIST OF THE SEISMOLOGICAL STATIONS

Station Name	Code	Geographical Coordinates φ N	λ E	Altitude h m	Foundation	Instruments
Baotou (Paotow)	BTO (PT)	40° 35' 54"	110° 01' 06"	1120	Granite-Gneiss	SK, 64
Beijing (Peking)	BJI (PK)	40 02 25	116 10 30	43	Gravel bed	SK, 62, 513
Changchun	CN2	43 48 05	125 26 54	230	Slate	SK, 64, 513
Chengdu (Chengtu)	CD2 (CU)	30 54 36	103 45 28	628	Conglomerate	SK 513
Gaotai (Kaotai)	GTA	39 24 38	99 48 52	1341	Granite	SK, 62, DD-1
Guangzhou (Canton)	GZH (CT)	23 05 13	113 20 38	11	Sandstone	SK, DD-1, 513
Guiyang	GYA (HS)	26 27 31	106 39 50	1162	Dolomite	SK, DD-1
Hohhot (Huhehot)	HHC	40 50 58	111 33 49	1169	Rhyolite	SK, DD-1
Kashi (Kashi)	KSH (KS)	39 27 19	75 58 48	1286	Alluvialclay	SK
Kunming	KMI (KM)	25 07 24	102 44 24	1945	Basalt	SK, DD-1
Lanzhou (Lanchow)	LZH (LC)	36 05 12	103 50 40	1560	Lehm	SK, 64, 513
Lhasa	LSA (LS)	29 42 00	91 09 00	3789	Granite	SK
Mudan Jiang (Mutan River)	MDJ	44 36 59	129 35 31	250	Granite	SK, DD-1, 513
Nanjing	NJ2	32 03 06	118 51 16	45	Silicarenite	SK, DD-1, 513
Quanzhou	QZH (CCW)	24 56 35	118 35 30	21	Granite	SK, 64
Sheshan (Sose)	SSE (ZS)	31 05 44	121 11 12	10	Andesite	SK, DD-1
Tai'an	TIA (TA)	36 12 41	117 07 28	300	Amphibole-Granite	SK, 64, 513
Taiyuan	TIY	37 42 47	112 26 03	850	Limestone	SK, DD-1, 64
Urumqi (Urumchi)	WMQ (UM)	43 49 16	87 41 42	970	Sandstone	SK, 62
Wuhan (Wuchang)	WHN (WC)	30 32 37	114 21 01	26	Silicarenite	SK, DD-1
Xian (Sian)	XAN (SA)	34 02 22	108 55 17	630	Granite	SK, DD-1, 513

* The Code CD2 for Chengdu has been used since 1. Oct 1980 instead of CDU, because of the shift of the station.

仪 器 常 数

Constants of Seismographs

台站代号 station Code	仪器型号 type of Instruments	分 向 Comp.	T ₁	T ₂	D ₁	D ₂	σ^2	V ₀	r ₁	R _v mm/min	记 录 方 式 Recorder Type
BTO	SK	N-S	12.5	1.2	0.45	4.9	0.109	2.07×10^3			照像纸 Photo paper
		E-W	12.5	1.2	0.45	5.1	0.092	1.70×10^3		30	
		U-D	12.5	1.2	0.63	5.1	0.383	1.16×10^3			
	(473)	N-S	1.5		0.5			5.64×10^4			熏烟纸 Smoked paper
		E-W	1.5		0.5			5.85×10^4		120	
		U-D	1.5		0.5			3.71×10^4			
BJI	SK	N-S	12.5	1.1	0.45	5.4	0.092	1.82×10^3			照像纸 Photo paper
		E-W	12.5	1.1	0.45	5.4	0.083	1.64×10^3		30	
		U-D	12.6	1.1	0.59	5.5	0.288	0.87×10^3			
	62	N-S	1.5	0.4	0.7	1.5		3.30×10^4			照像纸 Photo paper
		E-W	1.5	0.4	0.7	1.5	0.058	3.21×10^4		60	
		U-D	1.5	0.4	0.7	1.5		3.93×10^4			
CN2	SK	N-S	12.5	1.2	0.45	5.0	0.081	1.48×10^3			照像纸 Photo paper
		E-W	12.5	1.2	0.45	5.0	0.085	1.73×10^3		30	
		U-D	12.5	1.2	0.60	5.0	0.338	1.30×10^3			
	(473)	N-S	1.5		0.45			17.05×10^4			熏烟纸 Smoked paper
		E-W	1.5		0.45			17.35×10^4		120	
		U-D	1.5		0.45			5.28×10^4			
	DD-1	N-S	1.0		0.45			11.40×10^4		120	墨水笔 Pen and ink
		E-W	1.0		0.45			10.10×10^4			
		U-D	1.0		0.45			2.34×10^4			
CD2	SK	N-S	12.5	1.2	0.45	5.0	0.040	1.47×10^3			照像纸 Photo paper
		E-W	12.5	1.2	0.45	5.0	0.041	1.47×10^3		30	
		U-D	12.5	1.2	0.55	5.0	0.169	1.01×10^3			
	DD-1	N-S	1.0		0.45			9.06×10^4			墨水笔 Pen and ink
		E-W	1.0		0.45			6.92×10^4		120	
		U-D	1.0		0.45			7.83×10^4			
GTA	SK	N-S	12.5	1.2	0.45	5.0	0.07	1.94×10^3			照像纸 Photo paper
		E-W	12.5	1.2	0.45	5.0	0.08	1.77×10^3		30	
		U-D	12.5	1.2	0.70	5.0	0.32	1.51×10^3			
	62	N-S	1.0	0.58	0.6	1.5	0.25	2.67×10^5			照像纸 Photo paper
		E-W	1.0	0.58	0.6	1.5	0.25	2.58×10^5		120	
		U-D	1.0	0.48	0.6	1.5	0.25	1.52×10^5			
GZH	SK	N-S	12.5	1.2	0.45	5.0	0.075	1.54×10^3			照像纸 Photo paper
		E-W	12.5	1.2	0.45	5.0	0.068	1.39×10^3		30	
		U-D	12.5	1.2	0.56	5.0	0.299	0.99×10^3			
	DD-1	N-S	1.0		0.45			$*3.59 \times 10^4$			墨水笔 Pen and ink
		E-W	1.0		0.45			$*4.44 \times 10^4$		120	
		U-D	1.0		0.45			$*2.77 \times 10^4$			
	513	N-S	5.0		0.33			5.0×10			熏烟纸 Smoked paper
		E-W	5.0		0.35			4.8×10		30	


续表

台站代号 station Code	仪器型号 type of Instruments	分向 Comp	T ₁	T ₂	D ₁	D ₂	σ^2	V ₀	r ₁	R _v mm/min	记录方式 Recorder Type
GYA	SK	N-S E-W U-D	12.5 12.5 12.5	1.2 1.2 1.2	0.45 0.45 0.45	5.1 5.0 4.9	0.090 0.071 0.299	1.49×10^3 1.45×10^3 0.77×10^3		30	照像纸 Photo paper
		DD-1	N-S E-W U-D	1.0 1.0 1.0		0.45 0.45 0.45		* 7.90×10^4 * 7.23×10^4 * 5.82×10^4		120	墨水笔 Pen and ink
HHC	SK	N-S E-W U-D	12.5 12.5 12.5	1.2 1.2 1.2	0.45 0.45 0.60	5.1 5.1 5.3	0.1 0.1 0.3	2.54×10^3 2.72×10^3 1.23×10^3		30	照像纸 Photo paper
		DD-1	N-S E-W U-D	1.0 1.0 1.0		0.45 0.45 0.45		* 1.52×10^5 * 1.47×10^5 * 0.61×10^4		120	墨水笔 Pen and ink
KSH	SK	N-S E-W U-D	12.5 12.5 12.5	1.2 1.2 1.2	0.45 0.45 0.54	5.0 5.0 5.0	0.039 0.032 0.249	1.12×10^3 0.68×10^3 0.83×10^3		30	照像纸 Photo paper
KMI	SK	N-S E-W U-D	12.5 12.5 12.5	1.1 1.1 1.1	0.45 0.45 0.60	5.5 5.5 5.5	0.092 0.080 0.322	1.47×10^3 1.40×10^3 0.90×10^3		30	照像纸 Photo paper
		62	N-S E-W U-D	3.0 3.0 2.0	0.1 0.1 0.1	0.6 0.6 0.6	5.0 5.0 5.0	2.00×10^4 2.00×10^4 2.01×10^4		60	照像纸 Photo paper
LZH	SK	N-S E-W U-D	12.5 12.5 12.5	1.2 1.2 1.2	0.45 0.45 0.59	5.1 5.0 5.0	0.078 0.077 0.359	1.44×10^4 1.55×10^4 1.02×10^4		30	照像纸 Photo paper
		64	N-S E-W U-D	2.5 2.5 2.5	0.1 0.1 0.1	0.5 0.5 0.5	6.0 6.0 6.0	0.25 0.25 0.25	2.27×10^4 2.27×10^4 2.65×10^4		60
	513	N-S E-W	5.0 5.0		0.32 0.36			4.1×10 4.6×10	0.15 0.17	30	熏烟纸 Smoked paper
L SA	SK	N-S E-W U-D	12.5 12.5 12.5	1.2 1.2 1.2	0.45 0.45 0.56	4.9 4.8 5.1	0.084 0.090 0.238	1.54×10^3 1.74×10^3 0.77×10^3		30	照像纸 Photo paper
MDJ	SK	N-S E-W U-D	12.6 12.6 12.6	1.2 1.2 1.2	0.45 0.45 0.55	4.7 5.0 5.0	0.27 0.23 0.20	2.42×10^3 2.00×10^3 0.85×10^3		130	照像纸 Photo paper
		DD-1	N-S E-W U-D	1.0 1.0 1.0		0.45 0.45 0.45		* 5.13×10^4 * 4.90×10^4 * 4.80×10^4		120	墨水笔 Pen and ink
NJ2	SK	N-S E-W U-D	12.5 12.5 12.5	1.2 1.2 1.2	0.45 0.45 0.60	5.0 5.0 5.0	0.081 0.092 0.268	2.02×10^3 1.50×10^3 1.26×10^3		130	照像纸 Photo paper
		DD-1	N-S E-W U-D	1.0 1.0 1.0		0.45 0.45 0.45		3.39×10^4 3.73×10^4 6.16×10^4		120	墨水笔 Pen and ink
	763	N-S E-W U-D	15.0 15.0 15.0	96.5 102 97.3	1.0 1.0 1.0	1.0 1.0 1.0	0.190 0.190 0.193	1.53×10^3 1.46×10^3 1.40×10^3		15	照像纸 Photo paper
	513	N-S E-W	4.8 5.0		0.36 0.36			7.3×10 4.6×10	0.25 0.28	30	熏烟纸 Smoked paper

续表

台站代号 station Code	仪器型号 type of Instruments	分向 Comp	T ₁	T ₂	D ₁	D ₂	σ^2	V ₀	r ₁	R _v mm/min	记录方式 Recorder Type
NJ2	S W	N-S E-W	1.40 1.40		0.337 0.262			1.62×10^3 1.10×10^3		30	熏烟纸 Smoked paper
QZH	S K	N-S E-W U-D	12.5 12.5 12.5	1.2 1.2 1.2	0.45 0.45 0.45	5.0 4.9 5.0	0.089 0.078 0.085	1.92×10^3 1.63×10^3 1.19×10^3		30	照像纸 Photo paper
		64 (473)	N-S E-W U-D	1.5 1.5 1.5		0.45 0.45 0.45		* 2.06×10^4 * 2.73×10^4 * 1.75×10^4		120	熏烟纸 Smoked paper
	513	N-S E-W	5.0 5.0		0.33 0.37			6.6×10 5.8×10			熏烟纸 Smoked paper
	763	N-S E-W U-D	15.0 15.0 15.0	100.0 100.0 100.0	1.0 1.0 1.0	1.0 1.0 1.0	0.024 0.031 0.025	1.50×10^3 1.50×10^3 1.50×10^3		15	照像纸 Photo paper
SSE	S K	N-S E-W U-D	12.5 12.5 12.5	1.2 1.2 1.2	0.45 0.45 0.55	5.1 5.0 5.1	0.074 0.081 0.230	2.06×10^3 2.06×10^3 0.90×10^3		30	照像纸 Photo paper
		DD-1	N-S E-W U-D	1.0 1.0 1.0		0.45 0.45 0.45		* 7.57×10^4 * 5.43×10^4 * 5.20×10^4		120	墨水笔 Pen and ink
	763	N-S E-W U-D	15.0 15.0 15.0	98.6 102.6 96.8	1.0 1.0 1.0	1.0 1.0 1.0	0.25 0.25 0.25	2.36×10^3 2.14×10^3 2.05×10^3		15	照像纸 Photo paper
TIA	S K	N-S E-W U-D	12.5 12.5 12.5	1.2 1.2 1.2	0.45 0.45 0.52	5.0 5.0 5.0	0.084 0.103 0.219	1.44×10^3 1.72×10^3 0.78×10^3		30	照像纸 Photo paper
		DD-1	N-S E-W U-D	1.0 1.0 1.0		0.45 0.45 0.45		* 1.47×10^5 * 1.42×10^5 * 0.98×10^5		120	墨水笔 Pen and ink
	64 (473)	N-S E-W U-D	1.5 1.5 1.5		0.45 0.45 0.45			* 3.90×10^4 * 5.40×10^4 * 4.60×10^4		120	熏烟纸 Smoked paper
	513	N-S E-W	5.0 5.0		0.33 0.33			9.9×10 9.5×10		30	熏烟纸 Smoked paper
TIY	S K	N-S E-W U-D	12.5 12.5 12.5	1.2 1.2 1.2	0.45 0.45 0.59	5.1 5.0 5.0	0.092 0.088 0.322	1.77×10^3 1.79×10^3 0.84×10^3		30	照像纸 Photo paper
WMQ	S K	N-S E-W U-D	12.5 12.5 12.5	1.2 1.2 1.2	0.45 0.45 0.61	5.0 5.0 5.0	0.100 0.088 0.349	1.73×10^3 1.63×10^3 1.03×10^3		30	照像纸 Photo paper
		62	N-S E-W U-D	2.0 2.0 2.0	0.5 0.5 0.5	0.5 0.5 0.5	1.5 1.6 1.6	6.80×10^1 6.10×10^1 6.80×10^1		60	照像纸 Photo paper
WHN	S K	N-S E-W U-D	12.5 12.5 12.6	1.2 1.2 1.2	0.45 0.45 0.56	4.9 5.0 5.0	0.088 0.087 0.305	1.71×10^3 1.57×10^3 1.01×10^3		30	照像纸 Photo paper
		DD-1	N-S E-W U-D	1.0 1.0 1.0	0.1 0.1 0.1	0.45 0.45 0.45	0.7 0.7 0.7	* 2.09×10^4 * 1.88×10^4 * 2.95×10^4		120	墨水笔 Pen and ink
	DD-1	S K	N-S E-W U-D	12.5 12.5 12.5	1.2 1.2 1.2	0.45 0.45 0.62	5.0 5.0 5.0	0.091 0.094 0.353	2.32×10^3 2.33×10^3 1.40×10^3	30	照像纸 Photo paper
XAN	DD-1	N-S E-W U-D	1.0 1.0 1.0		0.45 0.45 0.45			1.00×10^5 9.80×10^4 7.95×10^4		120	墨水笔 Pen and ink

62: type 62 seismograph with galvanometer recording
64: type 64 seismograph with galvanometer recording or with electronic amplifier and pen recorder
SK: type SK (Kirnos) seismograph with galvanometer recording
DD 1: type DD-1 seismograph with electronic amplifier and pen recorder
 T_1 : Pendulum period in sec.
 T_2 : Galvanometer period in sec.
 D_1 : Damping coefficient of pendulum
 D_2 : Damping coefficient of galvanometer
 σ^2 : Coupling coefficient
 r_1 : Amplitude of friction
 V_0 : Static magnification. An asterisk indicates magnification at T_1 .
 R_V : Paper speed in mm/min



1982 年 地 震 目 录

The Catalogue of Earthquakes in 1982

