

OFFICIAL PROCEEDINGS  
OF THE THIRTEENTH  
INTERNATIONAL

# **POWER QUALITY 2000**

Presented at

**POWERSYSTEMS WORLD<sup>®</sup> 2000  
CONFERENCE & EXHIBIT**

OCTOBER 3-5, 2000  
BOSTON, MASSACHUSETTS

M1-37  
887.4  
0000

OFFICIAL PROCEEDINGS  
OF THE THIRTEENTH  
INTERNATIONAL

# POWER QUALITY 2000

Presented at

## POWERSYSTEMS WORLD<sup>®</sup> 2000 CONFERENCE & EXHIBIT



OCTOBER 3-5, 2000  
BOSTON, MASSACHUSETTS



E200200146

This Book Is the Property of:

**This document is distributed exclusively by:**

**Adams/Intertec International Inc.**

**2472 Eastman Ave., #33**

**Ventura, CA 93003-5792, U.S.A.**

**Phone: 805-650-7070**

**Fax: 805-650-7054**

**Conference Manager  
Linda McCay**

**Copyright © 2000 by  
Adams/Intertec International Inc.**

**ISBN 0-931033-77-2**

**Thirteenth International  
Power Quality 2000  
October 2000**

**Published by Adams/Intertec International Inc.  
2472 Eastman Ave., #33  
Ventura, CA 93003-5792, U.S.A**

All rights reserved. This book, or any part thereof, may not be reproduced in any form without permission of the publisher. Printed in the United States of America. The responsibility for the content of each paper rests solely with its author. The publisher assumes no liability for the use of the information herein, nor for any infringements of patents, or other rights of third parties.



# POWER QUALITY 2000

## Proceedings

at

## POWERSYSTEMS WORLD® 2000

Technical Papers and Authors

Page No.

### PQ1A – Opening Session

#### Tomorrow's Superconducting Solutions for the Power Quality Industry

– Greg Yurek, American Superconductor. .... \*

#### Power Quality Solutions and Services – What is the Future After Deregulation

– Ram Mukherji, Enron Energy Services Operations ..... 859

#### Future Trends in Power Quality Solutions

– Tom Key, EPRI/PEAC. .... \*

### PQ2A – Power Quality Monitoring #1

#### Integrating Permanent Power Quality Monitoring into a Critical Operations Center

– Brad Gibson, Current Thinking Inc. .... 1

#### Voltage Sag Generators – Not As Simple As They Seem

– Alex McEachern, Power Standards Testing Laboratory ..... 8

#### Line to Ground Voltage Monitoring on Ungrounded and Impedance Grounded Power Systems

– Reza Tajali, Square D Company ..... 13

#### Intelligent Monitoring of Power Quality Using Substation and Feeder Equipment

– D. Hart, R. Wright, C. LaPlace, R. Ochoa, D. Uy, ABB-ETI ..... 28

#### Power Quality and Disturbance Recording

– David Guillot, ALSTOM Transmission & Distribution, France ..... 862

#### Some Aspects Regarding Digital Flicker Measurement

– Werner Mühlegger, Christoph Spielmann, Lem Norma GmbH, Austria. .... 38

### PQ2B – Premium Power Solutions

#### An Intelligent Solid State Switch for Ultimate Power Quality While Switching

– William LeCourt, Mik-Lin-Jul Corporation. .... 47

#### Operational Experience of Static Var Systems for Control of Flicker While Starting Various Sized Synchronous Motors

– Joseluis Castañeda, Central Arizona Project. .... 54

\* Paper not available at time of printing. May or may not be available at the Conference.



<b>Custom Power Reduces Wafer Production Losses: A Case Study</b> – Thomas La Rose, Salt River Project .....	69
<b>Progress Report on the Premium Power Park</b> – Michele Peel, George Gurlaskie, Siemens Power T&D; Harry Volkhommel, AEP; Laurence Carmichael, EPRI. ....	78
<b>Transfer Switches and Sags</b> – James Funke, Cutler-Hammer, Canada .....	*
<b>Dynamic Reactive Compensation</b> – Tony Jefferson, Trench Limited, Canada .....	*

## **PQ2C – Power Quality Design Considerations**

<b>Rapid Growth of Power Quality Problems</b> – Mohan Ray, Northrop Grumman Corp. ....	94
<b>Worst Case Power Quality Environments and Design of Power Electronic Products: Experiences of a Design Team In a Developing Country</b> – Nihal Kularatna, Arthur C. Clarke Institute, Sri Lanka .....	109
<b>Power Quality Compatibility &amp; Compliance</b> – Thomas Frail, Frank Sinicola, Peter Muccio, Con Edison; Jon Munderloh, Kenneth Griffing, Michael Hiles, Field Management Services Corp. ....	117
<b>Taking the Sensitive out of Sensitive Electronic Equipment</b> – Edward Gulachenski, Quality Power Engineering. ....	123
<b>Using IEC61000-3-2/3 Approach as the Basis for North American Power Quality Standards</b> – Mathieu van den Bergh, California Instruments .....	130

## **PQ3A – Power Quality Monitoring #2**

<b>Independent Modules to Ensure Vendor-Independence in Utility-Wide PQ Monitoring Systems</b> – Pramod Parihar, Mehmet Celik, Edwin Liu, Nexant, LLC. ....	*
<b>Power Analysis Using Real Time Data</b> – Brian Prokuda, Keweenaw Power Systems Inc. ....	*
<b>Studies of Power Quality: Disturbance Recognition</b> – M. Negnevitsky, J. Huang, M. Ringrose, University of Tasmania; M. Piekutowski, Hydro-Electric Corp. of Tasmania; M. Green, Transend Networks, Australia ...	137
<b>Accuracy Implications in the Power Quality World</b> – Alex Dorchak, Fluke Corporation; Afroz Khan, Mike Gipe, Reliable Power Meters. ....	*
<b>Power Quality – Survey and Monitoring</b> – Roland Provost, Maurice Ouellette, GE Industrial Systems .....	148
<b>Assessing a Power Quality Program in Southeast Asia</b> – Victor Wong, Sarawak Electricity Supply Corp.; Afroz Khan, Reliable Power Meters; Terry Chandler, Power Quality Inc. ....	158

## PQ3B – Transmission & Distribution Power Quality Concerns #1

<b>An Investigation Into Harmonic Current Flow on a 66KV Transmission Line</b> – R.A. Kolt, R. Price, Manitoba Hydro, Canada . . . . .	165
<b>The Impact of Mains Impedance on Power Quality</b> – Michael Russell, PowerLines . . . . .	176
<b>EHV Power Transformers Failures Case Study</b> – Nasrullah Khan, N. Mariun, M. Ramzan, University Putra Malaysia . . . . .	189
<b>The SyncCap Power Quality Switch: Minimizing Switching Transients on Power Systems During Capacitor Switching</b> – Frank DeCesaro, John Baranowski, Michael Dunk, Cooper Power Systems; Dwayne Tector, Georgia Power Co. . . . .	197
<b>Intelligent Feeder Automation to Minimize Customer Outages</b> – Carl LaPlace, David Hart, Will Mangum, , Marco Tellarini, John Saleeby, Richard Brown, ABB Power T&D Co. . . . .	207
<b>Automated Fault Location System for Primary Distribution Feeders</b> – Eduardo Senger, Clóvis Goldemberg, Giovanni Manassero Jr., Escola Politécnica de USP, Brazil. . . . .	215

## PQ3C – Motor & Drive System Compatibility

<b>The Impact of Thousands of Submersible Pumps Operating with VFD's on a Rural Electric System</b> – Rick Browne, Powder River Energy Corporation . . . . .	222
<b>Case Study: Power Quality in Mexico</b> – Jose R. Garnica, PowerCET Latinoamerica S.A. de C.V. . . . .	231
<b>Motors Operate on Large Unbalanced Voltage</b> – Richard Morash, Precise Power Corporation . . . . .	238
<b>A New Approach to Mitigate Nuisance Tripping of PWM ASDs Due to Utility Capacitor Switching Transients (CSTs)</b> – José Durán-Gómez, Prasad Enjeti, Texas A&M University . . . . .	247
<b>Utility-Friendly Interface Options for Variable Speed Drives</b> – Madhav Manjrekar, Tor-Eivind Moen, Kari Tikkanen, ABB Automation Inc. . . . .	255

## PQ4A – UPS Solutions for the Industry

<b>Powering the Internet: AC, DC or Hybrid Power Solutions for Today's Telecommunications Facilities</b> – Thomas Gruzs, Liebert Corporation. . . . .	271
<b>The Distribution UPS as an Alternative to Conventional UPS</b> – Ken Mattern, Michele Peel, Scott Henneberry, Siemens Power T&D. . . . .	*

\* Paper not available at time of printing. May or may not be available at the Conference.

<b>Next Generation UPS Technology for the Next Millennium</b> – Joergen Madsen, American Power Conversion .....	282
<b>Overcoming UPS/Generator Interface Problems</b> – John Tracy, Powerware Corporation .....	289
<b>Power Quality Evaluation of 480-V, 2-MVA UPS System</b> – Ernst Camm, Brad Roberts, S&C Electric Company; Garth Corey, Sandia National Laboratories .....	292
<b>A Flywheel Storage System for Power Quality Applications</b> – Hilmar Darrelmann, Piller GmbH, Germany .....	302

## **PQ4B – Transmission & Distribution Power Quality Concerns #2**

<b>Voltage Flicker on a 13.8kV Feeder: Causes and Solutions</b> – Fouad Dagher, James Bauer, Massachusetts Electric Co. .... *	
<b>Power Quality Degradation Caused by Congested Transmission System and Dynamic Loads</b> – Álvaro J.P. Ramos, Daniel C.P. de Lira, Escola Politécnica de UPE, Brazil .....	310
<b>Distributed DSP Coupled with Precise Time Synchronization Allows Unprecedented Integration of Substation Automation and Control</b> – Bruce Roeder, Arbiter Systems Inc. ....	316
<b>International Transmission Line Fault Performance Survey and Voltage Sag Profile Derivations</b> – Mark McGranaghan, Bill Roettger, Electrotek Concepts .....	321
<b>Improving Distribution System Power Quality Using Capacitors and Voltage Regulators</b> – Ljubomir Kojovic, Cooper Power Systems .....	331

## **PQ4C – Utility Deregulation and Power Quality**

<b>Cooperation Between Electric Utility and Sensitive Customers in Improving Service Power Quality and Reliability</b> – Yakov Shlemenzon, R.W. Beck Inc. ....	342
<b>Utility Deregulation Contracts: An Opportunity for the Customer to Obtain Premium Power Solutions from Energy Services Providers or Their DISCOs</b> – Richard D'Aquanni, Applied Resources Group Inc.; Gary Markowitz, Kilojolts Consulting Group .....	353
<b>Electric Power Quality and Reliability: Is There a Role for Formal Regulatory Standards? Current Perspectives of State Regulators</b> – John Howe, American Superconductor; Mary Wallan, Mary C. Wallan Communications .....	370
<b>How to Manage Power Quality in Your Contract with Power Providers</b> – Tom Ma, Hatch Associates .....	380
<b>Power Quality and New Energy Market in Romania</b> – Tudor Serban, CONEL; Ion Lungu, Stefan Gheorghe, Electrica SA, Romania. ....	391



## PQ5A – Distributed Generation as a Power Quality Solution

<b>Increasing Power Reliability via Distribution Generation</b> – E.J. Honton, Sarah Safir, Resource Dynamics Corporation .....	397
<b>Power Quality Impact of Implementing Distributed Generation</b> – Vladi Basch, Baltimore Gas & Electric .....	403
<b>Operation of a Network Based Technology to Facilitate Expanded Use of Distributed Energy</b> – Dr. John Balachandra, California State University, Sacramento; Eugene Weaver, Robert Davis, Atlas Energy Systems; Dave McShane, Capstone Turbine Corp. ....	410
<b>Short Voltage Sags in Electrical Power</b> – Dan Smith, AMD .....	*
<b>Fuel Cells – Improving the Bottom Line</b> – Thomas Ditoro, HDR Architecture, Inc. ....	421
<b>Voltage and Power Quality Control in Wind Power Applications by Means of Dynamic Compensation</b> – Rolf Grünbaum, ABB Power Systems AB, Sweden .....	431

## PQ5B – Power Quality Industry Solutions #1

<b>Interference and Grounding: Three Case Studies</b> – Robert Schuerger, Electro-Test Inc. ....	447
<b>Proactive Power Quality Assessment Process for Medical Imaging Equipment</b> – David Rush, General Electric Medical Systems .....	454
<b>Innovative Power Factor Correction Integrated in MV Switchboard</b> – Robert Borlotti, ABB SACE TMS; Carlo Gemme, Andrea Moratto, ABB Ricerca; Richard Tinggren, ABB Secheron, Italy .....	467
<b>Applying Basic Physics Laws to Solve Power Quality Problems</b> – Luis Ramón Gonzalez, Ramón Fernandez Barboza, DIRAM SA de CV, Mexico. ....	476
<b>Low-Cost Power Quality Mitigation Techniques</b> – Juan Menendez, Paul Ortmann, Southern California Edison .....	485
<b>A High Speed Transfer System Utilizing Medium Voltage Power Circuit Breakers</b> – Richard Tyner, ABB Power T&D Company, Inc. ....	873

## PQ5C – Battery Energy Storage for Power Quality

<b>Improved VRLA Battery Maintenance Programs Using Conductance Test Technology</b> – Daniel Cox, Midtronics Inc. ....	490
<b>Effective Remote Monitoring of Industrial Battery Systems: A Technological Breakthrough</b> – Larry Pfeil, MetriXX USA Inc. ....	498
<b>Intermittent Charging of Stationary Batteries</b> – George Mayer, Battery Technology Center Inc.; Charles Burns, AutoCap Inc. ....	*

\* Paper not available at time of printing. May or may not be available at the Conference.

<b>Ensuring Lead-Acid Battery Performance With Pulse Technology</b>	
– Scott Schilling, PulseTech Products Corporation . . . . .	507

<b>VRLA Batteries: Predominate Problems and Concerns, A Battery Manufacturers Evaluation</b>	
– J. Rhoades, F.J. Vaccaro, B. Le, Power Battery Company, Inc. . . . .	516

## **PQ6A – Harmonic Detection and Mitigation**

<b>Estimating Customer Contribution to Power Supply Harmonic Fluctuations</b>	
– Nedeltcho Kandev, Hydro-Québec, Canada. . . . .	524

<b>Power Quality Problems in High-Rise Commercial Buildings</b>	
– Dr. Kai-Sang Lock, PQR Technologies. . . . .	531

<b>Problems with Applying IEEE Std. 519</b>	
– Syed Peeran, Peeran Engineering Inc. . . . .	540

<b>Finding and Determining the Influence of Multiple Harmonic Sources on a Utility System Using Harmonic Measurements</b>	
– Michael Marz, John Witte, Cooper Power Systems; Donna Williams, Philip Thompson, Illinois Power . . . . .	547

<b>Using Harmonic Measurements and Simulations to Efficiently Design 300 Mvar Filters for Power Factor Correction and Harmonic Compliance</b>	
– Michael Marz, Karl Fender, Cooper Power Systems; Dan Roscoe, Ormet Primary Aluminum Corporation . . . . .	560

## **PQ6B – Power Quality Solutions #2**

<b>Power Quality Improvement and Power Factor Correction for a Mexican Petrochemical Facility with Own Electrical Generation</b>	
– Ignacio Suarez, INELAP SA de CV, Mexico. . . . .	571

<b>Powering the Internet</b>	
– Alan Katz, MGE UPS Systems . . . . .	579

<b>Power Quality with New Generation of 3 Phase Switch Mode Rectifiers</b>	
– Robert Szasz, AT&T Canada Corp.; C. Donovan Davidson, Argus Technologies Ltd., Canada . . . . .	589

<b>Industrial Application of Flywheels</b>	
– Kim Craven, Duke Power; Roger Lawrence, EPRI ASDO. . . . .	599

<b>Hybrid System for Unbalanced and Reactive Currents Compensation in Three Phase Three Wires Systems</b>	
– M. Chindris, S. Stefanescu, A. Cziker, Technical University of Cluj-Napoca, Romania; A.S. Andreu, Universitat Politècnica de Catalunya, Spain . . . . .	606

<b>Study of a Cement Plant Experiencing Power Quality Problems in Uruguay</b>	
– Diego Bentancur, Gustavo Perez, Alejandro Pardo, Aldo Rondoni, UTE, Uruguay . . . . .	614

## PQ6C – Transient Mitigation – Shielding, Grounding, Suppressing & Fueling

<b>Shielding and Grounding of Control Cables in Switching Stations to Reduce Surges</b> – Selim Trabulus, Yildiz Teknik Üniversitesi, Turkey . . . . .	620
<b>Zero Threshold Surge Suppressor – A New Approach to Suppressing Transients</b> – Rudy Wodrich, Tommy Mok, Schneider Electric, Canada . . . . .	627
<b>Methods for Transient Free and High Speed Medium Voltage Capacitor Switching</b> – Rudy Wodrich, Schneider Electric, Canada . . . . .	*
<b>Fusing Considerations for Surge Protection Devices</b> – Peter Lewis, Intermatic Inc. . . . .	*
<b>Surge-Rated Fuses for TVSS System Protection</b> – Robert Wilkins, Consultant, United Kingdom; Dan Dunlap, Ferraz Shawmut . . . . .	637

## Power Session #1

<b>Combining the Slow Speed Flywheel Kinetic Energy Storage System with the Micro Turbine to Provide a Fully Integrated Batteryless Power Back Up for Critical Installations</b> – Robert Davis, Eugene Weaver, Atlas Energy Systems; Dave McShane, Capstone Turbine Corp. . . . .	648
<b>A Unified Approach to Power Converter Modules for Distributed Generation Applications</b> – George Robinson, Yuri Khersonsky, L3 Communications . . . . .	662
<b>Efficiency of Three Winding, Single-Phase Induction Motor Under Distorted Voltage Waveform</b> – ShyShenq Liou, Demetrio Aguiar, Peter Leung, San Francisco State University . . . . .	675
<b>Analysis of Poly-Phase Voltage Sags and Their Effects on Adjustable Speed Drive Systems</b> – José Durán-Gómez, Prasad Enjeti, Texas A&M University . . . . .	689
<b>Harmonics Produced by Transformer Saturation</b> – Guilherme A.D. Dias, Marcos Telló, Fausto B. Libano, Pontificia Universidade Católica do Rio Grande do Sul, Brazil . . . . .	695
<b>Power Quality Assessment and Harmonic Comparison of Typical Solid State Loads</b> – Virendra Kumar Sharma, Jamia Millia Islamia; Dr. H.C. Rai, Indraprastha University, India . . .	701
<b>Using of Active Power Filters at Hydro Power Plant</b> – Boris Bizjak, University of Maribor, Slovenia . . . . .	707
<b>The Analysis of Harmonic Voltage Influenced by Transformer Connection</b> – Chenbinfa, Beijing Electrical Power Supply Bureau, China. . . . .	714
<b>A Reliable Technique for Interharmonic Measurement</b> – Mohammad Sedighy, James Wikston, Hatch Associates . . . . .	723
<b>Active Harmonic Filters: A Brief Overview of a New Market That Promises to Change the Field of Power Quality</b> – Alex Augoustidis, Mesta Electronics Inc. . . . .	731

\* Paper not available at time of printing. May or may not be available at the Conference.



## Virtual Instrumentation for the Study of Non-Sinusoidal and Non-Symmetrical States (Behaviours) in Romania

– Ion Lungu, Corneliu Stan, SC Electrica SA; Costin Stefanescu, Carmen Golovanov, Politechnical University of Bucharest, Romania ..... 742

## Transients on Control Circuits Within Electric Power Station

– Dr. Selim Trabulus, Yildiz Teknik Üniversitesi, Turkey ..... 753

## Power Session #2

### Load Detection and Classification Using Wavelet and Instantaneous Power Signal

– Eduardo Cano Plata, Universidad Nacional de Colombia; Hernán Tacca, Carlos D'Attellis, Universidad de Buenos Aires, Argentina. .... 761

### Data Acquisition System for Ascertaining the Electrical Parameters Under Non-Symmetrical Regime

– Corneliu Stan, Ion Lungu, SC Electrica SA; Carmen Galovanov, Polytechnic University of Bucharest; Oana Radoveanu, CONEL SA, Romania ..... 775

### The Power Quality Panorama in Portugal

– Joaquim Delgado, Anibal Traca de Almeida, Pedro Saraiva, ESTV/IPV, Portugal. .... 785

### The Liberalisation Process in Electricity Markets in the European Union

– Tuija Mannila, Petri Trygg, Kimmo Laitinen, Leena Korpinen, Tampere University of Technology, Finland. .... 796

### On the Characterization of Instrument Transformers Behaviour in Frequency Domain

– Mihaela Marilena Albu, Carmen Golovanov, Politechnical University of Bucharest; Ion Lungu, V. Stan, SC Electrica SA; Romania. .... 804

### Magnetically Controlled Reactor Shrinks Power Quality Costs

– A.M Bryantsev, Moscow Power Institute, G.A. Evdokunin, St. Petersburg State Technical University, Russia; M.D. Galperin, Expanding Edge LLC; A. Dolgoplov, VEI Scientific & Engineering Center, Russia ..... 810

### Response of Different Protocols for Detection and Measurement Parameters of Voltage Sags and Swells

– N. Kagan, N.M. Matsuo, S.X. Duarte, E.L. Ferrari, A. Sanommiya, University of São Paulo; J.L. Cavaretti, U.F. Castellano, A. Tenório, Electropaulo, Brazil ..... 817

### Assessing the Voltage Quality in Distribution Networks

– Mohamed M. Saied, Kuwait University, Kuwait. .... 827

### Using Genetic Algorithms to Determine FACTS Devices Location and Parameters for Enhancing Simultaneous Interchange Capacity

– Wang Feng, Nanyang Technological University, Singapore ..... \*

### A Multitasking Active Shunt Compensator for Power Quality Improvement

– P.S. Sensarma, K.R. Padiyar, V. Ramanarayan, Indian Institute of Science, India ..... 839

### Hospital Electronic Problems Due To Poor Power

– Harry Rauworth, General Electric Medical Systems. .... 848

\* Paper not available at time of printing. May or may not be available at the Conference.

# Integrating Permanent Power Quality Monitoring into a Critical Operations Center

By

Brad Gibson, P.Eng.  
Managing Partner, Current Thinking Inc.  
Hamilton, ON Canada  
bradg@currentthinking.com

## Abstract

This paper covers the important reasons for considering power quality when installing a building metering and monitoring system. At this site, hundreds of PC workstations, dozens of servers as well as a variety of banking and e-commerce business tools are installed as part of a redundant corporate operations center. The subject system is comprised of a 17 point metering network utilizing meters from Power Measurement Ltd. Software consists of the PML Pegasys package running under Windows NT4. The author describes why these products were utilized, how they are connected and what should be considered when integrating the components with an existing building's operations.

The customization of the system is described; detailing the requirements for determining power quality alarm notification to the operators. Reporting extensions utilizing standard software components are described and critiqued. These components can be very useful to the operators, however the metrics must be carefully evaluated and analyzed. One such metric -- the ITIC curve -- better known as the CBEMA curve, is examined and found to be of little significance for building service entrance analysis.

Some usage data from the site is presented and management issues after a full year of operation are presented for consideration. The reliability and accuracy of the system are highlighted with some anecdotal monitoring incidents obtained from the first year of monitoring. Internet based extensions for data presentation are also discussed briefly.

## The Need

The field of power quality diagnostics and monitoring has matured dramatically in the past 20 years. The most fundamental transition has occurred in the way power quality is perceived in commercial facilities. Where once facility managers and technical personnel viewed power quality in a reactive fashion, new lower-cost monitoring systems can integrate standard electrical energy monitoring information with high-speed power quality data capture to provide proactive electrical system information.

Proactive, or more correctly; predictive power quality monitoring, is still in its infancy in terms of the software tools available to alert electrical system personnel. These tools and systems are being built in response to those in data intensive environments who require real-time power system information. The introduction, concentration and networking of small computer systems in commercial facilities since the early 1980s requires increased awareness of the electrical system resource. These needs have been amply demonstrated in many other papers presented both at this forum and other technical conferences. The data intensive environments of today feature concentrations of high-speed network workstations and clusters of "server farms". The rapidity of acquisition and deployment of these systems along with the expectation of high mobility and near 100% up-time often catches facility managers off-guard. From an electrical power standpoint one way to increase system up-time is to monitor electrical system parameters, leading to preventative actions that will avert equipment failure. These systems have only become "ready for prime time" in the past 4 to 5 years.

## Site Description

The site in question is located in a multi-story office tower. The top four floors of the building have been designated as a "Business Recovery Center"(BRC) by one of Canada's largest financial institutions. The function of the center is to provide backup, mirror or support services for any of the company's business units. If a natural or operational disaster occurred in credit card transaction processing, currency trading, stock transactions or automated banking many of the functions could be temporarily routed to this center. As a result, the BRC contains a significant concentration of computing resources that need to be available at any time. In addition, staffing at the center could swell from 10 to 500 people in the matter of a few days. Workstation computing requirements are based on the actual working systems used by line personnel. Theoretically, a trader could move from their normal workstation to the BRC workstation and provide identical service.

Disaster and recovery planning must allow for unforeseen events. Even the best disaster planner will realize that some events contain the seeds for others; some problems are cascading in nature and this requires adaptability on the part of the recovery center. At this location, electrical capacity has been designed to allow for increased loading from extra workstations and servers that may be brought to the site subsequent to the on-set of a recovery situation and added to the existing complement of business equipment. This could result in system over-loading at some points in the distribution network. In the modern context of loading, harmonic currents need special attention, thus a real time monitoring system was requested to provide harmonic and true loading of the center's distribution grid.

As was pointed out to the BRC personnel and engineering staff, for only a small additional cost a total power quality monitoring system could be installed that would provide building envelope information along with distribution point data within the envelope. The BRC utilizes

a 600 V base building distribution system.<sup>1</sup> BRC business equipment transformers are fed from one of two bus risers, while mechanical equipment is fed from a separate 600 V bus duct. In the event of a total loss of utility power these bus ducts can be fed by two diesel generators that have an extended operating capability.

## Site Considerations and Requirements

The following elements were critical in developing a workable electric monitoring system for this site:

### *Staff Technical Expertise*

While there are many experienced computer and networking personnel at site, they are not involved with the day to management of the building. In addition, building managers and base-building technicians – adept at dealing with the usual building control systems (ie: alarms, HVAC, fire etc.) – are not electricity monitoring experts. There exist therefore, a gap between the two groups both in terms of expertise and responsibility for the electricity resource. Realizing this dilemma, the building superintendent sought a system that was easy to operate while providing timely alarms and monthly reports.

### *Building Operations*

Movement of loads by BRC computer staff are not always coordinated with building managers; ie: they are "tenants" and the building managers provide building services. It is possible that due to business process requirements concentration of loads may develop in particular operational areas of the building without regard to the harmonic loading requirements of the source transformer.

---

<sup>1</sup> 600 VAC, 3 phase, 60 Hz distribution systems are standard throughout most commercial and industrial buildings in Canada.



## Integrating With Other Building Monitoring Components

The system had to be capable of interfacing with the existing building management system. Data from system had to be portable to allow interchange between departments and corporate programs.

## The Monitoring System

### System Selection Criteria

The following requirements were developed both from BRC requests and expert input from the various stakeholders:

- Each dry-type transformer in the BRC was to be monitored  
**Reason:** To provide current and harmonic loading, current and voltage distortion, voltage unbalance, neutral current readings in real-time.
- A low cost per point for transformer monitors
- Reduced form factor required because of retrofit space requirements
- Power quality meters to provide transient, sag/swell and waveform deviation graphs and statistics
- Power quality thresholds must be programmable and accessible
- Reporting of power quality data and energy data must be a "low click", easily reproducible exercise requiring little training
- Energy monitoring must provide an aggregated table of consumption criteria with graphs on a monthly basis
- All meters must be fully networked utilizing open standards networking architectures and protocols
- Software must be Windows NT 4 compatible
- All data must be ODBC compliant for export/query purposes

## The Selected System

The system of meters chosen to perform the monitoring was comprised of:

- 15 PML 7300 Meters on each of 14 dry-type distribution transformers and one on the BRC mechanical bus
- 2 PML 7700 Meters on each of the BRC business equipment busses
- All meters were interconnected by RS-485 multi-drop network; one 7700 at each end
- Each 7700 acts as a gateway from the RS485 to Ethernet that leads to the host computer (one is the active gateway, one is a hot standby)
- Host computer is a Windows NT4 server running PML Pegasys power management software

## Configuring and Installing

The system is connected as shown in Figure 1. The host server runs 4 basic software modules or servers. These are the communications server, log server, virtual ION processor and the




Figure 1: Monitoring System Layout

display/analysis component. Data is logged to a Structured Query Language (SQL) database; a license for Sybase SQL Anywhere is included with the Pegasys Software.

## Database Tracking for Quality Control and Commissioning

The system requires the advance collection of electrical distribution information and metering data. This is easily tracked in a basic database for later project and operator access. The basic items collected, noted by field name are in Table 1. Also maintained in this database are a series of checklists for project quality control. These include items like register initialization for nominal voltage, CT Ratios and communications parameters; as well as hardware setup items like per point cable termination acceptance and parts installation. Use of this type of checking enables the network to be brought up in a very rapid manner. For example, at this site the network did not operate beyond the 7700 gateways when first fired up. A scan of the checklist showed that RS485 terminating resistors had not been installed on the ends of the RS485 network. Installation of these resistors led to an immediate initiation of communications and the network was ready for commissioning.

**Table 1: Field Names of Items Tracked for Installation and Commissioning**

ID
Generic_Name
Source
Location
Primary_Feeder
Secondary_Feeder
Amps_Per_Phase
Meter_Type
Sec_Voltage
Transformer_Size
Other_Data
CT_Ratio
Meter_SerialNo
Unit_ID
RS485_Speed
Meter_DeviceName

## Not a "Plug and Play" Exercise

There are two basic components to meter installation; hardware installation and system integration. The clear network orientation of the metering system requires a mix of computer networking skills along with electrical power system knowledge. This is a scarce combination of skills and is a key element in determining the ease with which a metering installation will proceed.

Key points to note from the installation of hardware are as follows:

- The metering CT ratios at each point must be cross-checked by the electrician
- The electrician must install the correct serial number of meter at the designated point. Serial numbers are a fundamental component of establishing the network communications scheme through equipment ID's.

## Use of Networking Standards

Network set-up is aided by the use of a rational ID scheme and the use of standard TCP/IP network protocols. The use of IP addressing allows for routing in more advanced networking environments and means that the meter can be hooked directly to a Virtual Private Network on the Internet. The non-proprietary networking scheme also means that standard networking cables, hubs and switches can be employed. It also implies the use of alternative physical media like fiber optic cables if these are desired.

## Customizing the System

The basic metering screens and power quality screens that PML ships with Pegasys were adequate for BRC staff look-ups but the central operator screen was built from scratch. The basic operating screen shows each of the 17 meters arranged in a stylized one-line diagram by floor and by load (ie: the designated transformer or bus they are monitoring). Each meter indicates on the screen at all times:

- the highest present phase current
- the  $V_{thd}$
- the present KVA load at the monitoring point and its acceptable maximum

K-13 rated transformers, where they are installed, can carry 100% of the design KVA,

while each of the non-K rated transformers in the BRC have been de-rated using the simple CBEMA de-rate calculation (where the de-rated capacity of the transformer is the majority of the loads are single phase switchmode power supplies is the ratio of the average RMS phase currents to the average peak phase currents). If the monitoring point reaches 80% of either of these maximums then the on-screen meter icon for that location turns yellow indicating increased loading. Monitoring points turn red when any of the screen parameters exceeds the rated maximum for that point.

PML's software technology is dubbed the "ION" system. ION utilizes a distributed processing model that can be confusing for a new user. Each meter has processing functionality that allows for the calculation of certain electrical monitoring parameters. For instance, a meter may have the ability to capture and display individual odd and even harmonics and then totalize these values to provide summary harmonic distortion data. Other meters may have the ability to capture these individual harmonics but not to prepare summarized totals. In cases like this the data from a meter can be further processed by another ION module either on a more capable meter or in a virtual ION processor running at the host server. The system invites a sharing of data and processing across the network that can increase the efficiency of data presentation, but that may also slow down network operation and lead to data clutter. ION processing decisions must be well designed to overcome network latency and the trend to providing too much information to an operator. Some ION/Pegasys data systems viewed by this author have poor presentation and usage models; the designers have succumbed to the notion that being able to do something means that it should be done.

## Reporting: Data to Information

While the on-screen operator interface is the key component of real-time interaction with BRC staff, it is the ad hoc reporting element that provides the BRC with data about energy usage and power quality. Reports are built utilizing a PML written custom software component that presents a check-list of SQL queries from the

database. This component then passes the data from the queries to a Visual Basic for Applications Macro that runs in Microsoft Excel. This is an open system that allows for some level of customization, however an excellent knowledge of both the database structure and of Visual Basic are required. The BRC utilizes an energy report that aggregates power consumption from each of the 2 business equipment busses. This information is used for intra-company energy billing and replaces a monthly manual meter reading exercise that took half a day.

Building envelope power quality is summarized in a report that captures sag/swell, transient and waveform data from each of the data logs of the 7700 meters. This information represents instantaneous incidents regarding phenomenon like load switching or utility feeder faults. Steady state harmonic and loading information is available through the operator screens. While the power quality reports provided by the PML technology have been helpful, the basic metric for determining incident severity is flawed, since it utilizes the 1996 ITIC curve; better known as the CBEMA curve. The CBEMA curve has become a tonic for numerous power quality event characterizations. As has been described elsewhere<sup>2</sup>, the CBEMA curve is a poor predictor of equipment upset since its thresholds are arbitrary, universal and ignorant of current surge characteristics in a load. The curve definition can be replaced by alternative envelopes but this process is not easily carried out with the PML software.

---

<sup>2</sup> Gibson, Brad. Five Things to Forget about Power Quality. Presented to the 1999 Electricity Forum on Power Quality and Harmonics, Toronto. Also available on the [www.openpowerquality.com](http://www.openpowerquality.com) web site.

Note too, that one of the developers of the original CBEMA curve, Alex McEachern, has referred publicly to this curve as the "BOGSAT" Curve ("Bunch of Guys Sitting Around Talking"). As he related in his talk to the attendees at the 2000 Electricity Forum on Power Quality and Harmonics in Toronto, he noted that the curve was never developed to be a comprehensive guideline for all types of distribution systems and electrical loads.

A better metric for report generation would be a query set based on the definitions for power quality outlined in IEEE Std 1159. This would allow one to analyze the data in distinct subsets from shortest duration to longest duration and by class of disturbance. The 7700 meter samples at 7680 Hz or 128 samples per 60 Hz cycle. This allows transient detection to no less than 260  $\mu$ s in duration, but the meter can actually over-sample during high speed trigger to allow resolution down to 130  $\mu$ s. The practical meaning of this is that the unit has a capability to only monitor transients in parts of Categories 1.1.2 and 1.2.2 and in Categories 1.1.3 and 1.2.1 and as defined by IEEE Std. 1159-1995. A reporting tool that summarized the waveform deviations in terms of Transients, Short Duration Variations and Long Duration Variations and then allowed screening by threshold voltages or currents would be far more helpful in terms of rapidly finding events of interest to the power quality engineer. At the present time we have constructed a number of queries utilizing SQL and run these against the database on an ad hoc basis to generate custom power quality reporting data. For instance a simple query of data from March to December 1999 revealed that 128 separate transient events were recorded on BRC Bus 1. Many of these transients were oscillatory in nature and therefore registered multiple transient hits in the 7700 detection circuitry. Filtering these using the timestamp and duration data it was revealed that the largest transient impacting the bus was 304 V on August 24 1999, during a lightning storm. The maximum duration of the transients was of 15.6 ms and the minimum detected was 130  $\mu$ s, the limit of the device.

## The Monitoring System in Use

After over one year in operation at the site, data has been collected that exceeds an 80 MB file size. This is a small, manageable database by modern standards and indicates there are many years of growth available for the data file given the multi-gigabyte hard drive available. Back-up functionality is performed via a daily tape storage routine, while one annual database tuning and off-site capture has been carried out. An additional meter was added to the system in

the summer of 2000 in order to accommodate additional mechanical load. The longer term requirements for this system are a more functional power quality reporting tool that will integrate with a messaging host off-site. The host will be enabled to determine the severity of a power quality disturbance from within the parameters of the Std. 1195 categories and past historical data, it will then notify key personnel through a combination of email, paging or PCS messaging depending on severity.

## Notes from the Field...

The high accuracy of the meters was put to the test during a Y2K drill in October of 1999. At that time every load in the facility was powered up in order to stress the distribution system. Bus voltage drop was found to be the range of 5% on one riser; checks with hand-held meters revealed voltage drops of only 3%. However a survey of the meter specifications and technology for each of the meter types showed that the 2% difference could be accounted for and that the 7700 meters were delivering the more accurate measurement. One of the key decisions that has been made at this site on the basis of data viewed from the power quality component of the meters has been with regard to Uninterruptible Power Supplies (UPS). Two issues have arisen that have lead to great cost savings. The first of these concerned the need for a large on-site UPS system which was advocated by some. While servers require the ride-through of the UPS, management has determined that the impact of transfer switching, while annoying for some is acceptable and that most workstations do not need the protection of 0.5 – 2 s of ride through afforded by the UPS. Data from monthly generator tests revealed however that transfer switch wave shape anomalies were impacting the servers leading to some network anomalies. The UPS's in use at the site were of a hybrid type that allowed transient and switching noise to pass through the UPS. UPS's have also been subject to excessive battery wear. Based on waveform data captured during testing a decision was made to switch to an on-line UPS design and to institute a networked UPS management system. The UPS's are being introduced to the site for all servers and key workstation functions.