

Barry Lewis

Small Dams

Planning, Construction and Maintenance



Small Dams

Planning, Construction and Maintenance

Barry Lewis

Dam Consultant, Melbourne, Australia



CRC Press

Taylor & Francis Group

Boca Raton London New York Leiden

CRC Press is an imprint of the
Taylor & Francis Group, an **informa** business

A BALKEMA BOOK

CRC Press/Balkema is an imprint of the Taylor & Francis Group, an informa business

© 2014 Taylor & Francis Group, London, UK

Typeset by MPS Limited, Chennai, India

Printed and Bound by CPI Group (UK) Ltd, Croydon, CR0 4YY.

All rights reserved. No part of this publication or the information contained herein may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, by photocopying, recording or otherwise, without written prior permission from the publishers.

Although all care is taken to ensure integrity and the quality of this publication and the information herein, no responsibility is assumed by the publishers nor the author for any damage to the property or persons as a result of operation or use of this publication and/or the information contained herein.

Library of Congress Cataloging-in-Publication Data

Lewis, Barry, 1942–

Small Dams : Planning, Construction and Maintenance / Barry Lewis, Dam Consultant, Melbourne, Australia.

pages cm

Includes bibliographical references and index.

ISBN 978-0-415-62111-3 (hardback)

1. Reservoirs—Design and construction. 2. Water-supply, Agricultural. I. Title.

TC540.L55 2013

627'.8—dc23

2013022561

Published by: CRC Press/Balkema

P.O. Box 11320, 2301 EH, Leiden, The Netherlands

e-mail: Pub.NL@taylorandfrancis.com

www.crcpress.com — www.taylorandfrancis.com

ISBN: 978-0-415-62111-3 (Hbk)

ISBN: 978-1-315-85774-9 (eBook PDF)

Small Dams

Disclaimer

This book is intended for use as a guide to owners and operators of small dams. It suggests prudent approaches to normal surveillance and maintenance practice with a view to enhancing the long-term safety and survival of small dams. It is not intended as a source of detailed information to cover all possible eventualities. In the event of any suspected imminent or potential failure condition, expert advice should be sought immediately.

Preface

Farmers are well aware of the need to boost productivity. In the face of greater competition for domestic and overseas markets, the farmer who wants to succeed has to take a business person's approach to increasing efficiency, reducing costs and improving output. In this environment, water becomes an economic factor and its provision a matter for careful deliberation.

This book is designed as a guide for small dam owners, engineering students, Government agencies, developers, and earthmoving contractors who are responsible for designing, building and using the majority of water storages constructed. It is also designed for engineers who have not specialised in small earth dam design for agricultural hydrology, but who may be called upon, from time to time, to design small water storage schemes. It is not intended to replace standard procedures currently used by those specialised engineers who are engaged in farm water design, although many of the design methods described herein are based on their procedures. It does, however, attempt to provide such engineers with a comprehensive array of design data and a concise reference to basic design techniques that are not otherwise readily available.

To cover all aspects of water conservation and use in detail is not possible in a book of this size. However, it will give the landowner an insight to those aspects of planning which must precede the establishment of a feasible and economic water supply project.

The information for this book has come from a number of sources. One is a series of small dam pamphlets (which I wrote for the Rural Water Authorities in Australia over a number of years), another is data from papers that I have read and presented at conferences around the world.

Barry Lewis
May, 2013

Acknowledgments

There are many people who have supported and provided information, ideas and procedures in the collation of this book on small dams. Perhaps a major dilemma for me is the incorporation of sources of information, which are better explained in the anonymous quote:

How about the many ideas and procedures that one picks up from discussion with colleagues? After the passage of time, one can no longer remember who originated what idea. After the passage of even more time, it seems to me that all of the really good ideas originated with me, a proposition that I know is indefensible.

It becomes clearer with time that nothing is new, but people forget the original sources and whether those sources were really original or were the result of slight modifications of other people's ideas. It is like the wheel. Nobody knows who conceived the idea, yet it is used universally. So, credit must be given to those who have gone before me in this area.

My family has been supportive in assisting in many ways. My wife, Marion, has typed and corrected a number of drafts. Richard, my son, has shown me some of the intricacies of the computer, whilst Janette, Helen and Kenneth have done their bit in other ways.

In the practical areas of planning, design, construction, maintenance and legal issues of small dams and other related areas I would like to thank all of those who have been instrumental in the completion of this book.

Introduction

People have always gathered water during wet seasons so as to have enough for themselves, their animals and their crops in dry spells. The earliest known dams were in China in the sixth century BC. The ruins of ancient dams also exist in the Tigris and the Nile River Valleys. Some Roman dams built in Italy, Spain and North Africa are still being used today.

Today, dams are built to allow storage of water to give a controlled supply for domestic or industrial consumption, for irrigation, to generate hydro-electric power, or to prevent flooding. Large dams are built of earth, rock, concrete or a combination of these materials (for example, earth and rock fill). They are built as: gravity dams, where the stability is due entirely to the great weight of material; arch dams, where abutments at either side support the structure; or, arch gravity dams, which are a combination of the two.

Those who plan, design, construct, maintain, use and administer significant infrastructure developments which have a real potential to harm people and property if something goes wrong, are potentially subject to significant legal liabilities. These liabilities need to be taken into account when decisions are made in relation to such developments.

It is well known that Australia is a dry continent characterised by variable rainfall. It is less well known that, in response to widespread harvesting of water on the small and large scale, Australia has the highest water storage per capita in the world (Lewis and Perera, 1997; Lewis, 2001b). Small dam development has occurred in response to agricultural expansion, and to the need for a reliable source of water for stock, domestic and irrigation use, particularly during periods of drought. However, there is a growing belief in the community that small dams are impacting on water resources in many major catchments by reducing stream flow and flow duration. Potential and actual impacts of such reductions on the conflicting needs of the environment, agriculture and industry are cause for concern. These concerns are set against a background of changes including increased areas of intensive land uses such as viticulture and horticulture, and the development of farmland into rural residential subdivisions in commuter belts surrounding major cities and rural centres. These changes are associated with increased small dam development. In a significant proportion of cases, particularly where intensive land use changes have occurred, small dams are constructed that exceed the available water resource. Where this occurs, downstream impacts on stream flow will be the cause of conflict between users (including the

environment). In addition, landowners may experience financial losses by constructing dams of a size inappropriate for the catchment.

In most countries around the world and in Australian States, provisions of the relevant *Water Act(s)* require that environmental consideration be taken into account in relation to new and renewed licences. These requirements apply to both regulated and unregulated waterway systems. Since unregulated waterways may not have large storage capacities from which environmental releases can be made, flow needs to be specified as a proportion of daily stream flow, or as a minimum daily flow. Many factors such as in-stream habitat requirements need to be considered when allocating an entitlement to environmental flows. In the case of regulated waterways, environmental flows can be released as part of the normal operating procedure.

Table of contents

<i>Preface</i>	xiii
<i>Acknowledgments</i>	xv
<i>Introduction</i>	xvii

Section I Planning	I
1.1 Assessing water needs	1
1.1.1 Planning water supplies	1
1.1.2 Water quality	2
1.2 Assessment of catchment yield	3
1.2.1 Factors controlling catchment yield	3
1.2.2 Methods of estimating catchment yield	4
1.2.3 How trees affect yield	8
1.2.4 Artificial catchments	8
1.3 Dam site selection	9
1.3.1 Choosing a dam site	10
1.4 Types of farm storages	12
1.4.1 Gully dams	14
1.4.2 Hillside dams	14
1.4.3 Ring tanks	15
1.4.4 Turkey's nest tanks	17
1.4.5 Excavated tanks	18
1.4.6 Weirs	20
1.4.7 Off-waterway storages	20
1.5 Dam storage size	20
1.5.1 Evaporation losses	21
1.5.2 Ways of controlling evaporation	22
1.5.3 Seepage losses	22
1.5.4 Average water consumption	22
1.6 Using a dam in drought	25
1.7 Fire fighting	28
1.8 Small dams and trees	29
1.9 Dam cost justification	30

Section 2 Investigation	33
2.1 Soil testing	33
2.1.1 Foundation	33
2.1.2 Borrow pit for embankment material	34
2.1.3 Spillway site	34
2.2 Site selection criteria	34
2.2.1 Seepage losses	34
2.2.2 Stability of dam sides	36
2.2.3 Sedimentation in dams	36
2.3 Foundation materials	36
2.4 Embankment materials	37
2.5 Site investigation of materials	38
2.5.1 Soil texture tests	38
2.5.2 Unified soil classification	38
2.6 Analysis of soil	41
2.6.1 Core trench	41
2.6.2 Embankment soil	42
2.7 Location of soil	42
2.8 Unsuitable material	43
Section 3 Design	45
3.1 Items that need to be considered	45
3.1.1 Embankment types	46
3.1.2 Core trench	48
3.1.3 Embankment batter slope	48
3.1.4 Crest width	50
3.1.5 Freeboard	51
3.1.6 Alternative ways of batter protection	52
3.1.7 Topsoil cover	54
3.1.8 Fencing	55
3.2 Flood flow estimation	55
3.2.1 Peak flow estimation	56
3.3 Outlet structures	56
3.3.1 Earth spillways	57
3.3.2 Design spillway capacity	58
3.3.3 Selecting spillway dimensions	58
3.3.4 Chute spillways	60
3.4 Pipelines through embankments	61
3.4.1 Trickle pipes	64
3.4.2 Drop inlet structures	64
3.4.3 Cut-off collars	65
3.5 Earth and water computations	65
3.5.1 Embankment material	65
3.5.2 Floor slope	68
3.5.3 Area beneath embankment	68
3.5.4 Excavated tanks	69

3.5.5	Water storage capacity computations	69
3.5.6	Storage excavation ratio	72
3.6	Estimate of costs	72
3.6.1	Economics	72
3.6.2	Dam quality pays over time	74
Section 4	Documentation	75
4.1	Collation of plans and specification	75
4.2	Collecting basic design data	76
4.2.1	Catchment map	76
4.2.2	Location (topographical) map	77
4.2.3	Profiles and cross-sections	77
4.2.4	Soils	77
4.3	Assembly of data	78
4.3.1	Analysis of data	78
4.3.2	Design	78
4.4	Construction documents and drawings	79
4.4.1	Specifications	79
4.4.2	Checklist	80
4.5	Final review and approval	80
4.5.1	Records	80
Section 5	Construction	81
5.1	Approval for dam building	81
5.1.1	Details that may need to be submitted	81
5.1.2	Referral dams	82
5.2	Selecting your dam builders	83
5.2.1	Selecting an engineer	83
5.2.2	Details that an engineer can provide	84
5.3	How to build a dam	85
5.4	Steps in constructing a dam	85
5.4.1	Setting out	85
5.4.2	Diversion of water	87
5.4.3	Clearing and grubbing	87
5.4.4	Stripping topsoil	87
5.4.5	Core trench	88
5.4.6	Borrow pit material	88
5.4.7	Selection and placing of material	88
5.4.8	Spillway and outlet structures	88
5.4.9	Batters and topsoil	89
5.5	Compaction	89
5.5.1	Compaction when constructing a dam	90
5.5.2	Recommendations for compaction	90
5.6	Soil moisture	91
5.6.1	Adjusting soil moisture	91
5.7	Allowance for settlement	92

5.8	Equipment	93
5.8.1	Rollers	94
5.8.2	Features of roller compaction	95
5.8.3	Other machinery	95
5.9	Installation of outlet pipe	96
5.9.1	Testing of the pipe	96
5.9.2	Foundations on rock	96
5.10	Checking for compliance with standards	97
5.10.1	Checking the contractor's work	97
5.10.2	Inspection during construction	97
5.10.3	Good work takes time	97
5.10.4	Extra 'bonuses'	98
5.10.5	Changing your mind	99
5.10.6	Progress payments	99
5.11	Final inspection and measurements	99

Section 6 Maintenance 101

6.1	Safety surveillance	101
6.1.1	Equipment for inspection	102
6.1.2	Observations to be recorded	102
6.2	Inspection procedures	104
6.2.1	General techniques	104
6.2.2	Specific techniques	105
6.2.3	Evaluation of observations	106
6.2.4	Frequency of inspection	107
6.3	Causes of dam failures	107
6.3.1	Dispersive clays	109
6.3.2	Seepage and leakage	109
6.3.3	Cracking and movement cracks	109
6.3.4	Erosion	110
6.3.5	Deformation and movement	115
6.3.6	Defects in associated structures	118
6.3.7	Vegetation	120
6.3.8	Total catchment protection	120
6.3.9	Weed control	121
6.4	Dam leakage	121
6.4.1	Rebuilding	122
6.4.2	Use of soil additives	122
6.4.3	Artificial liners	124
6.4.4	Using a clay liner	125

Section 7 Water 127

7.1	Quantity	127
7.2	Water quality	128
7.2.1	Domestic use	130
7.2.2	Stock water	132

7.2.3	Irrigation water	132
7.3	Water treatment for human consumption	132
7.4	Algae in farm water supplies	133
7.4.1	Problems	133
7.4.2	Identification	134
7.5	Salt in dam water	134
7.5.1	Minimising salinity in dams	136
7.5.2	Interception of sub-surface saline water	136
7.5.3	Maintenance	137
7.5.4	Downstream effects	137
7.5.5	Minimising the effects of evaporation	137
7.5.6	Stock and salty water	137

Section 8 Ecology 139

8.1	Wildlife and plants in dams	139
8.1.1	Water regime	140
8.1.2	Basic topography	140
8.1.3	Vegetation	140
8.1.4	Grazing by stock	141
8.1.5	Waterways and swamps	141
8.1.6	The role of hunting	142
8.1.7	Waterfowl management	142
8.2	Water plants in dams	143
8.2.1	Aquatic plants	143
8.3	Using herbicides near water	147
8.3.1	Hazards	148
8.4	Vegetation on and around dams	148
8.5	Yabbies	149
8.5.1	Physical removal	149
8.5.2	Biological removal	149
8.5.3	Chemical control	150

Section 9 Commercial 151

9.1	Fish farming	152
9.1.1	Established freshwater species	152
9.1.2	Dam conditions that control productivity	153
9.1.3	Feeding	154
9.1.4	Aquatic vegetation	154
9.1.5	Fish loss by escaping	154
9.1.6	Muddy water	155
9.1.7	Algae	155
9.1.8	Other species	155
9.2	Yabby farming	156
9.2.1	Types of dams for yabby production	156
9.2.2	Water properties	157

9.2.3	Stocking and feeding	157
9.2.4	Harvesting	157
9.3	Native fauna and total ecosystem management	158
9.3.1	Native fauna	158
9.3.2	Managing predation by native fauna	158
9.4	Licensing process	159
9.4.1	Licences required	159
9.4.2	Other steps that may need to be taken	160
Section 10 Legal		161
10.1	Legal and policy aspects in Australia	161
10.2	Liability	164
10.3	Responsibility of dam owners	165
10.3.1	Liabilities of dam owners	166
10.3.2	Permission to build a dam	166
10.4	Dam failure	167
10.4.1	Potential hazard and risk of small dams	168
10.4.2	Minimising the risk of dam failure	168
10.4.3	In case of dam failure	168
10.4.4	Abandonment of small dams	170
10.5	Designer and earthmoving contractor(s)	171
10.6	Property insurance	171
<i>References and suggested further reading</i>		173
<i>Appendix 1 Glossary of terminology</i>		179
<i>Appendix 2 Engineering specification for an earth-fill farm dam</i>		183
<i>Appendix 3 Metric and imperial conversion tables</i>		189

Planning

1.1 ASSESSING WATER NEEDS

Water is the most plentiful and vital liquid on earth. No life, as we know it, could exist without water as it provides the essential medium in which all things grow and multiply.

In recent years the steady growth in the numbers of agricultural businesses, including viticulture, aquaculture, irrigating crops and grazing animals, has increased the demand for water supplies. No longer can the small, muddy small dam or the small bore with windmill provide adequate supplies of clean water for these uses.

Landholders are lucky if their property can be serviced from a local water trust or authority. In most cases, the only option is to utilise on-farm water resources and this requires careful planning prior to costly construction. In a majority of cases farmers use roofs of buildings to collect rainwater for domestic and farm purposes. Rainwater is the main source of high quality water for human consumption, providing that guttering and tanks are kept in good order. In some cases underground water is used, but it may require treatment to remove or neutralise the minerals it contains. Where the terrain permits, rainfall and run-off gravitating to various categories of dams (for example, off-stream and on-stream catchment dams), provide the farm water supplies.

1.1.1 Planning water supplies

When deciding the most appropriate source of water for a farm, the following steps should be taken:

- determine the purpose for which the water is to be used (for example, household, garden, irrigation, stock, aquaculture, viticulture or a combination of all of the above);
- determine the quantity of water required for the different purposes, time of year and seasonal use and conditions (for example, summer, winter, flood or drought);
- ascertain whether the source of water supply is regulated (controlled from a reservoir that releases flows subject to availability) or unregulated (for example, bore water, rainfall or combination of both) and can be maintained when supplies are needed.

These factors are a guide to planning and they differ with almost every property. The most likely base can be established by calculating the average daily or average annual requirements for each proposed use of the dam. It is only after these facts are established that harvesting, storing and distributing the water resource can be planned (Lewis, 1993).

1.1.2 Water quality

In project planning the quality of water can determine success or failure of a small dam for several reasons. First, the quality of water available from a farm water system will determine the use to which that water can be put, and hence govern the overall feasibility of the system. Many natural waters have impurities that can make them directly harmful to crops. Therefore, knowledge of the quality of the water supply is essential.

Second, water quality is a factor in determining storage capacity. For example, if saline water is intended for irrigation use, additional quantities of non-saline water must be applied from time to time to avoid damage to the irrigated crops or soils.

Third, the presence of certain mineral constituents (such as calcium, potassium, magnesium and/or sodium cations) in stored water may cause tunnel erosion in some soil types. Therefore, the quality of water to be stored in a small dam must be considered in the design and construction of the impounding embankment.

Finally, overland flows mobilise and transport nutrients, fertilisers and silt which can contaminate the dam water supply. Precautions need to be taken to minimise the risk of this occurring, as algal blooms and weed infestation could result (see Section 7.4.1).

When planning for farm water supply, the presence of minerals, sediments, nutrients, agricultural chemicals, biota or bacteriological contamination needs to be considered, according to whether the water is to be used for:

i Water for consumption for humans and animals

- Micro-organisms and other harmful organisms which may produce illness or disease.
- Soluble minerals and other substances which give the water an unpleasant taste or make a person unwell.
- Silts, suspended impurities or algae which may cause discolouration, odour or taste problems and in some cases are toxic to both humans and animals.

ii Water for household, dairy or general farm use

- Suspended minerals and compounds which cause problems with clothes washing and the build-up of scale in equipment such as pipes, hot water systems and cooking utensils.
- Impurities which can cause water discolouration and associated staining and odour problems.
- Acids, dissolved minerals and gases which corrode pipes and equipment.