

PROCEEDINGS

---



# 26th Intersociety Energy Conversion Engineering Conference

Boston, Massachusetts  
August 4-9, 1991

---

*"Energy and the Environment: A Continuing Partnership"*

VOLUME 3

Conversion Technologies  
Electrochemical Conversion



IECEC-91  
August 4-9, 1991  
Boston, Massachusetts

PROCEEDINGS OF THE  
26th INTERSOCIETY  
ENERGY CONVERSION  
ENGINEERING CONFERENCE  
VOLUME 3

**Conversion Technologies (Continued)**

Magnetohydrodynamics

Thermionics

Thermoelectrics

**Electrochemical Conversion**


Aerospace Batteries

Batteries for Secondary Applications

Batteries for Terrestrial Applications

Fuel Cells for Space Applications

Fuel Cells for Terrestrial Applications



AMERICAN NUCLEAR SOCIETY

555 North Kensington Avenue • La Grange Park, Illinois 60525

# PROCEEDINGS OF THE 26th INTERSOCIETY ENERGY CONVERSION ENGINEERING CONFERENCE

---

## ■ VOLUME 1

### **Aerospace Power Systems**

- Advanced Aerospace Power Concepts
- Aircraft Power
- Analysis of PMAD Performance
- Automation
- Burst and Pulse Power
- Environmental Issues
- Power Circuits
- Power Components
- Simulation
- Solar Dynamics
- Solar Dynamics Conversion Cycles
- Space Design of PMAD Systems
- Space Environmental Effects
- Space High Voltage Environment
- Space Nuclear Systems
- Space Power Automation

## ■ VOLUME 2

### **Aerospace Power Systems (continued)**

- Space Power Requirements
- Space Power Systems
- Space Power Systems Hardware
- Space Radioisotope Systems
- Space Solar Arrays
- Space Solar Cells
- Space Station Power
- Terrestrial Applications of Aerospace Technology

### **Conversion Technologies**

- Heat Engines
- Heat Pumps

## ■ VOLUME 3

### **Conversion Technologies (continued)**

- Magnetohydrodynamics
- Thermionics
- Thermoelectrics

### **Electrochemical Conversion**

- Aerospace Batteries
- Batteries for Secondary Applications
- Batteries for Terrestrial Applications
- Fuel Cells for Space Applications
- Fuel Cells for Terrestrial Applications

## ■ VOLUME 4

### **Energy Conservation, Policies and Environment**

- Energy Conservation
- Energy for Developing Countries
- U. S. Domestic Policy

### **Energy Systems and Alternative Fuels**

- Advanced Fuels
- Conversion Technology
- Mechanical and Thermal Storage
- System Performance
- Thermal Management
- Transportation

### **Innovative and Advanced Systems**

- Advanced Energy Concepts
- High Temperature Superconductors and Thermal-Magnetic Stability
- Superconducting Magnetic Energy Storage
- Superconductive Power and Magnetic Devices at High Temperature

## ■ VOLUME 5

### **Renewable Resource Systems**

- Developments in Nuclear Power
- Energy from Waste and Biomass
- Photovoltaics
- Solar Thermal Energy
- Wind Energy Systems

### **Stirling Engines and Applications**

### **Systems and Cycles**

- Advanced Co-Generation
- AMTEC
- Fossil Fuel Systems and Technologies
- Marine Energy

## ■ VOLUME 6

### **Post-deadline Papers**

- Subject Index
- Author Index

Copyright © 1991

American Nuclear Society

555 North Kensington Avenue • La Grange Park, Illinois 60525

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without the prior permission of the copyright owner.

ISBN 0-89448-163

# CONTENTS

*NOTE: Please check Post-deadline Section in Volume 6 for any missing papers.*

## CONVERSION TECHNOLOGIES ELECTROCHEMICAL CONVERSION

### CONVERSION TECHNOLOGIES

#### MHD I

- Coal-Fired MHD Test Progress at the Component Development and Integration Facility 1  
A. T. Hart, C. Alsberg, *MSE, Inc., Butte, MT*
- The J. E. Corette Magnetohydrodynamics Retrofit—A Conceptual Design and Project Proposal 7  
F. W. Walter, *Montana Power Company, Butte, MT*  
R. J. Labrie, *MHD Development Corporation, Butte, MT*
- Economics of MHD Retrofits and New Plants 13  
J. Lohrasbi, G. Ashby, *MSE, Inc., Butte, MT*  
F. Walter, *Montana Power Co., Butte, MT*
- Modern Energy Technologies Need Modern Diagnostics: MHD, A Case Study 23  
R. A. Kumar, R. L. Cook, *Mississippi State University, Mississippi State, MS*
- Prototypic MHD Generator Design of the Integrated Topping Cycle Power Train 33  
C. C. P. Pian, A. W. Dunton, L. C. Farrar, S. W. Petty, R. J. Pollina, J. Reich,  
E. W. Schmitt, *Textron Defense Systems, Everett, MA*

#### MHD II

- The Electrical Conductivity of MHD Gaseous Mixtures Under Equilibrium and Nonequilibrium Conditions 41  
P. J. Karditsas, *Culham Laboratory, Oxfordshire, United Kingdom*
- MHD Plant Turn Down Considerations 47  
J. T. Lineberry, J. N. Chapman  
*The University of Tennessee Space Institute, Tullahoma, TN*
- Prospects of Co-Generation Through MHD for Chlor-Alkali Industries in India 53  
K. V. S. Sundaram  
*Bharat Heavy Electricals, Ltd., Tiruchirapalli, India*
- Simulation of Normal and Oblique Shock Waves in an MHD Channel 59  
J. Zhang, S. Anghaie, *University of Florida, Gainesville, FL*

Transient Behavior of MHD Power Plants	63
W. D. Jackson, <i>HMJ Corporation, Kensington, MD</i>	
F. E. Bernard, <i>Westinghouse Electric Corporation, Pittsburgh, PA</i>	
R. J. Harrington, <i>George Washington University, Washington, DC</i>	
O. S. Mazzone, <i>Systems Research International, Great Falls, VA</i>	
G. R. Seikel, <i>SeiTec, Inc., Cleveland, OH</i>	
 <b>MHD III</b>	
Interactions of Turbulent Eddies and Combustion in an MHD Second Stage Combustor	69
S. L. Chang, S. A. Lottes, <i>Argonne National Laboratory, Argonne, IL</i>	
MHD Power Generation System and Environment	75
R. Nagalakshmi, S. K. Pandey	
<i>Bharat Heavy Electricals Limited, Tiruchirapalli, India</i>	
Numerical Prediction of the Velocity Profiles of the Slagging Stage of an MHD Combustion Chamber	81
O. P. Norton, A. Skaggs, C. W. Bouchillon	
<i>Mississippi State University, DIAL, Mississippi State, MS</i>	
Stability of MHD Plasmas Ionized by Nuclear Fragments	87
Y. Watanabe, J. Appelbaum, I. Maya, <i>University of Florida, Gainesville, FL</i>	
On the Synergism Between the "OMACON" Liquid Metal MHD and the FBC Technologies	93
E. Greenspan, A. Barak, <i>University of California, Berkeley, CA</i>	
A. Baron, H. Branover, A. El-Boher	
<i>Ben-Gurion University of the Negev, Beer-Sheva, Israel</i>	
A. Cohn, <i>Electric Power Research Institute, Palo Alto, CA</i>	
 <b>THERMIONICS I</b>	
Coupled Thermionic and Thermalhydraulic Analyses of Thermionic Fuel Elements	99
R. A. Pawlowski, A. C. Klein, <i>Oregon State University, Corvallis, OR</i>	
J. B. McVey, <i>Rasor Associates, Inc., Sunnyvale, CA</i>	
Prediction of the Start-Up Characteristics of a Heat Pipe-Cooled Thermionic Fuel Element (TFE)	105
D. Lieb, T. Witt, C. Lee, G. Miskolczy, <i>Thermo Electron Technologies, Waltham, MA</i>	
J. McVey, <i>Rasor Associates, Inc., Sunnyvale, CA</i>	
Stress in Alumina Insulator Due to Irradiation	110
W. Y. Wu, R. H. Zee, <i>Auburn University, Auburn University, AL</i>	
TFE Sheath Insulator In-Reactor Test Design	116
G. Miskolczy, C. Lee, D. Leib, <i>Thermo Electron Technologies, Waltham, MA</i>	

Thermionic Fuel Element Verification Program-Overview	121
R. C. Dahlberg, <i>General Atomics Company, San Diego, CA</i>	
R. J. Bohl, <i>Los Alamos National Laboratory, Los Alamos, NM</i>	
D. S. Dutt, <i>Westinghouse Hanford Company, Richland, WA</i>	
J. T. Wood, <i>U. S. Department of Energy, Oakland, CA</i>	

## THERMIONICS II

Adherence of Diamond Films on Refractory Metal Substrates for Thermionic Applications	126
---	-----

B. H. Tsao, M. L. Ramalingam, *UES, Inc., Dayton, OH*  
 S. F. Adams, J. S. Cloyd, *Wright Laboratory, Wright-Patterson Air Force Base, OH*

The Advanced Thermionics Initiative Program	132
---	-----

T. R. Lamp, B. D. Donovan  
*Wright Laboratory, Wright-Patterson Air Force Base, OH*

Diamond Film Sheath Insulator for Advanced Thermionic Fuel Element	137
--	-----

S. F. Adams, *Wright Laboratory, Wright-Patterson Air Force Base, OH*  
 L. H. Caveny, *SDIO, Washington, DC*

Particle Strengthened Tungsten for Space Power Applications	142
---	-----

A. Luo, D. L. Jacobson, K. S. Shin, *Arizona State University, Tempe, AZ*

Thermionic Critical Technology Investigation	148
--	-----

P. Jalichandra, R. W. Hamerdinger, E. A. Anderson  
*LORAL Electro Optical Systems, Pasadena, CA*  
 T. R. Lamp, B. D. Donovan, *Wright Research and Development Center, Wright-Patterson Air Force Base, OH*

W-Re-HfC as an Emitter Material with Long Life for Thermionic Fuel Element Application	154
--	-----

B. H. Tsao, M. L. Ramalingam, *UES, Inc., Dayton, OH*  
 B. D. Donovan, T. R. Lamp  
*Wright Laboratory, Wright-Patterson Air Force Base, OH*

## THERMIONICS III

Experimental Evaluation of Cs-Ba Thermionic Switch/Inverter-"TACITRON"	160
--	-----

M. El-Genk, C. Murray, S. Chaudhuri, *University of New Mexico, Albuquerque, NM*  
 V. Kaibyshev, A. Borovskikh, Y. Djashiashvili, Y. Taldonov  
*I. V. Kurchatov Institute of Atomic Energy, Moscow, USSR*

Extension of the CENTAR System Simulation Code to Thermionic Space Nuclear Reactors	166
---	-----

B. Nassersharif, M. Gaeta, F. Berge, *Texas A&M University, College Station, TX*  
 L. Guffee, K. Williams  
*Science Applications International Corporation, Albuquerque, NM*

Possibilities of Using Alternative Fuels in a Thermionic Fuel Element	171
---	-----

A. S. Gontar, Ye. B. Kukin, M. V. Nelidov, Yu. V. Nikolaev  
*Research Institute of Scientific Industrial Association, Podolsk, USSR*

Research of Thermionic Converter Collector Properties in Model Experiments with Surface Control 175  
 V. R. Agafonov, A. V. Vizgalov, V. I. Yarygin  
*Institute of Physics and Power Engineering, Obninsk, USSR*

#### THERMIONICS IV

Effects of CS Vapor Pressure on Steady-State and Transient Operation of Thermionic Converters 179  
 M. El-Genk, C. Murray, S. Chaudhuri, *University of New Mexico, Albuquerque, NM*

Refractory Metal to Stainless Steel Joints 185  
 R. H. Zee, S. Chen, B. A. Chin, *Auburn University, Auburn University, AL*

Thermionic Model of ZnSe: I Schottky Diode 190  
 D. M. Chiu, *Victoria University of Technology, Victoria, Australia*

#### THERMOELECTRICS

Characteristics of a Promising New Thermoelectric Material: Ruthenium Silicide 196  
 T. Ohta, *AIST, Ibaraki, Japan*  
 C. B. Vining, C. E. Allevato, *Jet Propulsion Laboratory, Pasadena, CA*

Effect of Microstructure and Composition on the Improvement of n-Type SiGe/GaP Material 202  
 J-P. Fleurial, A. Borshchevsky, J. Vandersande  
*Jet Propulsion Laboratory, Pasadena, CA*

Effect of Small Scattering Centers on the Thermoelectric Properties of P-Type SiGe Alloys 208  
 J. S. Beaty, J. L. Rolfe, *Thermo Electron Technologies Corporation, Waltham, MA*  
 J. W. Vandersande, *California Institute of Technology, Pasadena, CA*

Evaluation of Thermoelectric Performance of Iron Disilicides Doped With Oxygen 212  
 M. Hayashibara, A. Koyanagi, M. Tsukamoto, *Hitachi Ltd., Ibaraki, Japan*

A High-Efficiency Thermoelectric Converter for Space Applications 218  
 J. D. Metzger, *Westinghouse Savannah River Company, Aiken, SC*  
 M. S. El-Genk, *University of New Mexico, Albuquerque, NM*

High Figure-of-Merit N-Type SiGe/GaP Alloys 224  
 A. N. Scoville, *Thermo Electron Technologies Corporation, Waltham, MA*  
 C. Bajgar, *Thermo Electron Technologies Corporation, Waltham, MA*  
 J. Vandersande, J. P. Fleurial, *Jet Propulsion Laboratory, Pasadena, CA*

The Problems of Thermodynamic Characterization of Direct Conversion Process of Thermal-to-Electric Energy in Approximation of Classic Ideal Gas 230  
 V. A. Grodtko, *USSR National Technical Physics and Automation Research Institute, Moscow, USSR*

Thermopower and Conduction of  $\alpha$ -As<sub>2</sub>Te<sub>3</sub>,  $\alpha$ -As<sub>2</sub>Se<sub>3</sub> and Mixed System 236  
 D. M. Chiu, *Victoria University of Technology, Victoria, Australia*

## ELECTROCHEMICAL CONVERSION

### AEROSPACE BATTERIES I

- Comparison of Nickel-Hydrogen and Nickel-Cadmium Reliability 242  
D. Hafen, *Lockheed Missiles and Space Company, Sunnyvale, CA*
- Design of the MSX NiH<sub>2</sub> Battery 249  
J. E. Jenkins, *Johns Hopkins University, Laurel, MD*
- Five-Year Update: Nickel Hydrogen Industry Survey 253  
M. J. Milden, *The Aerospace Corporation, El Segundo, CA*
- Hubble Space Telescope Nickel-Hydrogen Batteries Testing and Flight Performance 257  
J. C. Brewer, T. H. Whitt, J. R. Lanier, Jr.  
*NASA-Marshall Space Flight Center, Huntsville, AL*
- Nickel-Hydrogen Cell Low-Earth-Orbit Life Test Update 263  
D. T. Frate, *NASA-Lewis Research Center, Cleveland, OH*
- Olympus F1 Nickel Hydrogen Experience 269  
P. J. Leggett, *ESTEC, Noordwijk, Netherlands*

### AEROSPACE BATTERIES II

- Effect of KOH Concentration on LEO Cycle Life of IPV Nickel-Hydrogen Flight Cells—An Update 276  
J. J. Smithrick, *NASA-Lewis Research Center, Cleveland, OH*  
S. W. Hall, *Naval Weapons Support Center, Crane, IN*
- French Technology in NiH<sub>2</sub> Cell and Battery for Geo Satellite for the Present Decade 282  
B. Lacout, D. Paugam, *SAFT, Romainville, France*
- Nickel-Hydrogen LEO Cycling at 20-50 Percent DOD 289  
J. E. Lowery, J. Mai, *NASA-Marshall Space Flight Center, AL*
- Prelaunch Self-Discharge and Charge-Acceptance Characteristics of the Hubble Space Telescope Nickel Hydrogen Batteries 294  
J. R. Lanier, J. R. Bush, Jr., *NASA-Marshall Space Flight Center, AL*

### AEROSPACE BATTERIES III

- Battery Performance Simulation for the Magellan Mission 298  
P. R. Gluck, *California Institute of Technology, Pasadena, CA*
- Destructive Physical Analysis Results of NI/H<sub>2</sub> Cells Cycled in LEO Regime 304  
H. S. Lim, G. R. Zelter, *Hughes Aircraft Company, Torrance, CA*  
J. J. Smithrick, *NASA-Lewis Research Center, Cleveland, OH*  
S. W. Hall, *Naval Weapons Support Center, Crane, IN*

Effect of LEO Cycling on 125 Ah Advanced Design IPV Nickel-Hydrogen Flight Cells—An Update	311
J. J. Smithrick, <i>NASA-Lewis Research Center, Cleveland, OH</i>	
S. W. Hall, <i>Naval Weapons Support Center, Crane, IN</i>	
Flight Performance of Navy Navigation Satellite System Nickel Cadmium Batteries	318
L. T. Goliaszewski, <i>Johns Hopkins University, Laurel, MD</i>	
Hydrogen Diffusion and the Self-Discharge of Nickel-Hydrogen Batteries	323
J. P. Fellner, <i>Wright Laboratory, Wright-Patterson Air Force Base, OH</i>	
Test Simulation of More Than Ten Year Geostationary Operation of Ni-Cd Batteries Under High Depth of Discharge	329
J. Verniolle, <i>European Space Agency, Noordwijk, The Netherlands</i>	
Thermal Modeling of Nickel-Hydrogen Battery Cells Operating Under Transient Orbital Conditions	335
D. S. Schrage, <i>Sverdrup Technology, Inc., Brook Park, OH</i>	
<b>AEROSPACE BATTERIES IV</b>	
Charge Control of Nickel Cadmium Batteries	341
S. Gross, <i>The Boeing Company, Seattle, WA</i>	
Evaluation of Advanced NiCd Cell Designs for NASA Applications	347
S. Di Stefano, G. Halpert, <i>California Institute of Technology, Pasadena, CA</i>	
T. Y. Yi, <i>Goddard Space Flight Center, Greenbelt, MD</i>	
P. Dalton, S. Hall, <i>Naval Weapons Support Center, Crane, IN</i>	
Life Testing of Secondary Silver-Zinc Cells	352
J. C. Brewer, R. Doreswamy, <i>NASA-Marshall Space Flight Center, AL</i>	
Modelling of Nickel-Cadmium Batteries Using Porous Electrode Theory	358
P. J. Timmerman, S. DiStefano, P. R. Gluck, D. Perrone	
<i>California Institute of Technology, Pasadena, CA</i>	
Production Lot Testing and Characterization of Fruedenberg 2538 Separator	364
G. C. Klein, <i>Gates Energy Products, Inc., Gainesville, FL</i>	
Super Nickel-Cadmium Battery Design and Life Test Data	372
R. S. Bogner, <i>Hughes Aircraft Company, Torrance, CA</i>	
<b>AEROSPACE BATTERIES V</b>	
Bipolar Lead Acid Battery Development	378
M. Eskra, R. Vidas, R. Miles, <i>Johnson Controls, Inc., Milwaukee, WI</i>	
G. Halpert, A. Attia, D. Perrone, <i>California Institute of Technology, Pasadena, CA</i>	
The DELTA 181 Lithium Thionyl Chloride Battery	384
R. M. Sullivan, L. E. Brown, A. P. Leigh, <i>Johns Hopkins University, Laurel, MD</i>	

Investigation of Heat Pipe Working Fluids for Thermal Control of a Sodium/Sulfur Battery L. R. Grzyll, <i>Mainstream Engineering Corporation, Rockledge, FL</i>	390
Performance Characteristics of Lithium Primary Cells After Controlled Storage F. Deligiannis, D. H. Shen, G. Halpert <i>California Institute of Technology, Pasadena, CA</i> V. Ang, S. Donley, <i>TRW, Redondo Beach, CA</i>	395
Progress and Recent Developments in Sodium-Metal Chloride Batteries B. V. Ratnakumar, A. I. Attia, G. Halpert <i>California Institute of Technology, Pasadena, CA</i>	401
The Status of Rechargeable Li-TiS <sub>2</sub> Cell Technology G. Halpert, S. Surampudi, A. Attia, <i>California Institute of Technology, Pasadena, CA</i>	407
Study of Rechargeable Lithium Cells for Space Applications J. Goualard, J. Bodet, J. Labat, <i>SAFT, Romainville, France</i>	411
<b>BATTERIES FOR SECONDARY APPLICATIONS</b>	
Development of Prototype Sealed Bipolar Lithium/Sulfide Cells T. Kaun, M. Duoba, W. Johll, V. Luong, F. Mrazek, D. Palkon, D. Simon <i>Argonne National Laboratory, Argonne, IL</i>	417
Modeling of Lithium/Sulfide Batteries for Electric Vehicles and Hybrid Vehicles P. A. Nelson, T. D. Kaun, <i>Argonne National Laboratory, Argonne, IL</i>	423
Operation of a 500kW/4,000kWh Na/S Battery Energy Storage Plant K. Takashima, K. Matsui, E. Nomura, Y. Matsumaru <i>Yuasa Battery Co., Ltd., Osaka, Japan</i> S. Iijima, Y. Matsuo, <i>NGK Spark Plug Co., Ltd.</i> T. Hirabayasi, S. Furuta <i>New Energy and Industrial Technology Development Organization, Tokyo, Japan</i>	429
<b>BATTERIES FOR TERRESTRIAL APPLICATIONS I</b>	
Advances in the Development of Ovonic Nickel Metal Hydride Batteries for Industrial and Electric Vehicles S. Venkatesan, M. A. Fetcenko, S. K. Dhar, S. R. Ovshinsky <i>Ovonic Battery Company, Troy, MI</i>	435
Durability of Polymeric Materials Used in Zinc/Bromine Flow Batteries C. Arnold, Jr., <i>Sandia National Laboratories, Albuquerque, NM</i>	440
Ideal Use of Nickel-Hydrogen Batteries in Remote Power Systems T. Stockebrand, S. Baer, J. Randall, <i>Zomeworks Corporation, Albuquerque, NM</i>	446
Nickel-Hydrogen Batteries for Terrestrial Applications D. K. Coates, <i>Eagle-Picher Industries, Inc., Joplin, MO</i> G. Roumpf, S. Baer, <i>Zomeworks Corporation, Albuquerque, NM</i>	452
Preparation of Ionic Membranes for Zinc/Bromine Storage Batteries R. A. Assink, C. Arnold, Jr., <i>Sandia National Laboratories, Albuquerque, NM</i>	458

- The Rechargeable Alkaline Zinc-Manganese Dioxide Battery 463  
 K. Kordesch, *Hibar Systems, Ontario, Canada*  
 J. Daniel-Ivad, E. Kahraman, R. Mussnig, W. Toriser  
*Technical University Graz, Graz, Austria*

## BATTERIES FOR TERRESTRIAL APPLICATIONS II

- Air Electrodes for Metal-Air Batteries and Fuel Cells 469  
 I. Iliev, A. Kaisheva, S. Gamburgzev  
*Bulgarian Academy of Sciences, Sofia, Bulgaria*
- The Control and Optimization of High Performance Rechargeable Cobalt  
 Electrodes by Reactive Deposition 471  
 A. C. C. Tseung, C. Q. Cui, S. P. Jiang, *University of Essex, Colchester, U.K.*
- A Lithium/Tetrachloroethane (Li/TCE) Primary Cell 477  
 F. Walsh, *Energy Conversion, Sommerville, MA*
- Performance Test of Advanced Battery Under Severe Conditions 480  
 R. Ishikawa, T. Ishikawa, Y. Ariga  
*Central Research Institute of Electric Power Industry, Tokyo, Japan*  
 S. Furuta, T. Hirabayashi, K. Sato  
*New Energy and Industrial Technology Development Organization, Tokyo, Japan*

## FUEL CELLS FOR SPACE APPLICATIONS

- Bifunctional Alkaline Oxygen Electrodes 486  
 L. Swette, N. Kackley, S. A. McCatty, *Giner, Inc., Waltham, MA*
- A Comparison of Various PEM Fuel Cell Systems for Both Open and Closed  
 Loop Applications 492  
 R. P. Hollandsworth, P. G. Bailey  
*Lockheed Missiles and Space Company, Sunnyvale, CA*  
 P. C. Symons, *Electrochemical Engineering Consultants Inc., Morgan Hill, CA*
- Lightweight Zirconia Power Package for Space Applications 498  
 M. Hsu, *Ztek Corporation, Waltham, MA*
- Reduction Potential of the System Mass of Hydrogen/Oxygen Based Regenerative  
 Fuel Cell (RFC) Systems for LEO Applications 504  
 K. Bolwin, S. Hauff, *Institute for Technical Thermodynamics, Stuttgart, Germany*
- Sensitivity Analyses of PEM Fuel Cell Systems for Both Open and Closed Loop  
 Applications 510  
 P. G. Bailey, *Lockheed Missiles and Space Company, Sunnyvale, CA*
- Stable Silver-Oxide Electrode Development 515  
 L. Swette, S. Sarangapani, M. Manoukian, *Giner, Inc., Waltham, MA*  
 S. Dallek, K. Orrson, *Naval Surface Warfare Center, Silver Spring, MD*

## FUEL CELLS FOR TERRESTRIAL APPLICATIONS I

- Commercial Fuel Cell Technology Status 521  
J. H. Hirschenhofer, *Gilbert/Commonwealth, Inc., Reading, PA*
- Dense Hydrogen and Oxygen Sources for Fuel Cells 527  
P. M. Dunn, C. J. Egan, W. L. Harbison, G. K. Pitcher  
*Naval Underwater Systems Center, Newport, RI*
- Modular Fuel Cell Stack Model in SIMTAS 533  
R. Simon, M. Huchler, J. Eickhoff, *Dornier GmbH, Friedrichshafen, Germany*
- Regenerative Fuel Cell for Energy Storage in PV Systems 538  
K. Ledjeff, A. Heinzel  
*Fraunhofer-Institut für Solare Energiesysteme, Freiburg, Germany*
- Solid State Direct Methanol Fuel Cells 542  
J. Kjaer, S. Yde-Andersen  
*Energy Research Laboratory A/S, Odense M, Denmark*

## FUEL CELLS FOR TERRESTRIAL APPLICATIONS II

- Effects of Coolant Parameters on Steady State Temperature Distribution in Phosphoric-Acid Fuel Cell Electrode 546  
K. A. Alkasab, *Cleveland State University, Cleveland, OH*  
A. Abdul-Aziz, *Sverdrup Technology, Inc., Cleveland, OH*
- Electrodes Without Platinum for a Methanol-Air Acid Fuel Cell at Ambient Temperatures 552  
R. Manoharan, J. B. Goodenough, *University of Texas at Austin, Austin, TX*
- Measurement of the Effects of Thermal Contact Resistance on Steady State Heat Transfer in Phosphoric-Acid Fuel Cell Stack 558  
A. Abdul-Aziz, *Sverdrup Technology, Inc., Cleveland, OH*  
K. A. Alkasab, *Cleveland State University, Cleveland, OH*
- On the Mechanism of the Effects of Super Acids in Fuel Cell Reactions 564  
J. O'M. Bockris, R. C. Bhardwaj, N. G. Smart  
*Texas A&M University, College Station, TX*
- PAFC Performance Loss Due to CO<sub>2</sub> Dilution Effect 570  
M. T. Le, *Westinghouse Electric Corporation, Pittsburgh, PA*
- Some Approaches to Improve the Life Performance of Phosphoric Acid Fuel Cell 572  
M. Aoki, Y. Ueki, H. Enomoto, K. Harashima  
*Fuji Electric Corporate R&D, Ltd., Chiba, Japan*

## FUEL CELLS FOR TERRESTRIAL APPLICATIONS III

- Cathode Corrosion In Molten Carbonate Fuel Cells 577  
M. Williams, T. George, *United States Department of Energy, Morgantown, WV*

Development of Internal Reforming Molten Carbonate Fuel Cell Stack T. Tanaka, M. Matsumura, T. Gonjo, M. Miyazaki, A. Sasaki, K. Sato, H. Urushibata, T. Murahashi <i>Mitsubishi Electric Corporation, Amagasaki, Japan</i>	583
Development of Monolithic Solid Oxide Fuel Cells for Army Applications G. Hossepian, L. Schipper, <i>Allied-Signal Aerospace Company, Torrance, CA</i> T. Hynes, R. Benfer <i>U.S. Army Materials Technology Laboratory, Watertown, MA</i>	589
Modeling Studies of a Monolithic Solid Oxide Fuel Cell S. Ahmed, R. Kumar, <i>Argonne National Laboratory, Argonne, IL</i> H. Walden, K. P. Barr, <i>Allied-Signal Aerospace Corporation, Torrance, CA</i>	594
Performance of Direct Internal Reforming Molten Carbonate Fuel Cells Y. Gonjyo, T. Tanaka, M. Matsumura <i>Mitsubishi Electric Corporation, Amagasaki, Japan</i>	600
Planar Solid Oxide Fuel Cell Technology Development M. Hsu, H. Tai, <i>Ztek Corporation, Waltham, MA</i>	606
<b>FUEL CELLS FOR TERRESTRIAL APPLICATIONS IV</b>	
Characterizing Fuel Cell Membrane Performance Under Load A. Cisar, <i>Dow Chemical USA, Freeport, TX</i>	611
Influence of Hydrophobic-Hydrophilic Properties of Porous Gas Diffusion Layer on the Water Management in a SPEFC P. Staiti, Z. Poltarzewski, N. Giordano, V. Alderucci, G. Maggio <i>Istituto Trasformazione ed Accumulo dell'Energia, Messina, Italy</i> A. Fasulo, <i>University of Reggio Calabria, Reggio Calabria, Italy</i>	619
The Operation of a Solid Polymer Fuel Cell: A Parametric Model B. A. Peppley, J. C. Amphlett, M. Farahani, R. F. Mann, P. R. Roberge <i>Royal Military College of Canada, Kingston, Ontario, Canada</i>	624
PEM Fuel Cells for Energy Storage Systems K. Strasser, <i>Siemens AG, Erlangen, Germany</i>	630
Recent Achievements in Polymer Electrolyte Fuel Cell (PEFC) Research at Los Alamos National Laboratory S. Gottesfeld, M. S. Wilson, T. E. Springer, T. A. Zawodzinski <i>Los Alamos National Laboratory, Los Alamos, NM</i>	636
Some Design Considerations for a Catalytic Methanol Steam Reformer for a PEM Fuel Cell Power Generating System R. F. Mann, J. C. Amphlett, B. A. Peppley, D. M. Stokes <i>Royal Military College of Canada, Kingston, Ontario, Canada</i>	642

# COAL-FIRED MHD TEST PROGRESS AT THE COMPONENT DEVELOPMENT AND INTEGRATION FACILITY

A. T. Hart and C. Alsberg

MSE, Inc.  
Butte, MT 59701

## ABSTRACT

The Component Development and Integration Facility (CDIF) is a Department of Energy test facility operated by MSE, Inc. MSE personnel are responsible for the integration of topping cycle components for the national coal-fired magnetohydrodynamics (MHD) development program. Initial facility checkout and baseline data generation testing at the CDIF utilized a 50-MW<sub>e</sub> oil-fired combustor (with ash injection to simulate coal slag carryover) coupled to the 1A supersonic channel. In the fall of 1984, a 50-MW<sub>e</sub> pressurized, slag rejecting coal-fired combustor (CFC) replaced the oil-fired combustor in the test train. In the spring of 1989, a coal-fired precombustor was added to the test hardware, and current controls were installed in the spring of 1990. In the fall of 1990, Phase I of the slag rejector was installed. In addition, significant progress and developments were made by MSE in the areas of solid suspension injection, stack gas analysis, and current control installation.

Testing during the last year emphasized baseline testing including materials, duration, and current control checkout testing. This testing will be discussed.

MSE test hardware activities included incorporating test coupons into the channel walls and installing various combustor components to test prototypic hardware designs. This paper discusses the involvement of this hardware in the test progress during the past year.

Facility modification and installation of system upgrades for improved operation and duration testing will be addressed. Future projects such as activation of the slag rejection/removal system and testing to address preparations for the prototypic hardware will be discussed. In addition, this paper will also address long-term plans for new installations.

## INTRODUCTION

The CDIF is operated for the Department of Energy by MSE, Inc. MSE is chartered with integrated testing of coal-fired MHD topping cycle components. Currently under evaluation are a 50-MW<sub>e</sub> coal-fired combustor (CFC), developed by TRW, and a linear generator, diffuser, and a full complement of current control units, all supplied by Avco Research Laboratory, Inc. Previous CDIF papers have detailed the initial oil-fired, ash-injected power tests, as well as the CFC and coal-fired precombustor (CFPC) checkout and initial power generation testing at the CDIF. This paper provides the status of CDIF coal-fired power generation testing during the past

year. Test activities have concentrated on technical issues of coal-fired MHD--the cathode wall shorting phenomena, proof-of-concept (POC) channel electrode materials and design, low stress operating conditions, current control operations, and duration testing--all with the goal of additional data to support POC hardware decisions.

## TEST SYSTEM DESCRIPTION

Since August 1985 when the first electrical power tests with the CFC were conducted, CDIF test activities have focused on coal-fired MHD power generation. The oil-fired vitiator (OFV), sometimes referred to as the air preheater, receives the incoming air from a high-volume compressor and heats this air to 1,200 °F after oxygen is added to obtain the desired enrichment. The CFPC uses a portion of the preheated air from the OFV to combust coal and produce air heated to 2,900 °F that is then introduced to the first-stage combustor. Preheated air enters the cylindrical first stage tangentially and entrains pulverized coal particles injected from the head end plate. Operating substoichiometrically, coal is gasified, and slag particles are driven to the combustor wall. A concentric baffle separates the slagging stage from the deswirl section and assists in guiding the molten slag into a water-filled slag collection tank below. The gas stream continues through the deswirl section of the combustor (where dry potassium carbonate is generally added) and enters the second stage. Additional oxygen and sometimes nitrogen (to simulate a prototypical oxidizer product) are injected in the second stage to bring the plasma to near-stoichiometric conditions.

Baseline operating conditions used for the majority of the testing during the last year are:

Thermal Throughput	50 MW
Mass Throughput	17.4 lb/s
OFV Preheat	1,200 °F
CFPC Preheat	2,900 °F
Oxidizer Enrichment	39.2%
CFPC Equivalence	1.09
First-Stage Equivalence	0.55
Second-Stage Equivalence	0.90
Global N/O	0.70-0.76

The channels that provided almost all of the test service during the past year were primarily comprised of workhorse elements [1]. In addition to the workhorse elements, various prototypic material test elements were also installed in these channels.

A full complement of Avco-supplied current controls was installed. The aft power-take-off (PTO) region was resistively configured, and the forward PTO region was consolidated with an Avco-supplied current control portable unit.

Major CDIF plant support systems are shown in Figure 1. Compressed air, gaseous oxygen and nitrogen, fuel oil, pulverized coal, iron oxide/oil slurry, and dry seed are the process flow delivery systems. Medium pressure, deionized cooling water maintains the desired test train component temperature. The magnetic field is provided by a 2.9 tesla iron core magnet. Conversion of the dc to ac power, transmission to the commercial power grid, and variable generator loading are provided by an EPRI-supplied inverter.




FIGURE 1 -- CDIF TEST TRAIN SUPPORT SYSTEMS

Channel electrical configurations and measurements are achieved in the high voltage room, which contains the required numerous termination blocks and voltage/current transducers. A data acquisition system (DAS) records and stores over 2,000 measurements and calculated values each second (over 1,500 of these are electrical parameters). Since the combustor operates at a voltage potential of up to 10,000 volts, all process flows, cooling water, and instrumentation attachments must be electrically isolated to this level.

### TEST RESULTS

Programmatic and technical objectives have been met in the last year. From July 1990 through March 1991, 39 test starts occurred with a coal burn time of 93 hours 35 minutes and electrical power generation of 48 hours 53 minutes. Major test accomplishments are highlighted in Table 1.

Over the past year, the CDIF test program was designed to support the overall effort to acquire more and longer duration data to aid vendors responsible for designing the POC

hardware. Major technical accomplishments during the year were:

- completed testing of several designs and materials for POC channel design--testing of the final candidates continues;
- completed a duration thermal test to address long-term slagging effects in the combustor--21 hours 12 minutes in length; and
- completed current control checkout testing.

### Materials Testing

Potential prototypical materials, designs, and fabrication methods have been tested at the CDIF during the past year. These prototypic test elements have been installed in the nozzle and the combustor, but primarily in the channel. Various test elements have been installed in the anode, sidewalls, and cathode. The most notable test elements include a 0.7 pitch area of electrodes and sidewall elements. The anodes and cathodes in this region are of proposed prototypic design, and the sidewall is of prototypic Z-bar design (see Figures 2 and 3).

### Duration Testing

One of the goals for the FY90-91 test program was to accomplish steady state combustor testing and long duration power testing. Efforts were made to test for a 24-hour duration. Although a 24-hour test was not accomplished, a record continuous thermal test duration length was achieved. This record, 21 hours and 12 minutes, surpassed the previous continuous thermal operation of 12 hours and 50 minutes. This new record allowed assessment of long-term slagging effects in the combustor--primarily in the CFPC filler section. A post-test examination found the slag coverage to be heavy, with some buildup in the filler section.




FIGURE 2 -- 0.7 PITCH ELECTRODES AND SIDEWALL ELEMENTS




FIGURE 3 -- PROTOTYPIC Z-BAR COUPONS

### Current Control Checkout Testing

Original testing of the Avco-supplied current controls (CCs) in May 1990 resulted in the units being removed from service for further investigation. In August, the units along with diagnostic instrumentation were reinstalled to complete checkout testing. Instrumentation revealed that the line voltage feeding the CC cabinets sagged when all the facility equipment was brought on line. This condition resulted in a supply voltage that was too low, which caused the CC clock boards to malfunction. During the testing, correct CC operation was verified with an alternate power source from an isolated feeder. The CCs continued to be operated with the alternate power source until November 1990, when new clock boards with updated power transformers were installed. Once this upgrade was complete, the CCs operated successfully with regular facility power.

### TEST HARDWARE SUPPORT ACTIVITIES

During the last year, several test hardware activities in support of the test program have been accomplished. These activities, as agreed upon with the TRW and Avco vendor representatives, have included the following significant accomplishments.

- Completed the CFC modification as specified by TRW to enhance first stage reliability, test prototypic designs, and address the filler fouling potential.
- Continued a program of 1A, channel refurbishment, fabrication, assembly, and materials test element installation necessary to support testing at the CDIF.
- Completed installation and initiated checkout of the TRW-supplied slag rejection system.

- Continued the design, fabrication, and installation of the replacement diffuser sections.

### TRW Combustor Modifications

The smooth-wall air inlet filler section installed to reduce CFPC fouling was replaced with a hot-wall section to simulate the prototypic high pressure, high temperature cooling system (HPCS). Since the HPCS project was canceled and an alternate cooling method is being planned, the hot-wall section was replaced with a coupon filler section.

An Avco-supplied iron oxide injection frame to simulate prototypic iron oxide injection on the cathode wall of the channel was installed. Installation of a new head end plate and a replacement pintle were also completed.

### Channel Refurbishment, Fabrication, Assembly and Material Test Element Installation

On May 11, 1990, the materials test channel was placed into service. The channel contained wall sections 33, 34, 19, 20, 37, 30, 31, and 32. Because of an internal water leak in the cathode wall, the materials test channel was removed from service on May 22, 1990. The leak was caused by restricted cooling water flow to a bar element. The channel was repaired and reinstalled on June 8. It was again removed from test service June 22 because an electrical arc had burned the G-9 frame material near the midjoint.

After the channel was removed and inspected, it was discovered that the workhorse bars in the anode wall had markedly deteriorated after only 19 hours 16 minutes of test service. It was decided to install the material coupons in new anode wall sections 41 and 42. On July 31, 1990, testing resumed with a materials test channel that consisted of wall sections: 41\*, 42\*, 19\*, 20, 37, 30\*, 31, and 32\*.

During the October shutdown, the channel was dismantled, coupons were removed for evaluation, and repair/refurbishment activities on the channel were completed. Wall 63 (new) was installed during this shutdown as a replacement for wall 31. Some of the coupons previously used were reinstalled and some new ones were installed.

Following the November testing, the channel was removed because of a water leak on left forward sidewall 63. The channel was disassembled and inspected for wear. Refurbishment activities were started on wall sections 19, 20, 30, and 32. These wall sections were incorporated into the next channel, which was designated as Materials Test Channel II. In addition to the above mentioned wall sections, Materials Test Channel II also consisted of anode wall sections 57 and 50 and forward diagonal bar sidewalls 29 and 31. The anode wall sections contain many new prototypic designs, and the forward sidewalls contain elements of Z-bar wall prototypic design.

The assembly of these new and refurbished channel walls was completed; the channel was assembled and again installed into the test train. This channel contained all of the new Avco test bars and A-bar sections in the right and left forward sidewall sections. The channel consisted of wall sections 57\*, 50\*, 19, 20, 29\*, 30, 31\*, and 32.

\* Walls containing test coupons.

The channel was again removed when testing was shutdown because of a water leak in the magnet, after an accumulated 22 hours 30 minutes of electrical power generation. All anode and sidewall test bars were removed and shipped to Avco for evaluation and input into their Channel Design Review Update. All test bars shipped to Avco with the exception of several molybdenum Z-bars, were reinstalled into the materials test channel. This channel, which was installed for April-May 1991 testing, consisted of wall sections 49, 56, 19, 20, 29, 30, 31, and 32.

### **Slag Rejection System Installation and Checkout**

The TRW slag rejector consists of a slag grinder assembly, a dense phase pneumatic transport vessel, and an atmospheric collection tank with interconnecting valves and piping. The slag rejector project has been separated from the CDIF slag removal system, which is discussed in the Plant Support section of this paper. The two systems together provide batch removal and slag weighing from the TRW 50-MW, coal-fired combustor to support extended duration testing.

The hardware was installed in phases to minimize test interruption. During the past year, the slag grinder assembly, the dense phase pneumatic transport vessel, and the atmospheric collection tank with interconnecting valves and piping were installed. Between phases, the newly installed equipment was used as batch slag containers, in much the same as the previous equipment was used. This configuration was used during the November and January-February testing, without the electrical, instrumentation, and control portions. The electrical, instrumentation, and electrical portion of the slag rejection system was then installed during the March-April shutdown and checkout testing began in April 1991.

### **Replacement Diffuser Walls**

Until recently, the diffuser was made up of the original Avco-supplied diffuser walls with a few special purpose walls (i.e., triple port wall) added. The original diffuser walls had become warped, and reassembly of the diffuser was difficult. Therefore, MSE began to design and fabricate new diffuser walls. The new walls are being installed as they are completed and when test shutdowns occur. The fabrication of the aft subsonic and forward horizontal subsonic diffuser wall sections was completed, and they were installed into the diffuser. Replacement sections for the aft subsonic section are in progress.

## **PLANT SUPPORT SYSTEM ACTIVITIES**

Major improvements in plant system operation yielded longer duration tests and higher quality experimental data. Many plant activities improved system reliability while others satisfied changing requirements of the test program. For a more extensive overview of these activities, see Reference [2].

### **Coal System Improvements**

As the result of an external task force coal system review, eight coal-related projects were budgeted and scheduled. It is believed that implementing these projects will enhance the overall performance of the coal system. These projects

include reintroducing the coal fines into the system and replacing the scalping screen. An analysis and performance of a system mass balance are also planned. This analysis will quantify the performance of the coal system, especially through the pulverizer.

Designs for many of these modifications are in progress and are planned for installation on a noninterference basis with the test schedule.

### **Seed System Improvements**

A task force assessment of this system was completed. Some of the suggested modifications to the system included items such as placing a vertical plate in the conical section of the seed storage silo and replacing the silo outlet spool. Design work for many of these modifications is near completion, and field work is planned during the May-September 1991 shutdown. The seed storage silo must be empty to accomplish this work.

### **Solid Suspension Injection System**

The solid suspension injection system was designed to mix, store and inject slurry additives into the test train. The current slurry, a 50/50 by weight mixture of iron oxide and hydraulic oil is being added to mitigate the effects of erosion caused by interelectrode shorting.

Two new progressive cavity pumps have been installed as replacements/back up for existing diaphragm metering pumps. These pumps are being characterized. The iron oxide injectors, which have a concentric annulus nitrogen flow, still experience some plugging when configured with a single pump with split flow to two ports. The lower flow rates have been a difficult requirement to meet; therefore, new pumps for supplying lower flow rates have been ordered.

### **Stack Gas/Environmental Compliance Upgrade**

A new stack gas analysis facility and a compressed gas storage facility were designed and constructed. The upgrade provides permanent facilities for analyzing off gases at the CDIF during on-line operation. It also includes a modification to comply with the required safety standards for storing and dispensing compressed gases and to comply with the Environmental Protection Agency's and the State of Montana's need-to-know the actual stack emissions of nitrogen oxides (NO<sub>x</sub>), sulfur dioxides (SO<sub>2</sub>), and carbon monoxide (CO).

Work continues on analyzing the off gases for CO, CO<sub>2</sub>, and O<sub>2</sub> on a dry basis and SO<sub>2</sub>, CO, and NO<sub>x</sub> on a wet basis. A new H<sub>2</sub> analyzer is scheduled for installation.

### **New Data Acquisition System**

A new data acquisition system (DAS) to replace the existing system is scheduled for delivery to the CDIF in July 1, 1991. The system will arrive at the CDIF ready for installation and will include both hardware and software commensurate with the original system. This turnkey DAS will be installed, checked, and prepared for immediate use during September checkout testing.