

Journal Subline

LNBI 4780

Transactions on **Computational Systems Biology VIII**

Corrado Priami
Editor-in-Chief



Springer

Corrado Priami (Ed.)

Transactions on Computational Systems Biology VIII



Springer

Series Editors

Sorin Istrail, Brown University, Providence, RI, USA

Pavel Pevzner, University of California, San Diego, CA, USA

Michael Waterman, University of Southern California, Los Angeles, CA, USA

Editor-in-Chief

Corrado Priami

The Microsoft Research - University of Trento

Centre for Computational and Systems Biology

Piazza Mancini, 17, 38050 Povo (TN), Italy

E-mail: priami@dit.unitn.it

Library of Congress Control Number: 2007938331

CR Subject Classification (1998): J.3, F.1, F.4, I.6

LNCS Sublibrary: SL 8 – Bioinformatics

ISSN 1861-2075

ISBN-10 3-540-76638-3 Springer Berlin Heidelberg New York

ISBN-13 978-3-540-76638-4 Springer Berlin Heidelberg New York

This work is subject to copyright. All rights are reserved, whether the whole or part of the material is concerned, specifically the rights of translation, reprinting, re-use of illustrations, recitation, broadcasting, reproduction on microfilms or in any other way, and storage in data banks. Duplication of this publication or parts thereof is permitted only under the provisions of the German Copyright Law of September 9, 1965, in its current version, and permission for use must always be obtained from Springer. Violations are liable to prosecution under the German Copyright Law.

Springer is a part of Springer Science+Business Media

springer.com

© Springer-Verlag Berlin Heidelberg 2007

Printed in Germany

Typesetting: Camera-ready by author, data conversion by Scientific Publishing Services, Chennai, India

Printed on acid-free paper SPIN: 12187638 06/3180 5 4 3 2 1 0

Edited by S. Istrail, P. Pevzner, and M. Waterman

Editorial Board: A. Apostolico S. Brunak M. Gelfand
T. Lengauer S. Miyano G. Myers M.-F. Sagot D. Sankoff
R. Shamir T. Speed M. Vingron W. Wong

Subseries of Lecture Notes in Computer Science

Lecture Notes in Bioinformatics

- Vol. 4780: C. Priami (Ed.), Transactions on Computational Systems Biology VIII. VII, 103 pages. 2007.
- Vol. 4774: J.C. Rajapakse, B. Schmidt, G. Volkert (Eds.), Pattern Recognition in Bioinformatics. XVIII, 410 pages. 2007.
- Vol. 4751: G. Tesler, D. Durand (Eds.), Comparative Genomics. IX, 193 pages. 2007.
- Vol. 4695: M. Calder, S. Gilmore (Eds.), Computational Methods in Systems Biology. X, 249 pages. 2007.
- Vol. 4689: K. Li, X. Li, G.W. Irwin, G. He (Eds.), Life System Modeling and Simulation. XIX, 561 pages. 2007.
- Vol. 4645: R. Giancarlo, S. Hannenhalli (Eds.), Algorithms in Bioinformatics. XIII, 432 pages. 2007.
- Vol. 4643: M.-F. Sagot, M.E.M.T. Walter (Eds.), Advances in Bioinformatics and Computational Biology. XII, 177 pages. 2007.
- Vol. 4544: S. Cohen-Boulakia, V. Tannen (Eds.), Data Integration in the Life Sciences. XI, 282 pages. 2007.
- Vol. 4532: T. Ideker, V. Bafna (Eds.), Systems Biology and Computational Proteomics. IX, 131 pages. 2007.
- Vol. 4463: I.I. Măndoiu, A. Zelikovsky (Eds.), Bioinformatics Research and Applications. XV, 653 pages. 2007.
- Vol. 4453: T. Speed, H. Huang (Eds.), Research in Computational Molecular Biology. XVI, 550 pages. 2007.
- Vol. 4414: S. Hochreiter, R. Wagner (Eds.), Bioinformatics Research and Development. XVI, 482 pages. 2007.
- Vol. 4366: K. Tuyls, R.L. Westra, Y. Saeys, A. Nowé (Eds.), Knowledge Discovery and Emergent Complexity in Bioinformatics. IX, 183 pages. 2007.
- Vol. 4360: W. Dubitzky, A. Schuster, P.M.A. Sloot, M. Schröder, M. Romberg (Eds.), Distributed, High-Performance and Grid Computing in Computational Biology. X, 192 pages. 2007.
- Vol. 4345: N. Maglaveras, I. Chouvarda, V. Koutkias, R. Brause (Eds.), Biological and Medical Data Analysis. XIII, 496 pages. 2006.
- Vol. 4316: M.M. Dalkilic, S. Kim, J. Yang (Eds.), Data Mining and Bioinformatics. VIII, 197 pages. 2006.
- Vol. 4230: C. Priami, A. Ingólfssdóttir, B. Mishra, H. Riis Nielson (Eds.), Transactions on Computational Systems Biology VII. VII, 185 pages. 2006.
- Vol. 4220: C. Priami, G. Plotkin (Eds.), Transactions on Computational Systems Biology VI. VII, 247 pages. 2006.
- Vol. 4216: M. R. Berthold, R.C. Glen, I. Fischer (Eds.), Computational Life Sciences II. XIII, 269 pages. 2006.
- Vol. 4210: C. Priami (Ed.), Computational Methods in Systems Biology. X, 323 pages. 2006.
- Vol. 4205: G. Bourque, N. El-Mabrouk (Eds.), Comparative Genomics. X, 231 pages. 2006.
- Vol. 4175: P. Bücher, B.M.E. Moret (Eds.), Algorithms in Bioinformatics. XII, 402 pages. 2006.
- Vol. 4146: J.C. Rajapakse, L. Wong, R. Acharya (Eds.), Pattern Recognition in Bioinformatics. XIV, 186 pages. 2006.
- Vol. 4115: D.-S. Huang, K. Li, G.W. Irwin (Eds.), Computational Intelligence and Bioinformatics, Part III. XXI, 803 pages. 2006.
- Vol. 4075: U. Leser, F. Naumann, B. Eckman (Eds.), Data Integration in the Life Sciences. XI, 298 pages. 2006.
- Vol. 4070: C. Priami, X. Hu, Y. Pan, T.Y. Lin (Eds.), Transactions on Computational Systems Biology V. IX, 129 pages. 2006.
- Vol. 4023: E. Eskin, T. Ideker, B. Raphael, C. Workman (Eds.), Systems Biology and Regulatory Genomics. X, 259 pages. 2007.
- Vol. 3939: C. Priami, L. Cardelli, S. Emmott (Eds.), Transactions on Computational Systems Biology IV. VII, 141 pages. 2006.
- Vol. 3916: J. Li, Q. Yang, A.-H. Tan (Eds.), Data Mining for Biomedical Applications. VIII, 155 pages. 2006.
- Vol. 3909: A. Apostolico, C. Guerra, S. Istrail, P.A. Pevzner, M. Waterman (Eds.), Research in Computational Molecular Biology. XVII, 612 pages. 2006.
- Vol. 3886: E.G. Bremer, J. Hakenberg, E.-H.(S.) Han, D. Berrar, W. Dubitzky (Eds.), Knowledge Discovery in Life Science Literature. XIV, 147 pages. 2006.
- Vol. 3745: J.L. Oliveira, V. Maojo, F. Martín-Sánchez, A.S. Pereira (Eds.), Biological and Medical Data Analysis. XII, 422 pages. 2005.
- Vol. 3737: C. Priami, E. Merelli, P. Gonzalez, A. Omicini (Eds.), Transactions on Computational Systems Biology III. VII, 169 pages. 2005.
- Vol. 3695: M. R. Berthold, R.C. Glen, K. Diederichs, O. Kohlbacher, I. Fischer (Eds.), Computational Life Sciences. XI, 277 pages. 2005.
- Vol. 3692: R. Casadio, G. Myers (Eds.), Algorithms in Bioinformatics. X, 436 pages. 2005.
- Vol. 3680: C. Priami, A. Zelikovsky (Eds.), Transactions on Computational Systems Biology II. IX, 153 pages. 2005.
- Vol. 3678: A. McLysaght, D.H. Huson (Eds.), Comparative Genomics. VIII, 167 pages. 2005.
- Vol. 3615: B. Ludäscher, L. Raschid (Eds.), Data Integration in the Life Sciences. XII, 344 pages. 2005.

Vol. 3594: J.C. Setubal, S. Verjovski-Almeida (Eds.), *Advances in Bioinformatics and Computational Biology*. XIV, 258 pages. 2005.

Vol. 3500: S. Miyano, J. Mesirov, S. Kasif, S. Istrail, P.A. Pevzner, M. Waterman (Eds.), *Research in Computational Molecular Biology*. XVII, 632 pages. 2005.

Vol. 3388: J. Lagergren (Ed.), *Comparative Genomics*. VII, 133 pages. 2005.

Vol. 3380: C. Priami (Ed.), *Transactions on Computational Systems Biology I*. IX, 111 pages. 2005.

Vol. 3370: A. Konagaya, K. Satou (Eds.), *Grid Computing in Life Science*. X, 188 pages. 2005.

Vol. 3318: E. Eskin, C. Workman (Eds.), *Regulatory Genomics*. VII, 115 pages. 2005.

Vol. 3240: I. Jonassen, J. Kim (Eds.), *Algorithms in Bioinformatics*. IX, 476 pages. 2004.

Vol. 3082: V. Danos, V. Schachter (Eds.), *Computational Methods in Systems Biology*. IX, 280 pages. 2005.

Vol. 2994: E. Rahm (Ed.), *Data Integration in the Life Sciences*. X, 221 pages. 2004.

Vol. 2983: S. Istrail, M.S. Waterman, A. Clark (Eds.), *Computational Methods for SNPs and Haplotype Inference*. IX, 153 pages. 2004.

Vol. 2812: G. Benson, R.D.M. Page (Eds.), *Algorithms in Bioinformatics*. X, 528 pages. 2003.

Vol. 2666: C. Guerra, S. Istrail (Eds.), *Mathematical Methods for Protein Structure Analysis and Design*. XI, 157 pages. 2003.

Preface

This issue of the journal reports regular papers. The first contribution is by Falko Dressler and discusses self-organizing mechanisms in computer networks. The second contribution is by Preetam Ghosh, Samik Ghosh, Kalyan Basu and Sajal K. Das and deals with a stochastic event based simulation technique to estimate protein-ligand docking time. The third contribution is by Morteza Analoui and Shahram Jamali, and it deals with the interpretation of the Internet as a biological environment to study congestion phenomena. The fourth contribution is by Corrado Priami and it discusses how computational thinking in biology can be implemented through the use of process calculi. The last contribution is by Peter Saffrey, Ofer Margoninski, James Hetherington, Marta Varela-Rey, Sachie Yamaji, Anthony Finkelstein, David Bogle and Anne Warner and it deals with management information systems in biology. Finally we publish a corrected version of a paper by Ruet and Remy published in the previous volume of the journal.

July 2007

Corrado Priami

LNCS Transactions on Computational Systems Biology – Editorial Board

Corrado Priami,
Editor-in-chief
Charles Auffray

Matthew Bellgard
Soren Brunak
Luca Cardelli
Zhu Chen
Vincent Danos
Eytan Domany

Walter Fontana
Takashi Gojobori
Martijn A. Huynen

Marta Kwiatkowska
Doron Lancet
Pedro Mendes
Bud Mishra

Satoru Miayano
Denis Noble
Yi Pan
Alberto Policriti
Magali Roux-Rouquie
Vincent Schachter
Adeline Uhrmacher
Alfonso Valencia

University of Trento, Italy
Genexpress, CNRS and Pierre and Marie Curie
University, France
Murdoch University, Australia
Technical University of Denmark, Denmark
Microsoft Research Cambridge, UK
Shanghai Institute of Hematology, China
CNRS, University of Paris VII, France
Center for Systems Biology, Weizmann Institute,
Israel
Santa Fe Institute, USA
National Institute of Genetics, Japan
Center for Molecular and Biomolecular
Informatics, The Netherlands
University of Birmingham, UK
Crown Human Genome Center, Israel
Virginia Bioinformatics Institute, USA
Courant Institute and Cold Spring Harbor Lab,
USA
University of Tokyo, Japan
University of Oxford, UK
Georgia State University, USA
University of Udine, Italy
CNRS, Pasteur Institute, France
Genoscope, France
University of Rostock, Germany
Centro Nacional de Biotecnologia, Spain

Table of Contents

Bio-inspired Network-Centric Operation and Control for Sensor/Actuator Networks	1
<i>Falko Dressler</i>	
A Computationally Fast and Parametric Model to Estimate Protein-Ligand Docking Time for Stochastic Event Based Simulation ...	14
<i>Preetam Ghosh, Samik Ghosh, Kalyan Basu, and Sajal K. Das</i>	
Equation-Based Congestion Control in the Internet Biologic Environment	42
<i>Morteza Analoui and Shahram Jamali</i>	
Computational Thinking in Biology	63
<i>Corrado Priami</i>	
End-to-End Information Management for Systems Biology	77
<i>Peter Saffrey, Ofer Margoninski, James Hetherington, Marta Varela-Rey, Sachie Yamaji, Anthony Finkelstein, David Bogle, and Anne Warner</i>	
On Differentiation and Homeostatic Behaviours of Boolean Dynamical Systems (Corrected Version).....	92
<i>Élisabeth Remy and Paul Ruet</i>	
Author Index	103

Bio-inspired Network-Centric Operation and Control for Sensor/Actuator Networks

Falko Dressler

Autonomic Networking Group, Dept. of Computer Science 7,
University of Erlangen-Nuremberg, Germany
`dressler@informatik.uni-erlangen.de`,
<http://www7.informatik.uni-erlangen.de/~dressler/>

Abstract. Self-organization mechanisms have been investigated and developed to efficiently operate networked embedded systems. Special focus was given to wireless sensor networks (WSN) and sensor/actuator networks (SANET). Looking at the most pressing issues in such networks, the limited resources and the huge amount of interoperating nodes, the proposed solutions primarily intend to solve the scalability problems by reducing the overhead in data communication. Well-known examples are data-centric routing approaches and probabilistic techniques. In this paper, we intend to go one step further. We are about to also move the operation and control for WSN and SANET into the network. Inspired by the operation of complex biological systems such as the cellular information exchange, we propose a network-centric approach. Our method is based on three concepts: data-centric operation, specific reaction on received data, and simple local behavior control using a policy-based state machine. In summary, these mechanisms lead to an emergent system behavior that allows to control the operation of even large-scale sensor/actuator networks.

1 Introduction

In the communications area, there is a strong research focus on networked embedded systems because of their broad diversity in application domains. Especially, wireless sensor networks (WSN) have become popular for many applications. Similarly, there is a growing demand for sensor/actuator networks (SANET).

Sensor networks are composed of numerous small, independently operating sensor nodes [1]. Such sensors nodes are self-contained units consisting of a battery, radio communication, sensors, and some minimal amount of on board computing power. While the application scenarios are manifold [2], the operation of such WSNs is still challenging [3], basically due to the limited resources in terms of CPU power, storage, and, first of all, energy [4]. Within a WSN, nodes are thought to be deployed, to adapt to the environment, and to transmit data among themselves and/or to a given base station. The research topics include efficient communication in terms of resource consumption, reliability, and scalability [2, 5]. Because sensor nodes are usually battery operated, many efforts

have been made to develop energy-efficient algorithms and protocols for communication in WSNs [6].

Usually, WSNs are thought to be dynamic in terms of the current availability, i.e. they care about the potential removal and addition of sensor nodes. Dynamics in terms of mobility is concerned in sensor/actuator networks. Basically, SANETs consist of sensor networks that are enhanced by additional actuation facilities [3]. In most application scenarios, mobile robot systems are used as actuation facilities [7]. Nevertheless, we concentrate on general purpose actuation controlled by measures from corresponding sensor nodes. Therefore, the same network infrastructure is used for actuation control as well as for sensor data collection.

There are many application scenarios for WSNs and SANETs. The most popular examples include the service as first responders in emergency situations [8] and the supervision and control of challenging environments such as the monitoring of animals [9].

Operation and control of such networks is one of the most challenging issues. Typically, a central control loop is employed consisting of the following actions: measurement, transmission to a base station, (external) analysis, transmission to the actuation devices, actuation. Besides the increased network load, severe delays might be introduced. Driven by the limited resources, mechanisms for network self-organization have been proposed for higher scalability. Most of these approaches focus on efficient communication in WSNs, e.g. directed diffusion as a data-centric communication paradigm [10], and on stateless task allocation in SANETs [11]. Similar issues have been addressed in the artificial intelligence domain. Agent-based systems have been developed that enable an efficient distributed control in uncertain environments [12]. Nevertheless, there are still many unsolved issues such as predictability of an action, reliability of the communication, and boundaries for response times.

In this paper, we present and discuss an approach for *network-centric operation and control* in WSNs and SANETs that prevents the necessity of the described control loop or reduces the loop to a few neighboring nodes within the network, respectively. Inspired by the information handling in cell biology, we have built a rule-based system that allows to achieve all decisions within the network itself. There is no external control required. Nevertheless, we propose to allow such external intelligence for the handling of unexpected situations. The adaptive rule system has the inherent property of being self-learning by inducing new rules that match previously unknown situations. Therefore, our method provides at least limited control in a system showing an emergent behavior.

The network-centric control system allows to operate even in scenarios with the following challenging properties:

- Mobility of nodes – commonly it is believed that sensor networks being stationary, nowadays, mobility is a mayor concern
- Size of the network – much larger than in a infrastructure networks
- Density of deployment – very high, application domain dependent
- Energy constraints – much more stringent than in fixed or cellular networks, in certain cases the recharging of the energy source is impossible

The main contributions of the paper can be summarized as follows. An approach is presented that features localized data analysis and diffuse communication of measurement and computation results based on the content of the information instead of topology information and central management. We adapted signaling pathways known from cell biology to achieve an emergent behavior of the addressed complex system consisting of sensors and actuators. Using simple rules that are pre-programmed into network nodes, the network becomes able to solve aggregation or decision problems without having a global view to the behavior of the entire system.

The rest of the paper is organized as follows. Section 2 depicts the shifting paradigms to network-centric operation and control in massively distributed sensor/actuator networks. In section 3, the rule-based state machine for localized actuation control is explained. This description is followed by a discussion in section 4 and a conclusion in section 5.

2 Shifting Paradigms: Network-Centric Operation and Control

The objective of this paper is to discuss the potentials of network-centric control and operation in sensor/actuator networks. We developed a scheme based on three principles: data-centric operation, specific reaction on received data, and simple local behavior control using a policy-based state machine. We start with a high-level motivation for the presented approach, followed by a detailed description of the involved algorithms, and a discussion that is meant to be a starting point for further contemplation.

2.1 Need for Network-Centric Control

The coordination and control of sensor/actuator networks is still an emerging research area. Sensor networks have been enhanced by mobile robots. The resulting system is continuously examining the environment using sensors (measurement). The measurement data is transmitted to a (more or less) central system for further processing, e.g. optimizations using global state information. Then, the actuators are controlled by explicit commands that are finally executed (actuation). Basically, this scheme is usually used because the involved components (sensors, actuators) do not have resources that allow to cover the global state. The scheme is depicted in figure 1 (left). The measurement and the control loop are shown by corresponding arrows. Obviously, long transmission distances have to be bridged leading to unnecessarily high transmission delays as well as to a questionable communication overhead in the network, i.e. possible network congestion and energy wastage.

The favored behavior is shown in figure 1 (right). Self-organization methodologies are used to provide a network-centric actuation control, i.e. a processing of measurement data within the network and a direct interaction with associated, i.e. co-located actuators. How can we build a system that behaves in this fashion




Fig. 1. Operation and control of a SANET: centralized (left), network-centric (right)

and that shows the desired emergent behavior? We tried to adapt mechanisms as known from cell biology as described in the next section. The result is a data-centric message forwarding, aggregation, and processing. The key requirements can be summarized as follows:

- Self-organized operation without central control
- Allowance for centralized "helpers" and self-learning properties
- Reduced network utilization
- Accelerated response, i.e. in-time actuation

2.2 An Excursion to Nature - Cellular Signaling Pathways

The turn to nature for solutions to technological questions has brought us many unforeseen great concepts. This encouraging course seems to hold on for many aspects in technology. Many efforts were made in the area of computer technology employing mechanisms known from biological systems [13]. For this work, we concentrate on information transmission and reaction capabilities employed by signaling pathways for inter-cellular communication [14].

The focus of this section is to briefly introduce the information exchange in cellular environments and to extract the issues in computer networks that can be addressed by the utilization of these mechanisms [15,16]. Similar to the structure, the intercommunication within both systems is comparable [17,18]. Information exchange between cells, called signaling pathways, follows the same principles that are required by network nodes. A message is sent to a destination and transferred, possibly using multiple hops, to this target.

From a local point of view, the information transfer works as follows. The cell expresses a specific surface molecule, the receptor. In consequence this receptor is activated, e.g. by a change in its sterical or chemical conformation (phosphorylation of defined amino acids). The activated receptor molecule is able to further activate intracellular molecules resulting in a "domino effect". The principle is not as simple as described here. Many of these signaling pathways are interfering and interacting. Different signaling molecules are affecting the same pathway. Inhibitory pathways are interfering with the straightforward signal transduction. To sum up, the final effect is dependent on the strongest signal. The effect of




Fig. 2. Information exchange in the cellular environment

such a signal transduction pathway is mostly gene transcription, other possibilities are the reorganization of intracellular structure such as the cell cytoskeleton or the internalization and externalization in and out of the cell. Gene transcription means that the cell respond to incoming the signal by production of other factors which are then secreted (transported out of the cell), where it can induce signaling processes in the cell's direct environment. This process is depicted in a simplified manner in figure 2. A cell is shown with a single receptor that is able to receive a very specific signal, i.e. a protein, and to activate a signaling cascade which finally forms the cellular response.

This *specific response* is the key to information processing. It depends on the type of the signal and the state of the cells (which receptors have been built and which of them are already occupied by particular proteins). Finally, a specific cellular response is induced: either the local state is manipulated and/or a new messaging protein is created. The remote information exchange works analogue. Proteins, peptides, and steroids are used as information particles (hormones) between cells. A signal is released into the blood stream, the medium that carries it to distant cells and induces an answer in these cells which then passes on the information or can activate helper cells (e.g. the Renin-Angiotensin-Aldosteron system [19] and the immune system). The interesting property of this transmission is that the information itself addresses the destination. During differentiation a cell is programmed to express a subset of receptor in order to fulfill a specific function in the tissue. In consequence, hormones in the bloodstream affect only those cells expressing the correct receptor. This is the main reason for the specificity of cellular signal transduction. Of course, cells also express a variety of receptors which regulate the cellular metabolism, survival, and death.

The lessons to learn from biology are the efficient and, above all, the very specific response to a problem, the shortening of information pathways, and the possibility of directing each problem to the adequate helper component. Therefore, the adaptation of mechanisms from cell and molecular biology promises to enable a more efficient information exchange. Besides all the encouraging properties, bio-inspired techniques must be used carefully by modeling biological and technical systems and choosing only adequate solutions.

So, how to use the described methods to WSN and SANET operation and control? The biological model needs to be checked and - partially - adapted




Fig. 3. Architecture and behavior of a local node

to match the tasks in sensor/actuator networks. In the following section, we describe and discuss a solution for network-centric operation and control based on the described biological mechanisms.

3 Rule-Based State Machine for Localized Actuation Control

As already mentioned, three basic mechanisms are used to achieve the demanded goals:

- *Data-centric operation* – Each message carries all necessary information to allow the specific handling of the associated data.
- *Specific reaction on received data* – A rule-based programming scheme is used to describe specific actions to be taken after the reception of particular information fragments.
- *Simple local behavior control* – We do not intend to control the overall system but focus on the operation of the individual node instead (see discussion on emergent system behavior in section 4). We designed simple state machines that control each node whether sensor or actuator.

The complete scheme as adapted from cellular behavior is shown in figure 3. Even though the principles are described later, the general architecture and the behavior can be shortly explained. Depicted is a network node that has four directly connected neighbors (A, B, C, D). The local behavior is controlled by a state machine (π , σ) and a set of rules (RuleDB). In this example, a data message of type x is received and transformed locally into a message of type y . Finally, this message is distributed to all neighbors. (Remark: we consider wireless communication. Therefore, each message that a node sends is basically a broadcast to all neighboring nodes.)

3.1 Data-Centric Operation

Classically, communication in ad hoc networks is based on topology information, i.e. routing paths that have been set-up prior to any data exchange. Additionally, each node carries a unique address that is used to distinguish the desired

destination. We follow the approach used in typical data-centric communication schemes, e.g. directed diffusion [10], and replace topology information and addressing by data-centric operation. Each message is encoded as follows:

$$M := \{\text{type, region, confidence, content}\}$$

Using this description, we can encode measurement data as well as actuator information (type and content). Additionally, the region is included to distinguish messages from the local neighborhood from those that traveled over a long distance. Finally, the confidence value is used to evaluate the message in terms of importance or priority. Measures with a high confidence will have a stronger impact on calculations than those with a lower confidence. The confidence can be changed using aggregation schemes, i.e. two measures of the same value in the same region will lead to a higher confidence.

The following examples demonstrate the capabilities of the message encoding for data-centric operation:

- $\{\text{temperatureC}, [10,20], 0.6, 20\} ::$ A temperature of 20C was measured at the coordinates $[10,20]$. The confidence is 0.6, therefore, a low-quality sensor was employed.
- $\{\text{pictureJPG}, [10,30], 0.9, \text{"binary JPEG"}\} ::$ A picture was taken in format JPEG at the coordinates $[10,30]$.

3.2 Specific Reaction on Received Data

An extensible and flexible rule system is used to evaluate received messages and to provide the "programming" that specifies the cellular response. Even though the message handling in biological cells is more sophisticated, the basic principles including the processing instructions (the DNA) are modeled. Each rule consists of two parts: a number of input values and some output: $\text{INPUT} \rightarrow \text{OUTPUT}$. Therefore, typical rules could look like that:

- $A \rightarrow B ::$ message A is converted to message B
- $C \rightarrow \{\} ::$ message C is discarded
- $A \wedge B \rightarrow C ::$ if both messages A and B were received, a message C is created

Using all the other information available in each message, more complex rules can be derived:

- $A(\text{content} > 10) \rightarrow A(\text{confidence} := 0.9) ::$ if the measured value was larger than 10, a copy of A is created with confidence set to 0.9
- $A(\text{content} = x) \wedge A(\text{content} = y) \rightarrow A(\text{content} := x + y) ::$ two messages of type A are aggregated to a single one by adding their values

Again, an example is provided to reflect the capabilities of the data-centric operation:

- $\text{temperatureC}(\text{content} > 85) \rightarrow \text{alarmFire}(\text{confidence} := 0.8)$




Fig. 4. Simple state machines for sensors (S) and actuators (A)




Fig. 5. Rule interpreter with system input and output

3.3 Simple Local Behavior Control

The local behavior is controlled by simple state machines acting as sensors or actuators. Additionally, an interpreter is checking the installed rules to previously received messages. It uses a queuing subsystem that acts as a generic receptor for all messages and keeps them for a given time. This time control is necessary to prevent queue overflows due to received messages of unknown type. The basic state machines for sensing and transmitting data and receiving and acting on data for sensors and actuators, respectively, are shown in figure 4.

The rule interpreter and its queuing system are depicted in figure 5. Basically, this is the standard behavior of each communication system. Received messages are stored in a local database. After a given timeout, each message is dropped in order to keep the size of the database below a given threshold. Periodically, the rule interpreter compares all received messages against the programmed rule set. A matching rule terminates the search and the rule is applied.

3.4 Case Studies

Two case studies are provided in this section to elaborate the principles and the flexibility of the proposed network-centric operation and control method for sensor/actuator networks: first, data aggregation and emergency calls, and secondly, in-network actuation control. Both examples were also chosen in order to show the benefits of our approach compared to traditional WSN mechanisms.

Data aggregation and emergency calls. We consider a typical scenario for wireless sensor networks. Sensor nodes are distributed over a given area. All nodes are equipped with sensors measuring a particular physical phenomenon, e.g. the temperature. In order to obtain information about the territory, the measurement results are transported to a given sink that analyzes the received temperature information. Additionally, measures exceeding a given threshold represent