Proceedings of CRIOCM 2006 International Research Symposium on

of

Construction Management and Real Estate

VOLUME 1



Organizers:

The Chinese Research Institute of Construction Management

North China Electric Power University

Beijing, China 3rd- 5th Nov., 2006 Proceedings of CRIOCM 2006 International Research Symposium on

Advancement

of

Construction Management and Real Estate



Organizers:

The Chinese Research Institute of Construction Management

North China Electric Power University

Beijing, China 3rd - 5th Nov., 2006

Copyright © This Collection, The Hong Kong Polytechnic University, 2006

All rights reserved. No part of this publication may be reproduced or transmitted, in any form or by any means, electronic or mechanical, including photocopying, recording or any information

storage and retrieval system, without permission in writing from the publisher.

CRIOCM 2006 International Research Symposium on

Advancement of Construction Management and Real Estate

Beijing, China

3rd – 5th Nov., 2006

Proceedings

ISBN: 962-367-536-4

First Edition 2006

Printed in Hong Kong

Editors:

Zhen-yu ZHAO

Ming-xuan YU

Chang-chun FENG

Lin-ling DUAN

Published by

The Chinese Research Institute of Construction Management

North China Electric Power University

Information of The Chinese Research Institute of Construction Management:

Tel. +852-2766 5809

Fax. +852-2764 5131

http://www.bre.polyu.edu.hk/criocm

F 293.3-53
A 244 发常华南理工大学图书馆
2006
V.1
2006.11.66



CRIOCM2006 建设管理与房地产发展国际学术会议



二00六年十一月三日至五日

中国 北京



Organizing Committee

Chairman

Shen Li-Yin, President, The Chinese Research Institute of Construction Management

Executive Chairman

Qi Jian-Xun, School of Business Administration of North China Electric Power University

Vice-Chairmen

Michael Brown, The Chartered Institute of Building Chen Xiao-Tian, Management Department of National Natural Science Foundation of China

Niu Dong-Xiao, North China Electric Power University
Huang Wen-Jie, North China Electric Power University
Yu Ming-Xuan, The Chinese Research Institute of Construction
Management

Zhang Zhi-Hui, Tsinghua University

Gao Yong-Jun, No.7 Installation Branch of HaiMen Equipment Installation Co.Ltd.

Secretary-General

Wang Jia-Yuan, The Chinese Research Institute of Construction Management

Executive Secretary-General

Zhao Zhen-Yu, North China Electric Power University

Members (alphabetical order)

Feng Yi, China Architecture & Building Press
Li Chun-Jie, North China Electric Power University
Liu Rui, North China Electric Power University
Shen Yue-Hong, Journal of Construction Economy
Song Wei-Guo, Ministry of Science and Technology of China
Sun Zhong-Quan, North China Electric Power University
Wang You-Song, South China University of Technology
Wu Yu-Zhe, Zhejiang University
Wu Yun-Na, North China Electric Power University
Wu De-Hua, Yu Bei District Construction Committee of
Chongging

Yam C H Michael, The Hong Kong Polytechnic University Zhang Hong, Tsinhua University

Zhang Xi-Chen, North China Electric Power University

Zou Chong-Hua, Beijing-Hong Kong Academic Exchange Centre

Zou X W Patrick, The University of New South Wales, Australia

Secretariat

Zhao Er-Dong, North China Electric Power University Zhang Gui-Qin, North China Electric Power University Jiang Yi, North China Electric Power University Tan Yong-Tao, The Hong Kong Polytechnic University Duan Lin-Ling, North China Electric Power University

Advisory Committee (alphabetical order)

Baldwin A, The Hong Kong Polytechnic University
Liu Ji-Zhen, North China Electric Power University
Li Cheng-Rong, North China Electric Power University
Lai Ming, Ministry of Construction of China
Ning Yuan, the South-to-North Water Diversion Project
Commission of the State Council
Norman Fisher, University of Reading, UK

Ofori G, National University of Singapore Wang Zhong-Tuo, Dalian University of Technology Wu Hai-Yang, Land and Resources of China Yao Bing, Ministry of Construction of China

International Scientific Committee

Chairman

Feng Chang-Chun, Peking University Roger Richard, Universite de Montreal

Vice-Chairmen

Chai Qiang, China Institute of Real Estate Appraisers and Agents Edwin Chan Han-wing, CRIOCM
Chau K W, University of Hong Kong
Derek Drew, The Hong Kong Polytechnic University
Li Qi-Ming, SouthEast University
Ren Hong, Chongqing University
Wu Ci-Fang, Zhejiang University
Yi Bing-Yuan, Journal of Construction Economy
Yu Xiao-Fen, Zhejiang University of Technology
Zhang Wei, Management Department of National Natural Science
Foundation of China

Members (alphabetical order) Abdul Rashid A, University Sains Malaysia Best R, University of Technology, Sydney Cheng Hu, SouthEast University Chew Ah Seng David, Nanyang Technological University Devapriya K A, Bauhaus-University Weimar English J, University of Cape Town Fang Dong-Ping, Tsinghua University Fellows R, University of Hong Kong Griffith A, Sheffield Hallam University Hai Shan, Shenzhen Project Quality Management Department He Zhi, Shanghai LND Engineering Develoopment Hao Jian-Li Jane, The Hong Kong Polytechnic University Josephson P, Chalmers University of Technology Kwok C W Gilbert, Hong Kong Institute of Surveyors Langston C, Deaking University Liao Hong-Jian, Xi'an Jiaotong University Li Heng, The Hong Kong Polytechnic University Li Shi-Rong, Government of Shaping District of Chongqing Li Yi-Ping, University of Macau Liao Mei-Wei, University of Hong Kong Lin Jian, Peking University Lam T I Patrick, The Hong Kong Polytechnic University Liu Hong-Yu, Tsinghua University Liu Yi-Sheng, Beijing Jiaotong University Ogunlana S, Asian Institute of Technology Platten A, University of Central Lancashire Robinson J, The University of Melbourne Shah M N, India National Institute of Construction Management Research Shen Qi-Ping Geoffrey, The Hong Kong Polytechnic University Shi J, Illinois Institute of Technology

Shi J, Illinois Institute of Technology
Shi Qian, Tongji University
Skibniewski M J, University of Maryland
Skitmore M, Queensland University of Technology
Tam Chi Ming, City University of Hong Kong
Van Egmond E, Eindhoven University of Technology
Wang Yao-Wu, Harbin Institute of Technology
Wong K W Francis, The Hong Kong Polytechnic University
Xu Bao-Gen, Zhejiang University of Finance & Economics
Xu Bing, Shenzhen Tian'an Property Management Co., Ltd.
Yang Dong-Lang, Xi'an Jiaotong University
Yu Shi Ming, National University of Singapore

Table of Contents

Keynote Speeches

Industrialised, Flexible and Demountable Building Systems: Quality, Economy and Sustainability	1
Roger Bruno Richard	
Chinese Contractors and International Construction: Tentative Analytical Models and Research Agenda	11
George Ofori	
Some Ideas about the Float in Network Scheduling	24
Xing Mei LL, Jian Xun QI, Hong Mei YI	
Theoretical Developments of Construction Management and Real Estate	
Project Inception: a Performance Brief Approach	29
Jim Smith, Ray Wyatt	
A Dynamic Approach for Evaluating Infrastructure Projects' Sustainable Performance	39
Hong Yao, Jian Li Hao, Li Yin Shenkinhang Lee	
Measuring Performance within Swedish Construction Project Organisations: Learnings from Other Tools	51
Per Erik Josephson, Mikael Frödell, Alf Karlsson, Johnny Lindström	
Applying the "Living Building" Concept to Construction: a School Building Experiment	59
Hennes De Ridder, Ruben Vrijhoef	
Measuring Competition Intensity by Removal Techniques	69
Kun Hui Ye, Albert P. C. Chan	
Teaching Professional Ethics in Construction Management and Property	78
Sidney Newton	
Impact of Climate Change on Energy Uses and CO ₂ Emissions from Office Buildings in Australia	83
Lisa Guan	
A Sensor Based Intelligent Building Assessment Model	91
Derek Clements Croome, Min Wu, Shi Rong Li	
Construction Techniques of Innovative Housing Systems in Chinese Mainland	100
Yu Hong Pan, Francis K. W. Wong, Eddie C. M. Hui	
Application of Knowledge Management in Construction Enterprises	110
Chun Hui GE, An Yong HUANG	
The Theoretical Advantage of JIT Purchasing is Probably Overstated	117
Min WU, Yun ZHANG, Mao Zeng XU	

An Integrated Theory for Construction Project Logistics Management	122
Min WU, Mao Zeng XU, Gui Wen LIU	
An Investigation of Construction Waste Made in Mainland China	128
Jia Yuan WANG, Xiang Ping KANG, Vivian Wing Yan Tam	
The Geomorphological Agent of Land Price for the Formation of the Urban Man-Made Landform:a	
Case Study of Chongqing	138
Tao ZHOU, Xiao Long LI, Ping LV	
A Quantitative Approach for Customer Satisfaction Measurement of Real Estate Development Enterprise	144
Jin ZHANG, Dong Ming XU	
Research of the Innovative Development Pattern of REITs in China	149
Yan Chun ZHANG, Meng Jun WANG, Ping CHEN	
A Co-Integration Analysis of Relationship between Real Estate Investment and Economic Growth in China	156
Xi Jun WANG, Chuan Zhe LIU	
A Micro View on Public Land Granting, Land Price and Housing Price: a Hangzhou Study	162
Juan Er ZHENG, Ci Fang WU, Yang YANG	
Generational Difference and Employee Retaining ——Taking Construction Eneterprises in China	
Electric Power Industry as Examples	170
Er Dong ZHAO, Li Wei LIU	
Comparison and Analysis of Employee Motivation in Cross-Culture Project Management	177
Li Wei LIU, Er Dong ZHAO	
Integrated Management of the Construction Project During the Building Phase	184
Yun Na WU, Na YAO	
On-Site Sorting of Construction Waste in Mainland China —— a Survey Made in Shenzhen	191
Xiang Ping KANG, Jia Yuan WANG, Vivian Wing Yan Tam	
Failure Factors in Chinese Construction Enterprises Business and Management	200
Hong Mei YI, Zhen Yu ZHAO, Jian Xun QI	
Application Flexibility Strategy to Organizational Structure Design in China's International	
Construction Enterprises	210
Guang YANG, Wen Jie HUANG, Zhen Yu ZHAO	
A Cash Flow State Equation of Construction Project Based on Interim Payment Estimates	
and Its Applications	219
Mao Zeng XU, Min WU	
Neighborhood Characteristic and Housing Price: an Empirical Analysis Based on Hedonic Price Model	226
Dong YAN, Wei Wen ZHANG	

The Analysis of Fuzzy Integrated Evaluationin the Pfi Project's Risk Estimation	234
Jing DU	
Research on the Application of Quality Function Deployment Principle in Real Estate Development	241
Wan Li MA, Li Jun ZHOU	
The Study on Cost Approach in Real Estate Appraisal Based on Fuzzy Mathematics	248
Ping Ping CUI, Sheng Yue HAO	
Study on Valuation Techniques of Constructing Commodity Property	254
Chun Hong ZHI	
Research on Incentive Mechanisms of Building Construction Safety Management	259
Liang Feng SHEN	
Study on Bank Loan Monitoring Model for Real Estate Project	266
Fei XU, Shi Rong LI, Chao MAO	
The Need for Value Management in the Development Process of Construction Projects in China: a	
Systematic Perspective	275
Gui Wen LIU, Qiang LUO, Qi Ping SHEN, Min WU	
The Research on Three-Dimensional Structure Model of Generalized Project Risk Element Transmission	285
Cun Bin LI, Bin QU, Ke Cheng WANG	
Identification of Factors Influencing Communication Between Participants in Construction Projects	291
Yan LIU, Andrew N. Baldwin, L.Y. Shen	
Model Analysis of CPEAs' Core Competencies	300
Ming Xuan YU, Qin Yu YANG, Qiong WANG	
Envaluating Indicators for Project Management of Construction During Implementation Phase	311
Yun Na WU, Na ZHAO	
Morphogenetic Process of Quality Management in Construction Companies	319
Jin GONG, Shi Rong LI	
GIS-Based Evaluation on the Reconstruction of Urban-Villages —— Case Study of Guangzhou	325
Zhi Gang WU, Su Hong ZHOU, Rui Bo ZHOU, Chen CHEN	
Study on the Social Assessment Model of Engineering Projects	332
Xing Ping ZHANG, Xiu Cheng SU, Ling CHEN	
Decision-making and Optimization for Construction Project Investment	
An Empirical Study of the Relationship between Buildabilty and Productivity in Singapore –	
Lessons for Hong Kong SAR	338
Patrick T.I. Lam, Franky W.H. Wong	

Etamoination of Walter of Company its Salation for Land at the Company is a salation for Land	2.40
Etermination of Value of Opportunity Selection for Investment in Construction Project	348
Ying HAN, Chang Bin LIU, Ying Xing QI On the Financial Evaluation for the Covernment to the Private Enterpolice Investigation	
On the Financial Evaluation for the Government to the Private Enterprise Investing in	252
Highway Construction	352
Zhi Min DAI, Yan Fei SHI The Improvements of Applehouse's Consumer Location Model.	250
The Improvements of Applebaum's Consumer Location Model	359
Wei LI, Hong ZHANG	262
A New Method for the Decision-Making of Venture Capital in Real Estate Project Based on DEA Xiang LI, Min Quan XU, Jun CHU	363
	270
Study of the Investing Value of Board Area Dwelling Real Estate Applied in City of NanJing Zhi LI, Tao YAN, Jin Sheng WANG	370
Preliminary Approach Construction Project Appraising Method of Construction Enterprise	378
Jing Juan GUO, Yi Sheng LIU	370
Ant Colony Optimization Algorithm for Resource Leveling Problem of Construction Project	384
Ying XIONG, Ya Ping KUANG	304
Take PFI as a Method of Improving the Performance of the Investment on Infrastructure in China	392
Qi Lin SUN	392
Risk Allocation of Bot Project Based on the Optimal Risk Responding Strategies	401
De Xuan SUN, Li Ming YANG	401
Decision-Making Method for Low Voltage Power Network Construction Project	408
Shu Xia YANG, De Sheng LI, Chen Feng HUANG	
Analysis of the Method about the Project Investment Risk Decision Making	414
Ze Hong LI, Shu Jing XU, Li Ping YAN	
Selecting the Appropriate Project Delivery Modes Using Non-Structural Fuzzy Decision Method	422
Zhen Yu ZHAO, Rui LIU	.22
A Study on Project Social Assessment in China	428
Lin CHEN, Patrick X.W. Zou	
Multi-Objective Decision Making Based on the Satisfactory Degree and Range Order and Its	
Application in Investment Decision	438
Nan Sheng PANG, Ying Ling SHI, Cun Bin LI	
Research on Fuzzy-Grey Comprehensive Evaluation Method of Power Investment Project Risk	442
Ying Ling SHI, Nan Sheng PANG, Cun Bin LI	112
The Applications of Risk Analysis in the Comprehensive Evaluation of Construction Projects	448
Tong Tao MA, Cun Bin LI	770
0	

A Fundermental Research on the Inherent Defect Insurance in Chiha	454
Ying Bo JI, Gang ZHENG, Ning WANG	
Selection Method of Commodity Housing Project Based on VE and Multistage Fuzzy Evaluation	459
Long ZHAO, Yuan Sheng HUANG, Ning ZHANG, Lei YU	
IT Applications in Construction Management and Real Estate	
Application of Information Technology in Construction Management	467
Yan Ping FENG	
Research and Application of Data Mining Technology on Construction Project Cost Control System	471
Ying ZHOU, Lie Yun DING	
The Design of Intelligent Residence Property Management Information System Based on E-Business	477
Mei Feng WANG, Chao HAN	
Construction and Property Enterprises Management	
Private Residential Property Developers and The System of Land Use Planning Regulation in Nigeria	486
Anthony Egbu, Paul Olomolaiye, Rod Gameson	
Land Reform and Land Development in Shanghai's Transformation	496
Ya Wei CHEN, Gerard Wigmans, Hans De Jonge	
Studies on the Evaluation for Land Use Intensification of Industrial Land in Xi'An City	506
Li Hua XUE, Xiao Ming ZHANG	
The Research on the Intensivism and Stint use of the Public Establishment Terra in Xi'An	513
Dong Lang YANG, Bin HUA	
A Theoretical Model of Compensation Standard and Distribution of Land Value Increment in Land	
Requisition	520
Hai Jun BAO	
The Echoing of Residential Land Market Due to the Reform of Land Supply Policy in Beijing	525
Hong Jian DING, Li ZHONG	
The Application of GIS in Urban Land Price Monitoring	532
Yu Ting HOU	
Game Analysis on Institution Defects of Mode for Construction Land Supply in China Small Towns	539
Xiong OU. Ji Wen LIU. Jie JIN	

INDUSTRIALISED, FLEXIBLE AND DEMOUNTABLE BUILDING SYSTEMS: QUALITY, ECONOMY AND SUSTAINABILITY

Roger Bruno Richard School of Architecture, Université de Montréal, Montreal (Quebec) Canada

Abstract:Industrialised / Flexible / Demountable (IFD) Building Systems stand as key methods to achieve quality, economy and full sustainability in architecture: INDUSTRIALISED, to amortise a process capable of simplifying the production and reaching a high level of quality; FLEXIBLE, to accommodate functional changes over time and in the space without destroying partitions or/and exterior walls; and DEMOUNTABLE, to meet the needs for reconfiguration or even relocation without demolition. Factory-made components can easily incorporate the precise detailing required for an adaptable construction, as proposed by a series of building systems presently or prospectively available worldwide and as demonstrated by some prototypes already operational notably in the Netherlands and in Japan.

Keywords:Building Systems; Industrialised Strategies and Technologies; Adaptability; Sustainability; Quality; Joints and Jointing; Open Systems; Individualisation

1 Introduction

The idea of producing buildings along an assembly line has fascinated architects and engineers ever since the Fifties. However, even if most components and some sub-assemblies are actually industrialised in many countries, construction is still an expensive trade-oriented site-intensive handicraft activity.

The 21st Century is now observing a major backlash against that situation. In the United States, notably, many young architects are clearly saying "No" to the actual way of building and proposing instead the way cars, airplanes and ships are built: "We need a new vision of process, not just product... The world, and our clients, have seen what has been accomplished in other manufacturing fields: ships, airplanes and cars. Higher quality and added scope and features are there, along with lower cost and shorter time to fabricate. The old equilibrium between cost and time no longer holds. The mandate for change has now shifted to architecture. We cannot continue to build architecture at ever higher costs, longer schedules, and lower quality. We must act" (Kieran and Timberlake 2004).

Applied to architecture, the strategies and technologies of industrialisation can generate better buildings at a lower cost, offering quality architecture to the vast majority of people. There is a plus: the precision that goes with factory production can generate simple and demountable dry-joints. Dry joints are essential to achieve without any demolition the partial or total reconfiguration required to accommodate the unavoidable changes affecting all human activities.

The Netherlands are paving the way in that direction. They recently added the sustainability agenda to the adaptability approach developed in the early Seventies by Niklas Habraken (explained in section 5.2): the Dutch government is promoting the development of "Industrialised, Flexible and Demountable" Systems (IFD). The IFD approach is warmly embraced by a number of functionally oriented architects and construction managers in the Netherlands and in the European Union.

The purpose of this paper is to explore the application of that IFD approach to the various types of building systems presently or prospectively available worldwide.

2 Industrialisation

Industrialisation is a generic organization based on quantity and offering an individualised finished product (Richard 2005).

- (a) A generic organisation means grouping all the participants (manufacturers, assemblers, designers, managers, distributors, installers, etc.) into a continuous interaction, either as employees, sub-contractors or partners.
- (b) Based on quantity means aggregating a large market to feed the continuity and to amortize the investment in a process capable of simplifying the production (Richard 08.2005).
- (c) Offering an individualised finished product means addressing diversity through mass-customisation. Four strategies are available and frequently used by the other industries to generate individualisation within mass production: Flexibility of the Product, Flexibility of the Tool, Multipurpose Framework and Combinability (Richard 2006).

2.1 Industrialisation = Quality and Economy

Ideally, the large number of units to produce (quantity) distributes the cost of a process into very small fractions. In return, this process reduces the number of operations, simplifies them and brings more precision. The result is better quality at a lower cost, exactly like what happened in most of the other industries.

In Japan, industrialised housing production appeared a few decades ago: 3D modules and panels are factory-made on continuous assembly lines quite similar to the ones in the automobile industry and the outputs are easily customised. "All the assembly lines visited demonstrate the capacity to accommodate the requirements of each client through flexibility of the tooling and combinability, reaching a high level of mass customisation. Each manufactured house in Japan is designed and produced according to the buyers' needs and demands, while the design components are fully standardised or mass-produced" (Richard and Noguchi 2006). One of these industries, Sekisui Chemicals, allows not only the possibility of dismantling the units to upgrade the house, but also to recycle and even relocate them. Toyota's Housing Group is offering a "Super Skeleton & Intelligent Infill", where the infill can be modified to respond to changing lifestyles within a support structure that does not change.

The costs of Japanese manufactured houses are \pm 8% more than with traditional in situ constructions, but the quality is incomparably higher and the after-sale services a major asset.

2.2 Industrialisation = Sustainability

Industrialisation is a force that can be a partner to sustainability. Eight points are backing that statement: the first three are related to an economy of means, the next four to factory production and the last two to adaptability over time and space (subject of section 4).

- (1) The global organisation is feeding a continuous production using the same methods, knowledge and experience; instead of forming a new group for each new project (often with participants that have never worked together).
- (2) Simplified processes take over from the long sequential handicraft operations of traditional construction and thereby reduce the total energy involved in the project.
 - (3) Working inside a factory avoids loosing time over severe weather conditions.
- (4) Modular coordination, bulk purchasing and factory applied finishes reduce wastes by 40 to 100% in comparison with the traditional construction site (Tam et al 2006).
- (5) Factory conditions assure better quality control, thereby avoiding some unnoticed defects that require later repairs.
- (6) The precision that goes with factory production reduces the site assembly operations while keeping the construction site clean and free of debris.
- (7) Flexible components/sub-systems using dry-jointing methods allow for planning changes without the usual destruction of partitions associated with renovation.
- (8) Demountable components/sub-systems using dry-jointing methods allow for a major reconfiguration and/or relocation of the building without demolition waste.

3 Industrialised Building Systems

In an industrialised building industry, the products are not buildings but mainly Building Systems. A Building System is a set of parts and rules where the details are solved so as to generate many different and customized buildings (Richard, 2005). Therefore, the construction method is not re-invented each time a building is planned, as it is still the case with the traditional set of "working drawings".

An Industrialised Building System implies maximal factory production, leaving only the final assembly to be done at the site. Although, in some cases, the factory will be brought to the site as described in section 7.3-"I".

The main parts of the building system are its sub-systems, which generally correspond to the main functions of the building. A building system is usually composed of five sub-systems: STRUCTURE, ENVELOPE, PARTITIONS, SERVICES and EQUIPMENT.

Some components or sub-systems are often merged into a single element, in order to further simplify the operations while reducing the costs. For instance, a load-bearing sandwich panel might meet both structural and envelope criteria, a modular closet kit can provide a partition between two rooms of the same apartment when the appropriate soundproofing measures are taken, etc. Integration within the sub-systems is also a necessity, as each sub-system must also offer provisions to interface with the other sub-systems.




Figure 1 Integration within the sub-systems

Many systems do not include some sub-systems: either because a sub-system is outside their technological scope or to leave it to many options, in order for instance to be compatible to different environments. There is then an opportunity for many manufacturers to offer options and participate to the system, as long as their dimensions and their interfacing details are compatible: that is the realm of the "Open Systems".

An open system can exchange parts, components and even sub-systems outside its original production environment. They are then considered "interchangeable". Interchangeable parts, components and sub-systems are the constituents of an Open System. Open Systems are advantageous: they offer more choice to the user and a larger market to any manufacturer that abides by the rules in terms of quality (performance criteria), dimensions (modular coordination) and interfaces (compatibility). In the European Community, there is a large movement towards the exchange of products and components within an Open Systems agreement, a movement called ManuBuild: "The ManuBuild vision is of a future where customers will be able to purchase high quality, manufactured buildings having a high degree of design flexibility and at low cost compared to today. For the first time, inspirational unconstrained building design will be combined with highly efficient industrialised production..... ManuBuild targets a radical breakthrough from the current 'craft and resource-based construction' to 'Open Building Manufacturing', combining ultra-efficient (ambient) manufacturing in factories and on sites with an open system for products and components offering diversity of supply in the market" (ManuBuild 2006).

4 Industrialised, Flexible and Demountable (IFD) Systems

There is a constant need for change in each and every building: society and technology are in perpetual evolution whereas individuals are different from their neighbours and different from themselves over time. Very often a building program becomes obsolete even before the building is completed.

Industrialised Building Systems offer increased adaptability to change through the precise jointing features of the factory-made components or sub-systems. Since most factory-made components or sub-systems are designed to facilitate site installation, they can also be dismantled and generate change without any partial or total demolition, thereby addressing the sustainability agenda and contributing to the formation of Industrialised, Flexible and Demountable systems (Quah et al 2004).

4.1 Flexible Systems

A building system that can respond to changing living patterns will be considered "flexible": usually, all the sub-systems besides the Structure will be involved.

For instance, the bedrooms of young children are visually close to their parents whereas the contrary will be demanded when they become teenagers. Then, a flexible partition sub-system with provisions to integrate the wiring will allow for a new planning layout with the same components, without destroying gypsum board walls or having to "wet-tape" the joints.

Flexible systems generate "user friendly" buildings: freedom of choice for the first-use users, opportunity to modify the layout for successive users, evolution of the layout over space and time, individualisation and elimination of renovation waste.

4.2 Demountable Systems

A system capable of major reconfigurations or even of a complete dismantling for rebuilding somewhere else will be considered "Demountable". All the sub-systems will be involved, including the structure.

Demountable systems are generating "multi-lives" buildings that can be reconfigured to new functions or relocated elsewhere: their sub-systems are suited for worthwhile re-use and wasteful demolitions are eliminated.

5 Specificities of IFD Systems

Most Industrialised Building Systems presently or prospectively available worldwide are or could be made Flexible and Demountable; but at a different degree. Two conditions must be met: dry joints and adaptability framework.

5.1 Dry Joints

Dry-joints call for disciplined detailing. Structurally, those joints will most likely be bolted, although post-tensioned bars could be used but their dismantling is much more complex as the tension has to be progressively reduced to zero. The operations are quite easy with precast concrete as that material is offering fireproofing and soundproofing by definition; an easy-to-crush lightweight grouting should then be used to fill the connection nests. In the case of a steel structure, the simple solution would be embedding the components into a concrete overall, instead of the usual gypsum cladding or sprayed layers. For the exterior wall panels and the partitions sub-systems, the interfaces can be sealed with a "peel off" compound although many sub-systems will offer integrated gaskets. Dry connections can be expressed architecturally or concealed.

5.2 Adaptability framework

The SAR (Stichting Architecten Research) approach, developed by Niklas Habraken, is offering an appropriate framework to generate adaptability in architecture. It is based on a common denominator called "Support Structure" and allows for variations to accommodate the individual needs through the permutation of "Detachable Units" (Habraken 1976).

The "Support" would normally be limited to the structure, the collective circulations and the wet services main conduits. The building is completed with the "Detachable Units", which include the external envelope panels, the partitions and the service & equipment sub-systems. These Units can be interchangeable, available at building products outlets and in most cases installed by the occupants themselves.

The "Detachable Units" are governed by the "Support", which provides a series of served and serving zones together with intermediate margins that can be allocated to one or another zone. Strategic openings are available to accommodate growth or size reduction.

The SAR approach is now pursued by the "Open Building" movement, rallied under the Working Commission W-104 of the International Council for Research and Innovation in Building and Construction (CIB). The "Support" is called "Basic Building" by the CIB W-104 specialists (Kendall 2004) and most of the time they will include the external envelope within that designation, whereas the other "Detachable Units" are called "Infill".

6 Applying the IFD approach to the Nine Types of Building Systems

As buildings are site-related and as technology is normally factory-related, three basic building systems categories can be outlined. They are the basic colours (i.e. blue/red/yellow) from which the 9 types of building systems are generated (Richard 2005): the Site-Intensive KIT-OF-PARTS (A- Post & Beam, B-Slab & Column, C- Panels, D- Integrated Joint); the Factory-made 3D MODULE (E- Sectional Module, F-Box); the HYBRID (G- Load-Bearing Service Core, H- Megastructure, I- Site Mechanisation).

The following tables will describe how the 9 types of systems can be brought to be Industrialised, Flexible and Demountable (IFD). Each table will indicate the basic nature of each category and of each type within that category. For each type, the tables will summarize the specific INDUSTRIALISED strategies and technologies as well as the levels of FLEXIBILITY and DEMOUNTABILITY.

6.1 Site-Intensive KIT-OF-PARTS

In general, the Site-Intensive KIT-OF-PARTS with bolted dry joints offers appropriate ductility in earthquake situations and can serve low and mid-rise buildings, up to \pm 20 stories. To reach the high-rise status, three options are available: additional bracing, use of mechanical formwork to cast in situ walls and/or floors in order to obtain a monolithic structure or adding a vertical circulation core cast in situ with sliding formwork (see 7.3-"1").

Table 1 Applying the IFD approach to the Site-Intensive KIT-OF-PARTS

© Roger-Bruno Richard 2004		INDUSTRIALISED Strategies and Technologies	FLEXIBLE and DEMOUNTABLE Operations
I- Site-Intensive KIT-OF-PARTS ("Meccano")	All sub-systems are made at specialised plants and transported separately = important jointing operations at the site.	Distributing the tasks to a large number of available manufacturers = reduction of the initial capital investment	By definition, all the sub-systems can be relocated and demounted when dry joints are used.
A- POST & BEAM	Skeleton requesting horizontal and vertical infill	The frame acts as a connector to the infill panels	Adaptability on three axes
B- SLAB & COLUMN	Simplification through the introduction of a single horizontal element	Possible integration of the services within the structural slab	Adaptability on two axes
C- PANELS	Load-bearing flat components providing a linear distribution of the loads	Usually integrating the soundproofing and fireproofing performances	Adaptability limited to the structural bay
D- INTEGRATED JOINT	Monolithic component simplifying the connections by locating the joints outside the geometrical meeting point	Simple single axis interfacings and accelerated site assembly	Adaptability conditioned by the geometry of the structural sub-system

The NEXT-21 prototype in Osaka (Osaka Gas 2000), designed under the direction of Professor Yositika Utida, as well as the Nikkenkei Open Housing System (NOHS) prototype in Kugahara, designed by Dr Shin Okamoto, are two significant examples of IFD systems.



Figure 2 NEXT21 in Osaka

The components themselves can offer multiple choices, like the many modular holes present on a piece of the Meccano set. As demonstrated by projects like GenterStrasse (Kossak 1994) in Munich, designed by Otto Steidle, multiple-corbels columns can be combined with other off-the-shelf components to generate a full-fledge IFD system.

The Descon system, developed under the leadership of William F. Dawson and only non-US winner of Operation Breakthrough, is a very clever Open System in precast concrete, innovating and generating variations within the realm of available technology. Descon was inviting local and regional manufacturers to bid on the basis of three documents: performance criteria, modular coordination rules and interfacing details. "D/C has no manufacturing facilities for off-site production. All elements of the system are produced in existing local plants, as in the case of pre-stressed concrete, or in regional plants as in the case of bathrooms, kitchens, etc." (HUD 1973).

As the jointing of an Integrated Joint system is done away from the geometrical meeting point of the axes, only two parts are meeting each other at each joint. The best example of an Integrated Joint system would be Componoform (Componoform 2003): it is basically a joint-to-joint system, generating an open skeleton identical to the configuration of a Post & Beam system as far as the other sub-systems are concerned.