


ENSURE ENERGY EFFICIENCY OF HVAC SYSTEMS

by Fulin Wang

INFOC & LCCE



ENSURE ENERGY EFFICIENCY OF HVAC SYSTEMS

by Fulin Wang



上海科学普及出版社

图书在版编目 (CIP) 数据

建筑热空调系统的节能方法/王福林编著. —上海: 上海科学普及出版社,
2006. 4

ISBN 7-5427-3219-6

I. 建... II. 王... III. ①建筑—空气调节系统—系统设计②建筑—空
气调节系统—运行—管理 IV. TU831.3

中国版本图书馆 CIP 数据核字 (2005) 第 136959 号

责任编辑 林晓峰

ENSURE ENERGY EFFICIENCY OF HVAC SYSTEMS

by Fulin Wang

上海科学普及出版社出版发行
(上海中山北路 832 号 邮政编码 200070)

<http://www.pspsh.com>

各地新华书店经销 上海市崇明裕安印刷厂印刷

开本 787 × 1092 1/16 印张 10.5 字数 363000

2006 年 4 月第 1 版 2006 年 4 月第 1 次印刷

ISBN 7-5427-3219-6/TK · 4

定价: 28.00 元

Introduction to the author




Dr. Fulin Wang was born in Yantai China in 1971. He graduated from Wuhan Urban Construction Institute, now the east campus of Huazhong University of Science and Technology, and obtained the bachelor degree in 1993. After working as a HVAC design engineer in Yantai Design and Research Institute for five years, in 1998 Mr. Wang entered Tsinghua University and studied in the Department of Thermal Engineering under the direction of Professor Yi Jiang, and got his master degree in 2001. Soon after that Mr. Wang went to Japan to study in Professor Harunori Yoshida's laboratory in Department of Global Environment Engineering, Kyoto University, and received his Ph.D. in 2004. Then he works as an assistant professor in Kyoto University until now.

PREFACE

Energy efficiency is of fundamental importance to the human society because of the limited amount of the fossil fuel reserve on our planet and the great impact on the global environment. For this reason, a lot of research on improving energy efficiency has been launched in many fields. Approximately one third of primary energy is consumed in non-industrial buildings, such as dwellings, offices, hospitals, and schools, where it is used for space heating and cooling, lighting and the operation of appliances. Hence the efficient energy use in building sector is an important issue to be studied.

Our laboratory, the Laboratory of Sustainable Built Environment Engineering, contributes to the research on energy efficiency of buildings since its establishment. During 2001 to 2004, we took part in an internationally cooperated research project Annex 40, which is a research project committed under the International Energy Agency and is focused on commissioning of building Heating, Ventilation and Air-conditioning (HVAC) systems to improve energy performance. Mr. Fulin Wang took part in this research project and used the research results as a part of his doctoral dissertation and received his Ph.D. in 2004.

This book is written on the basis of Fulin's Ph.D. dissertation, which mainly consists of two parts. The first part discusses how to determine an energy efficient design scheme of buildings' HVAC systems from the view point of life cycle cost, which was carried out in Tsinghua University during his master course. The method ensures an energy efficient HVAC system to be designed from its very beginning. The second part proposes the methodology for automated commissioning of HVAC system for the purpose of ensuring the energy efficiency of HVAC systems during the operational phase, which was conducted in Kyoto University during his Ph.D. course. The method keeps HVAC systems run energy efficiently during the whole life cycle. Besides proposing the methodology to ensure energy efficient HVAC systems, this book also proposed mathematical models of several HVAC components, equipments and subsystems to achieve automated commissioning of HVAC system. An experimental study is also introduced on the feasibility of automating the commissioning process of a Variable Air Volume (VAV) HVAC system. I think this book could be a useful reference to the researchers in the field of building energy and HVAC system.



Harunori Yoshida

Professor at the Dept. of Urban and Environmental Engineering
Faculty of Engineering, Kyoto University, Japan

September, 2005

NOMENCLATURE

Roman symbols

A	Area (m^2)
A_c	Amount of chillers
a	Error of proportional band L_0
a_0, a_1, a_2, a_3, a_4	Fitted coefficients for the equation of C_h-C_f
b	Error of proportional band L_1
C_a	Influence coefficient of HVAC scheme to cost
C_{EV}	Flow rate coefficient of expansion valve
C_f	Dimensionless flow rate
C_h	Dimensionless pressure head
C_o	Influence coefficient of outside air supply scheme to cost
C_p	Specific heat (kJ/kg.k)
C_r	Dimensionless flow resistance
C_s	Influence coefficient of heating and cooling source scheme to cost
C_v	Valve resistance coefficient ($\text{kPa}/(\text{kg/s})^2$)
C_{v0}	Valve resistance coefficient when valve is full open ($\text{kPa}/(\text{kg/s})^2$)
CL	Total cooling load (kW)
CO_y	The cost in the y^{th} year, CO_0 is the initial investment cost
D	Diameter (m)
E	Energy consumption (kW)
EC	Electric power consumption (kW)
EP	Electric power price
e_0, e_1, e_2, e_3, e_4	Fitted coefficients for the equation of $\eta-C_f$
F	Frequency of power line (Hz)
f_0, f_1, f_2, f_3, f_4	Fitted coefficients for the equation of C_f-C_r
G	Bias when dead-band is considered ($^{\circ}\text{C}$)
GC	Gas consumption (m^3/s)
g	Dead-band of valve control bias ($^{\circ}\text{C}$)

g_e	Error of dead-band of valve control bias (°C)
g_o	Original dead-band of valve control bias (°C)
H	Heat produced by unit fuel (kJ/kg)
HHV	Higher heat value (kJ/Nm ³)
hr	A building's opening hours
I	Integral control output (%)
IIC	Initial investment cost (RMB, unit of Chinese currency)
INV	Invert output (%)
i	Numbering of equipments
in	Interest
i_0, i_1, i_2, i_3, i_4	Fitted coefficients for the equation of inverter efficiency equation
I_v	Valve capacity index (m ³ /h at 1 bar)
K	Coefficient of proportional action (1/°C)
L	Proportional band (°C)
L_0	Proportional band when inverter output is 0 (°C)
L_1	Proportional band when inverter output is 100 (°C)
LE	Length (m)
LF	Load factor
m	Mass flow rate (kg/s)
m_0, m_1, m_2, m_3, m_4	Fitted coefficients for the equation of motor efficiency
n	Life cycle (year)
N	Rotational speed (r/m)
O	Controller output for valve opening (%)
O_v	Valve relative opening
OC	Yearly operational cost (RMB/a)
P	Pressure (Pa)
PE	Price of energy
PF	Price of fuel
PH	Pressure head (Pa)
PI	Proportional-integral control output (%)
PO	Proportional control output (%)

Q	Cooling/heating production (kW)
R	Coefficient of flow resistance (Pa/(m ³ /h) ²)
r	Ratio
s	Iterative step
T	Temperature (°C)
t	Time (s)
t_o	Original integral time (s)
t_e	Error of integral time (s)
V	Volume flow rate (m ³ /h)
v	Velocity (m/s)
W	Weight vector for ADLINE neural network model
W_a	Air humidity ratio (g/kg dry air)
W_f	The weight of valve linear characteristic
X	Input vector for ADLINE neural network model
Z	Bias of supply air temperature to set point (°C)

Greek symbols

α	Learning speed for ADLINE neural network model
Δ	Difference
ε	Error between estimated value and expected value
η	Efficiency
λ	Leakage coefficient (closed flow/open flow at constant pressure)
ξ	Local loss coefficient
ρ	Density (kg/m ³)
τ	Time
ϕ	Relative humidity

Subscripts and superscripts

a	Air
atm	Atmosphere

<i>c</i>	Cooling
<i>cp</i>	Cooling plant
<i>d</i>	Demand valve
<i>dl</i>	Driveline
<i>dp</i>	Dew-point
<i>EV</i>	Expansion valve
<i>f</i>	Fan
<i>ft</i>	Filter
<i>h</i>	Heating
<i>i</i>	Inlet
<i>id</i>	Indoor
<i>inv</i>	Inverter
<i>k</i>	Numbering of training samples
<i>m</i>	Measured value
<i>mo</i>	Motor
<i>max</i>	Maximum value
<i>n</i>	Number
<i>nor</i>	Normal operational data
<i>o</i>	Outlet
<i>OC</i>	Coil etc. other components except filter and fan in the indoor unit of a room air-conditioner
<i>od</i>	Outdoor air
<i>off</i>	Offset operational
<i>r</i>	Rated value
<i>re</i>	Return air
<i>ref</i>	Refrigerant
<i>s</i>	Set point
<i>st</i>	Saturation
<i>su</i>	Summer
<i>t</i>	Total value
<i>ts</i>	Time step

<i>w</i>	Winter
<i>ww</i>	Water vapor
<i>1,2,3,4</i>	State points in a refrigeration cycle, defined in Figure 7.2

Abbreviations

ADLINE	Adaptive linear element
AHU	Air handling unit
BEMS	Building energy management system
CAV	Constant air volume
CMOAR	Constant minimum outside air rate
COP	Coefficient of performance
DeST	Designer's simulation toolkits
FCU	Fan coil unit
HHV	Higher heat value
HVAC	Heating ventilation and air conditioning
IIC	Initial investment cost
LCC	Life cycle cost
LCCE	Life cycle cost estimation
LMS	Least Mean Square
NFOC	No-fault operation comparison
OC	Operational cost
PI	Proportional and integral
RMB	Unit of Chinese currency
VAV	Variable air volume
VSD	Variable speed drive
VOAR	Variable outside air rate

ABSTRACT

ENSURING ENERGY EFFICIENCY OF HVAC SYSTEMS

Fulin Wang

The most important two aspects for energy efficiency and high performance of buildings' Heating Ventilation and Air-Conditioning (HVAC) systems are the selection of proper HVAC scheme at design phase and the maintenance of proper running of the HVAC system during operational phase.

For the purpose of selecting a proper HVAC scheme, Life Cycle Cost (LCC) is a good criterion to make the decision of HVAC scheme selection at design phase. This book proposes the concept of estimating the Life Cycle Cost of a HVAC system stage-by-stage corresponding to the design progress of the HVAC system, which is gradually specified stage by stage. This book divides the economic estimation of HVAC systems into four stages: beginning of design, conceptual design, preliminary design, and detailed design. The Life Cycle Cost Estimation (LCCE) methods suitable for different design stages are analyzed and proposed. At the beginning of design stage, because there is little information that can be used to estimate the economic character of HVAC systems, neural network models are built to estimate the economic parameters of HVAC systems. At conceptual design stage, different HVAC system scheme are simulated to compare how they satisfy the demand of air conditioning. The simulation results are used to estimate the economic value of the HVAC Schemes. At preliminary design stage, parts of the HVAC systems are simulated and compared and some detailed information about the HVAC equipment can be obtained and used to accurately calculate the costs. The unknown information of the HVAC systems is estimated to calculate their economic values. At detailed design stage, every part of the HVAC systems is simulated. Accurate calculation methods are analyzed according to the detailed design information.

For the operational phase, the on-going commissioning is considered to be the method that can maintain the high performance of a HVAC system. This book proposes an on-going commissioning methodology of No-Fault Operation Comparison (NFOC). The no-fault operation data of a HVAC system can be obtained from simulation or past no-fault operational data records. The data obtained from the simulation using the design conditions represent the no-fault performance. The simulation analysis realizes on-going commissioning through continuously comparing the HVAC sys-

tems real-time operational data with simulated data. This approach suits for the air or water processing components or subsystems, such as fan subsystems, valves, VAV boxes, and coils etc., whose processing results or outputs can be both simulated and measured. Past no-fault operation that are under the almost same heat conditions as current operation can be used to continuously compare with the real-time current operation during operational phase to check whether current operation has faults or not. This approach suits for commissioning components whose simulation models are not suitable for commissioning, such as temperature sensors, air flow rate sensors etc.

The main new points of this book can be summarized as follows:

- 1) Develops a methodology for determining an optimal HVAC scheme from valid candidates using Life Cycle Cost Estimation at design stages.
- 2) Gives different economic estimation methods suitable for different design stages corresponding to the characteristics of different design stages: neural network method for the beginning of design and empirical estimations for conceptual design, preliminary design and detailed cost calculation method for detailed design phase.
- 3) Proposes the No-Fault Operation Comparison methodology for on-going commissioning of HVAC systems during operational phase through comparing real-time operational data with no-fault operational data that are obtained from simulation and past no-fault operational data records.
- 4) Develops a total energy consumption model of fan subsystems that can estimate the measurement-easy total energy consumption of fan subsystems and is suitable for on-going commissioning.
- 5) Experimentally studies the on-going commissioning characteristics of a real VAV system. The experimental study reveals the feasibility of automated on-going commissioning of HVAC systems through comparing real time operational data with no-fault operational data obtained from simulation or past no-fault operational data records.
- 6) Develops a filter resistance estimation model that can estimate filter resistance without pressure sensor only using thermal or energy performance data of air-conditioners and is suitable for on-going commissioning filters in room air-conditioners.

Keywords: HVAC, Design, Life cycle cost, Commissioning, Operation, Energy efficiency

CONTENTS

CONTENTS	i
LIST OF TABLES	vi
LIST OF FIGURES	vii
NOMENCLATURE	xi
ABSTRACT	xvii
INTRODUCTION	1
0.1 Background	1
0.2 Objectives	2
0.3 Structure	2
0.3.1 Part 1: design phase	2
0.3.2 Part 2: operational phase	3
 CHAPTER 1	
LIFE CYCLE COST ESTIMATION METHOD FOR HVAC	
SYSTEMS AT DESIGN PHASE	9
1.1 Concept	9
1.2 Methodology	11
 CHAPTER 2	
LIFE CYCLE COST ESTIMATION USING NEURAL NETWORK	
AT BEGINNING OF DESIGN	15
2.1 Introduction	15
2.2 Influence factors	16
2.3 Sensitivity analysis	17
2.3.1 Sensitivity analysis of initial investment cost	17
2.3.2 Sensitivity analysis of operational cost	19
2.4 Cost estimation	19
2.4.1 Selection of neural network model	20
2.4.2 Training of neural network model	22
2.4.3 Estimation using neural network model	31
2.5 Summary	33

CHAPTER 3

LIFE CYCLE COST ESTIMATION FOR THE OTHER THREE

DESIGN STAGES	35
3.1 Introduction	35
3.2 Conceptual design stage	35
3.2.1 Influence factors	35
3.2.2 Sensitivity analysis	36
3.2.2.1 Sensitivity analysis of initial investment cost	36
3.2.2.2 Sensitivity analysis of operational cost	37
3.2.3 Cost estimation	39
3.2.3.1 Estimation of initial investment cost	39
3.2.3.2 Estimation of operational cost	39
3.3 Preliminary design stage	40
3.3.1 Cost estimation of terminal systems	40
3.3.1.1 Initial investment cost	40
3.3.1.2 Operational cost	43
3.3.2 Cost estimation of heating/cooling source systems	43
3.3.2.1 Initial investment cost	43
3.3.2.2 Operational cost	45
3.4 Detailed design stage	46
3.4.1 Initial investment cost	46
3.4.2 Operational cost	47
3.5 Summary	47

CHAPTER 4

ON-GOING COMMISSIONING METHODOLOGY FOR

OPERATIONAL PHASE	51
4.1 Introduction	51
4.2 Introduction to commissioning	51
4.2.1 Definition of commissioning	51
4.2.2 Historical development of commissioning	53
4.2.3 Current research on building commissioning	54
4.3 On-going commissioning methodology	55
4.3.1 Simulation comparison approach	58

4.3.1.1 Coil	58
4.3.1.2 Valve and damper	59
4.3.1.3 VAV box	63
4.3.1.4 Fan subsystem	63
4.3.2 No-fault operational data comparison approach	66
4.3.2.1 Malfunctioning supply air temperature sensor	67
4.3.2.2 Malfunctioning room air temperature sensor	69
4.4 Summary	71

CHAPTER 5

TOTAL ENERGY CONSUMPTION MODEL OF FAN SUBSYSTEM

SUITABLE FOR ON-GOING COMMISSIONING	73
5.1 Introduction	73
5.2 Models	73
5.2.1 Fan efficiency model	77
5.2.2 Driveline efficiency	79
5.2.3 Motor efficiency	79
5.2.4 Inverter efficiency	81
5.3 Model parameters, inputs, and output	82
5.3.1 Parameters	82
5.3.2 Inputs	83
5.3.3 Output	83
5.4 Experimental validation	83
5.4.1 Validation using normal fan subsystem	84
5.4.1.1 Coefficients fitting for fan model	85
5.4.1.2 Coefficients fitting for motor model	87
5.4.1.3 Coefficients fitting for inverter model	88
5.5 Application for automated on-going commissioning	90
5.6 Application case study	91
5.7 Summary	94

CHAPTER 6

EXPERIMENT STUDY ON THE ON-GOING COMMISSIONING

OF A REAL VAV SYSTEM.....	97
6.1 Introduction.....	97

6.2 Low efficiency fan subsystem	100
6.2.1 Experimental method	100
6.2.2 Results, discussion and conclusions	103
6.3 Malfunctioning supply air and room air temperature sensor	104
6.3.1 Experimental method	104
6.3.2 Results, discussion and conclusions	105
6.4 Stuck AHU outdoor air damper	106
6.4.1 Experimental method	106
6.4.2 Results, discussion and conclusions	106
6.5 Stuck AHU water valve	108
6.5.1 Experimental method	108
6.5.2 Results, discussion and conclusions	108
6.6 Summary	108

CHAPTER 7

MODEL-BASED COMMISSIONING FOR FILTERS IN ROOM AIR-CONDITIONERS

7.1 Introduction	111
7.2 Models	113
7.2.1 Estimation using fan energy consumption data	116
7.2.2 Estimation using thermal performance data	116
7.3 Model parameters, inputs, and output	123
7.3.1 Parameters	123
7.3.2 Inputs	123
7.3.3 Output	124
7.4 Model validation	124
7.4.1 Validation results of estimating using fan power consumption data	129
7.4.2 Validation results of estimating using thermal performance data	129
7.5 Model-based commissioning methodology	132
7.6 Summary	133

CHAPTER 8

CONCLUSIONS

8.1 Efficiency should be ensured from very beginning using economic estimation method at design phase	135
---	-----

8.1.1 Neural network method suits for economic estimation at beginning of design.....	135
8.1.2 Empirical equations suit for economic estimation at other design stages	136
8.2 No-fault operation comparison methodology for operational phase ensures system efficiency during whole life cycle	136
8.2.1 Simulation using suitable models automates on-going commissioning	136
8.2.2 Past no-fault operational data records suits for continuously commissioning sensors	137
8.3 Summary	137
REFERENCES	139